

# 7013D120 ASSEMBLY INSTRUCTIONS

Please read carefully and save these instructions, as you may need them later. **CAUTION!**

Turn off the main power at circuit breaker before installing the fixture, in order to prevent possible shock. All glass is fragile, use care when handling . The important safeguards and instructions appearing in this manual are not meant to cover all possible conditions and situations that may occur. It must be understood that common sense, caution, and care are factors which cannot be built into any product.

These factors must be applied by the person(s) caring for and operating the fixture.

Power connection to be made by qualified personnel in accordance with the National Electrical Code. Please connect power according to the table below.

## Fixture Conductor Marking

"L" Live Conductor [Black or Brown]

"N" Neutral Conductor [White or Blue]

" $\perp$ " Ground Conductor [ Green or Bare]

## Connect to AC Power Conductors

"L" Line Voltage Conductor[Black]

"N" Neutral Conductor [White]

" $\perp$ " Ground Conductor [Green or Bare]

## Installation instructions:

- 1.Black wire from ceiling (junction box) attaches to "L" wire for the fixture by terminal nut(D) ;white wire attaches to "N" wire by terminal nut(D); " $\perp$ " wire from the fixture is attached to the monuting bracket (B) and an additional " $\perp$ " wire form the monuting bracket (B) must to secured to the junction box by terminal nut(D).
- 2.Use the screw(E) secure mounting bracket(B) to the junction box.
- 3-Use the screw(F) secure the canopy(A) to the mounting bracket(B).
- 4-Put the bulbs(H) and crystals (G) on the fixture .
- 5-Use scissors to cut the tape holding the crystal.
6. Adjust the wire and cord to the height you want.

