

BRIGHT, BOLD FLUORESCENT COLOR GLOWS UNDER BLACKLIGHT • LOW ODOR

From the inventors of fluorescent color, DayGlo Screamin' Fluorescent Paint is a premium, low odor fluorescent water-based paint. Use with DayGlo Filteray® W Clear Overcoat for maximum lightfastness and film integrity (DayGlo Filteray® W is not recommended for interior use where exposed to black light—fluorescent surfaces coated with DayGlo Filteray® W will not fluoresce in the dark under black light).

DayGlo Screamin' Fluorescent Paint can be used anywhere that requires the end product to be seen—theatrical special effects, graphic arts, safety, hobby, sports, and more! The results are only limited by your imagination!

General Application Instructions:

DayGlo Screamin' Fluorescent Paints are semi-transparent and, therefore, brightest when applied over a clean, white surface. White semi-gloss latex coatings, flat white latex undercoats, water-based primer-sealers and water-based block-out whites are ideally suited for this purpose. Over old finishes, clean and sand before applying a white undercoat or primer that offers good adhesion to both the old finish and new DayGlo Screamin' Fluorescent Paint. However, the best performance can be achieved by removing old finishes and starting with a freshly primed surface.

1. Stir well. If thinning is necessary, use water. (AVOID OVER THINNING).
2. Apply one moderate coat of DayGlo Screamin' Fluorescent Paint with a soft brush. Use short strokes. Cover completely and smooth out as you go to produce a uniform deep layer. Thin spots or streaks will fade prematurely. Allow to set-up or "top dry" for at least 10 minutes (at 70° F).
3. Apply the second coat the same as the first. Allow 3 hours to dry before applying DayGlo Filteray® W Clear Overcoat (fluorescent surfaces coated with DayGlo Filteray® W will not fluoresce in the dark under black light).
4. For sign applications, DayGlo Screamin' Fluorescent Paint can simply be roughed in, slightly overlapping the copy line. Your copy line will not be hidden because DayGlo Screamin' Fluorescent Paint is semi-transparent. Do not try to work the paint exactly to a line. An opaque background should be used to cut in accurately to the copy line for sharp detail after DayGlo Screamin' Fluorescent Paint has top dried for 24 hours.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

CAUTION: KEEP OUT OF REACH OF CHILDREN. PROTECT FROM FREEZING. WARNING: MAY BE HARMFUL IF SWALLOWED.
CONTAINS: BASIC VIOLET 11:1

PRECAUTIONS: Avoid skin and eye contact. Wash hands immediately after use. When using, use impermeable work gloves. Wear a work apron. Do not take internally. If swallowed, get medical attention immediately. MAY CAUSE EYE AND SKIN IRRITATION. Use only with adequate ventilation. Do not breathe dust, vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use. Close container after each use.

FIRST AID: If you experience difficulty in breathing, leave area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes; get medical attention. For emergency, call your physician, local poison control center or local emergency room. For product health information, call 1-800-424-9300.

Disclaimer: Our technical advice, information and statements—given verbally, in writing or in the form of test results—is offered for your guidance without warranty. **NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE IS MADE.** This also applies where protective rights of third parties are involved. It does not release the user from the obligation to test the suitability of the products and formulas for the intended process and applications. Our guarantee is limited to the consistent quality of our products.

CALIFORNIA PROP 65: This product contains components known to the state of California to cause cancer: Cumene (98-82-8) and Ethylbenzene (100-41-4) and birth defects or other reproductive harm: Toluene (108-88-3).



DayGlo

DayGlo Color Corp.
4515 St. Clair Avenue
Cleveland OH 44103 USA
(216) 391-7070 www.DayGlo.com

