ENGAGE CABLE & ACCESSORIES



The Engage Cable is a continuous length of 12AWG cable with pre-installed connectors for Enphase Microinverters to plug into. The cable is handled like standard outdoor-rated electrical wire, allowing it to be cut, spliced and extended as needed.

The Engage Accessories complement the Engage Cable and give it the ability to adapt to any installation.



FAST - Quick installation - Large branch capacity

FLEXIBLE - Simple design - No additional cables

> **SAFE** - No high voltage DC - Reduced fire risk



CABLING ACCESSORIES - DETAILS and SPECIFICATIONS

Portrait

Portrait

Landscape

Landscape

IFC.

Cable Types

Voltage 240VAC, 4 conductors 240VAC, 4 conductors 208VAC, 5 conductors 208VAC, 5 conductors **Connector Spacing** 1.025 meter (40") 1.7 meter (67") 1.025 meter (40") 1.7 meter (67")

Accommodates PV module orientation

Cable Length Options*



Cable Specifications

Description	Rating	
Cable temperature rating	90°C (194°F) wet/dry	
Cable insulator rating	THWN-2	
UV exposure rating	UL 746 C, F1	
Conductor gauge	12AWG	
Compliance	UL1741; CAN/CSA C22.2 Nos. 0, 21, 42, 65, 153, 182.1, 182.2, and 182.3; IE4 60529 IP67	


Model Number	Orientation	# Connectors	Approx weight
ET10-240-40	Portrait	40	40 lbs
ET17-240-40	Landscape	40	45 lbs
ET10-208-30	Portrait	30	30 lbs
ET17-208-30	Landscape	30	35 lbs

*additional lengths available through Enphase authorized distributors.

Engage Accessories



Branch Terminator One terminator needed per branch circuit ET-TERM-10 (quantity 10)



Disconnect tool Plan to use at least one per installation ET-DISC-05 (quantity 5)



Watertight sealing cap One needed to cover each unused connector on the cabling. ET-SEAL-10 (quantity 10)



Cable clip

Many needed to fasten cabling to the racking or to secure looped cabling. ET-CLIP-100 (quantity 100)

142-00013 Rev 01

Enphase Energy, Inc. 201 1st Street Petaluma, CA 94952 Phone: 877-797-4743 Fax: 707-763-0784 info@enphaseenergy.com http://www.enphase.com