

BHI Ductless Mini Split - Dimension Guide

			12K BTU	18K BTU
Rated Cooling (95F/35C)	Rated cooling capacity	Btu/h	12000	18000
	EER2	Btu/W.h	9.5	9.5
	SEER2	Btu/W.h	19	18
Rated Heating	Rated Heating capacity(47F/8.3C)	Btu/h	12000	18000
	Rated Heating capacity(17F/-8.3C)	Btu/h	6800	9700
	Max.Heating capacity(19F/-7C)	Btu/h	-	-
	Max.Heating capacity(5F/-15C)	Btu/h	-	-
	HSPF2 (Region IV)	Btu/W.h	8	8
	HSPF2 (Region V)	Btu/W.h	-	-
	COP2	W/W	10	10
	COP(5F/-15°C)	W/W	-	-
Rated Input Consumption	Cooling	W	1262	1897
	Heating	W	1194	1789
Rated Current	Cooling	W	11.2	8.8
	Heating	W	10.6	8.3
Min. Circuit Ampacity		A	Indoor:1,Outdoor:19.2	Indoor:0.81,Outdoor:16.45
MXimum Fuse Size		A	Indoor:15,Outdoor:30	Indoor:15,Outdoor:25
MXimum Operation Pressure		PSIG	609	609
Moisture removal		Liters/h	1.3	1.9
Unit Dimension	Indoor Unit (WHD)	Inch	31.69 x 10.63 x 7.87	40.35 x 12.6 x 8.9
	Outdoor Unit (WHD)	Inch	30.71 x 22.05 x 10.63	30.71 x 22.05 x 10.63
Box Dimension	Indoor Box (WHD)	Inch	34.02 x 13.03 x 10.43	43.39 x 15.55 x 12.01
	Outdoor Box (WHD)	Inch	35.04 x 24.41 x 14.17	35.04 x 24.41 x 14.17
Weight	Indoor Unit	Lbs	17.64	27.56
	Outdoor Unit	Lbs	71.65	71.65
	Indoor Box	Lbs	22.05	33.07
	Outdoor Box	Lbs	77.16	77.16