

L-Angle

2" x 2" standard L-Angle

A standard 10'-0" long galvanized steel product, which is often field cut to job site conditions for the ultimate use as a connector for framing members. On interior framing it is often used to secure drywall at corner intersections or along horizontal planes. It can also be used as a half track in chase and furred walls.

Product Data & Ordering Information:

Material: All Non-Structural Material: Grade 33ksi min. yield strength
 18mils: 25 Gauge, 0.0188" Design Thickness, 0.0179" Min. Thickness
 30mils: 20ga DW, 0.0312" Design Thickness, 0.0296" Min. Thickness
 Coating: G40EQ (G40 or G60 available)

All Structural Material: Grade 33ksi min. yield strength
 33mils: 20ga STR, 0.0346" Design Thickness, 0.0329" Min. Thickness
 43mils: 18 Gauge, 0.0451" Design Thickness, 0.0428" Min. Thickness
 54mils: 16 Gauge, 0.0566" Design Thickness, 0.0538" Min. Thickness
 68mils: 14 Gauge, 0.0713" Design Thickness, 0.0677" Min. Thickness
 97mils: 12 Gauge, 0.1017" Design Thickness, 0.0966" Min. Thickness
 Coating: CP60 (G90 available)

Dimensions: 2" leg x 2" leg angle
 Stock Lengths: 10'-0" long (Custom lengths available by special orders)

ASTM & Code Standards:

- Structural framing is produced to meet or exceed ASTM C955
- Drywall framing is produced to meet or exceed ASTM C645
- Galvanized sheet steel meets or exceeds requirements of A653 and A1003
- MSDS & Product Certification Information is available at www.clarkdietrich.com

Related Accessories:

- ClarkDietrich SwiftClip L-Series Clips

05.40.00 (Cold-Formed Metal Framing)



Used in framing applications:

- Framing connections
- Corner intersections
- Half track connections

Sustainability Credits:

For more details and LEED letters contact Technical Services at 888-437-3244 or visit www.clarkdietrich.com/LEED

LEED v4 MR Credit -- Building Product Disclosure and Optimization: EPD (1 point) - Sourcing of Raw Materials (1 point) - Material Ingredients (1 point) - Construction and Demolition Waste Management (up to 2 points) - Innovation Credit (up to 2 points).

LEED 2009 Credit MR 2 & MR 4 -- ClarkDietrich's steel products are 100% recyclable and have a minimum recycled content of 34.2% (19.8% post-consumer and 14.4% pre-consumer). If seeking a higher number to meet Credit MR 5, please contact us at (info@clarkdietrich.com / 888-437-3244)

CD-200L-Angle © 03/19/15 ClarkDietrich Building Systems

Project Information

Name:
Address:

Contractor Information

Name:
Contact:
Phone:
Fax:

Architect Information

Name:
Contact:
Phone:
Fax: