

L4744 Underwood

enhanced



SwiftClean

SwiftClean is a technologically advanced, high performance waterproof surface protector, chemically bound to the surface of every Enstyle Enhanced series product. Floors with SwiftClean are easier to maintain, helping to preserve the natural appearance of the floor for both residential and commercial installation.

PearlTouch™ Ceramic Bead

All Enstyle LVT products are coated with a durable ceramic bead finish. These tiny microscopic particles are embedded in the layers of the UV cured PearlTouch finish to help protect the surface finish from premature wear.

dBcover cv

Our premium high performance sound suppressant underlayment helps to smooth out minor subfloor imperfections while adding comfort and warmth to the floor.

FloorScore

Meets Indoor Air Quality Product Performance Standards for Building Interiors. CA Section 01350 and SCS EC10.3-2014.

Warranties

- 27 Year Residential Finish
- 10 Year Medium Commercial

See full text for details

Style L4744 – Available colours

04 Linseed

57 Ashwood

74 Timber

Style
Supplier

L4744 Underwood
Kraus®

SPECIFICATION INFORMATION

Construction	2 mm
Profile	6"
Wear Layer	12 mil
Type	UV cured coating with Ceramic Bead
Virgin PVC	Yes
Finish	4 sided micro-bevel

CARTON CONFIGURATION

Plank Size (t x w x l)	2 mm x 6" x random length (48", 30", 18")
Packaging	36 sq.ft./carton 24 pcs/carton 27.78 lbs/carton
Installation	Full spread Below, on or above ground level

WARRANTY

27 Year Warranty (see full text for details)	27 Year Residential Finish 10 Year Medium Commercial
---	---

Vinyl flooring is a beautiful reproduction of wood or stone and therefore variations in colour, tone and graining are to be expected. Please note that the display samples may not always be a true representation of the final product. For this reason, new and/or replacement flooring may not exactly match display samples and/or existing flooring. Product image colours may vary due to print processes and monitor display settings. See krausflooring.com for latest specifications.

E&OE.