



6449-9-27
ArmorMaxx
Blacktop Driveway Sealer

ArmorMaxx

- High Performance & Durability
- Ideal for asphalt driveways
- Speed Dri Technology, traffic ready in 6 hours
- UV inhibitors for superior color retention

Black Jack® ArmorMaxx is an advanced acrylic blacktop sealant that seals and protects asphalt and concrete surfaces. This advanced sealer dries 3x faster, applies easier, and is low odor. **Black Jack® ArmorMaxx** restores driveways and parking lots to their original black appearance, and helps fill imperfections for a renewed finish. Using **Black Jack® ArmorMaxx** will beautify your property and can add years of life to your driveway or parking area.

PREP: We recommend power washing area before application to ensure best adhesion. Scrub all oil spots with a dishwasher soap and a brush. Repair problem areas with **Black Jack®** fillers and patches, and let fully dry prior to sealing. New asphalt must cure at least six months and/or one full summer season before applying sealcoat.

APPLICATION GUIDELINES: Apply on a clear, warm, sunny day in morning hours where surface and air temperatures are 55 °F and rising. (Summer months deliver best results.) DO NOT apply when temperatures are dropping, or when cold weather, heavy dew or rain is expected within 36 hours. Most problems occur when temperatures are too cool. Shaded areas will dry slower, so wait for warm dry days for proper curing. Allow at least 2-4 hours between coats and 24 - 36 hours before vehicle traffic. Do not use on surfaces with greater than 20° slope. Two coats are recommended for proper results, applied in a perpendicular direction.

COVERAGE: For driveways in average condition, apply with roller in two thin coats to a 350 sq/ft area. Rough surfaces have a higher surface area and will require more product.

CLEAN-UP: While wet, clean up with water and soap. Clean dry product with a citrus cleaner.

PRECAUTIONS: Protect against freezing. When transporting this product, store in cargo area, ensuring the lid is tight and pail secure and upright to prevent spills. Secure with protective cloths and do not transport on passenger seats or inside the passenger area. Do not reuse empty containers. Do not use in drinking water or food systems.

WARRANTY AND DISCLAIMER: Gardner-Gibson warrants product to be free of material defects for a period of 12 months, the "Warranty Period", from the date of purchase. Product must be applied in accordance with the proper application procedures, and for the intended use as stated on the label. Proper prep and drying conditions must be observed to achieve correct results. Should a product not perform as stated, Gardner-Gibson shall, within its sole discretion and upon receipt of purchaser's timely written notice within the Warranty Period, provide replacement product(s) or refund the purchase price of the defective product. This limited warranty does not cover labor or installation costs, consequential damages or incidental damages. Under no circumstances will the company be liable for any amount in excess of the product purchase price. Contact company below to request a refund with purchase receipt. There are no warranties which extend beyond the description on the face hereof. THIS LIMITED WARRANTY IS THE SOLE WARRANTY PROVIDED BY GARDNER-GIBSON TO THE PURCHASER. THERE IS NO IMPLIED WARRANTY OF MERCHANTABILITY OR IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE PROVIDED WITH THIS PRODUCT.

AVAILABLE SIZES						
PRODUCT CODE	UNIT SIZE	UNIT DIMENSIONS	FILL LEVEL	UNIT WEIGHT	PACK	UPC
6449-9-27	3.5 gal.	11.9" x 11.9" x 10.5"	3.3 gal. / 12.5 L	32.2 lbs.	36/pallet	027134644979

www.gardner-gibson.com
Gardner-Gibson • P.O. Box 5449 • Tampa, Florida 33675-5449
Phone: (813) 248-2101