



**Cairn®**  
33-1/2" undermount single-bowl kitchen sink  
**K-8206**

### Features

- 36" minimum base cabinet width
- Single bowl
- 9-1/2" (241 mm) depth provides generous workspace
- Offset drain increases workspace in the sink and storage space underneath
- Includes sink rack
- Includes cutout templates and installation clips
- Matte finish offers rich, dimensional color

### Material

- KOHLER Neoroc® composite is durable and built to withstand day-to-day cleaning tasks
- Solid color throughout the sink
- Heat-resistant up to 750°F
- Scratch-, stain-, chip-, and thermal-shock-resistant

### Installation

- Undermount
- Easy to install in a one-person, single-day project

### Required Products/Accessories

K-5192 Small stainless steel sink rack for K-8206

### Recommended Products/Accessories


K-23730 Neoroc® cleaner  
K-23726 Drain treatment  
K-11352 Disposal Flange with Stopper  
K-8801 Sink drain and strainer with tailpiece  
K-8799 Sink drain and strainer basket

### Optional Products/Accessories

K-9000 P-Trap

### Included Components

K-5196 Sink Rack



### Codes/Standards






CSA B45.5/IAPMO Z124

### KOHLER® Neoroc® Sinks Lifetime Limited Warranty

See website for detailed warranty information.

### Available Colors/Finishes


*Color tiles intended for reference only.*

Color	Code	Description
	CM6	Matte White
	CM7	Matte Graphite
	CM2	Matte Brown
	CM3	Matte Taupe
	CM4	Matte Grey



Cairn®

33-1/2" undermount single-bowl kitchen sink  
K-8206



### Technical Information

All product dimensions are nominal.

Basin configuration: Single Bowl

Min. base cabinet width: 36" (914 mm)

Bowl area (Basin #1):  
Length: 30-9/16" (777 mm)  
Width: 15-3/8" (391 mm)  
Bowl depth: 9-1/2" (241 mm)  
Water depth: 9-1/2" (241 mm)

Drain hole: 3-7/8" (98 mm)

Template: 1256394-7, required, included

### Notes

Install this product according to the installation instructions.

Allow a minimum of 2" (51 mm) clearance around the sink rim for clip attachment.