

Actual customer review: "5 year old leak gone!", Through the Roof!® will immediately seal your nagging roof leaks even if it rains before, during or after application, for a permanent seal.

- Apply in temperatures down to 0°F (-18°C)
- Sticks to most surfaces – even wet*
- Expands & contracts with temperature changes
- Stays elastic, won't dry hard or crack

Use Through The Roof!

- To repair broken shingles, shakes & tiles
- To seal leaky gutters & downspouts
- To seal around most rooftop fixtures

DIRECTIONS FOR USE

1. Close ventilation intakes on roof until solvent dissipates (approx. 12 hours).
2. Surfaces must be clean & free of frost. Remove any silicone.
3. Use a foam or coarse bristle utility brush & apply product 1/8" to 1/4" thick.

NOTE: Due to flammability, do not apply over 1/4" thick. Flammable during early cure (approx. 24-48 hrs).

* Applying on thin rubber membranes, such as EPDM, may cause warping. Test in an inconspicuous area prior to use.

Seals
everything that goes



Through the *ROOF!*

- Apply down to 0°F (-18°C)
- Easy brush-on formula
- Lasts 20x longer than roof cement

Seals Leaks That Asphalt Can't!

**WARNING: VAPOR HARMFUL.
FLAMMABLE. IRRITANT.**
Read cautions on back panel.

**1 Quart
(946 mL)**

Fully cured in 1-2 weeks. Paintable after 1 week.

CLEAN-UP & STORAGE

- Clean tools & unwanted surface spills with mineral spirits.
- Clean hands with citrus-based hand cleaners.
- Wipe off excess product from container neck & replace lid tightly.

VOC <550 g/L

LIMITED LIFETIME WARRANTY

For a detailed description of the warranty & exclusions, visit www.sashco.com.



©2017 Sashco, Inc.
10300 E 107th Place
Brighton, CO 80601
800-767-5656
www.sashco.com

Made in USA
TRFCQT4-17

