



KITCHEN & BATH •

2 IN 1

HVAC • ROOFING • FLOOD VENTS • WINDOW • CONCRETE • SIDING

GRAY GRIP & SEAL

HURRIBOND

FORMULATED FOR THE TOUGHEST APPLICATIONS**Fast Curing****Interior / Exterior****Paintable****Sandable**

- High Strength Adhesion
- Will not Shrink or Crack
- UV Resistant/Color Stable
(Meets ASTM G26 Testing Standards)
- Odorless
- VOC Compliant
- Alternative to Mechanical Fastening

HURRIBOND is a one component, medium modulus, fast curing, multi-purpose silyl-terminated polyether (hybrid) elastomeric sealant. When fully cured, this unique VOC compliant formula offers UV stability and tenacious stress free adhesion to PVC, concrete, glass, aluminum, painted surfaces, wood, plywood, marble, metal, plus many other common substrates. This product is specifically formulated to offer all weather performance.

INSTRUCTIONS:

1. Remove dirt, grease, or moisture from surface to be sealed or bonded. Allow to dry thoroughly.
2. Cut nozzle at angle to desired bead size.
3. Push sealant ahead for uniform bead. Section thickness should be limited to 1/4" (6mm) or less.
4. Tool sealant to desired thickness immediately before skin forms.
5. Skin time is approximately 30 minutes. Tack free in about 45 minutes. Normal curing time is 24 hours. Length of time for full cure depends upon thickness of application and other factors including temperature and humidity (see data sheet for complete information).

WARRANTY: Any goods proved defective will be replaced or the purchase price refunded. The limited warranty described herein is in lieu of any other warranty, expressed or implied, including any implied warranty of merchantability or fitness for a particular use. The user shall determine suitability of the product for its intended use. Liability for any incidental or consequential damage or loss is excluded. The user assumes all risks for the product's use, handling and storage.



WARNING: Cancer and Reproductive Harm
www.P65Warnings.ca.gov

WARNING

HAZARD & PRECAUTIONARY STATEMENTS:

Keep out of reach of children | Wear eye protection. In case of contact with eyes, immediately flush with water for 15 minutes. If irritation persists, seek medical attention. Remove contact lenses before using sealant | Do not handle unless sealant has been cleared from the fingertips, nails, and cuticles. Residual sealant may remain on the fingers for several days and transfer to lenses, causing severe eye irritation | Uncured product contact may irritate the skin and lungs. To clean from skin, wipe very thoroughly with dry cloth or paper towel before washing with detergent and water | Avoid breathing vapor. Use in a well ventilated area | Get medical attention/advice if you feel unwell or if skin irritation or rash occurs. | Wear protective gloves | Dispose of all contents/container to an approved waste disposal plant | Fully cured sealant is non-hazardous | Refer to Material Safety Data sheet for detailed information and NFPA listings | Conforms to California Prop. 65 Listed Chemicals (see MSDS) | Do not exceed 45psig when using in air powered caulking guns | Not intended for continuous underwater usage. Not for structural glazing |

CONTENTS: 471-34-1 precipitated calcium carbonate, non-hazardous prepolymer CAS# proprietary, 25322-69-4 polyether polyol, 1317-65-3 calcium carbonate, 68611-44-9 silica, amorphous.

VOLATILE ORGANIC CONTENT (VOC): 26 GRAMS/LITER

STORAGE: Store in a dry area, at a temperature below 80°F (27°C).

HURRIBOND.COM
(877) 441-8368

Smart Product Innovations, Inc.
Technical Office
430 Andbro Drive, Unit 1
Pitman, NJ 08071

