

Project:

Fixture Type:

Location:

Contact:

Moderna LED

Ceiling Stem Hung with 6 links of chain Mounted • Dry Location Listed PROGRESS LED

Description:

Moderna LED Collection Brushed Nickel Clear Glass Mid-Century Modern Pendant Light

Specifications:

- Clear Glass Shade
- ${\boldsymbol{\cdot}}$ Etched White Glass Diffuser
- Dimmable to 10% brightness (See Dimming Notes)
- Canopy covers a standard 4" recessed outlet box: 5.125 in W.,
- + Mounting strap for outlet box included
- 120 in of wire supplied
- 1 EA Six links 9 Gauge

Performance:

Number of Modules	1
Input Power	9 W
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW (Source)	670/71 (LM-82)
Lumens/LPW (Delivered)	385/41.4 (LM-79)
ССТ	3000 K
CRI	90+ CRI
Life (hours)	60000 (L70/TM-21)
EMI/RFI	Meets FCC Title 47, Part 15 Class B
Max. Operating Temp	30 °C
Warranty	5-year Limited Warranty
Labels	cCSAus Dry Location Listed
	Meets California Title 24 JA8-2016

P500000-009-30



Dimensions:

Diameter: 5-3/4 in Height: 9-1/2 in Overall Ht. W/Chain And Stem: 75-1/2 in



Moderna LED

Ceiling Stem Hung with 6 links of chain Mounted • Dry Location Listed PROGRESS LED

Dimming Notes:

P500000-009-30 is designed to be compatible with many Triac/Forward Phase ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls:

Lutron_Diva DVELV-300P
Lutron_Nova T NTELV-300
Lutron_Caseta
Lutron_Ariadni AY-600P
Leviton_Illumatech IPI06-1LZ
Leviton_SureSlide 6672
Lutron_Skylark Contour CTCL-153P
Lutron_Diva DVCL-153P
Lutron_Toggler TGCL-153P
Lutron_Maestro MACL-153M
Lutron_Ariadni AYLV-600P
Lutron_Nova T NTLV-600
Lutron_Maestro MAELV-600
Lutron_spacer/system SPSELV-600
Leviton_Renoir II AWRMG-EAW
Lutron_Nova N-600

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.

Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.

P500000-009-30