

Safety Data Sheet

Revision Date: 05/28/2021

SECTION 1: Identification and Company Details

Product Name: BRUTUS TOUCH-UP PUTTY FOR WOOD, LAMINATE, & VINYL

Product Code: 82505BR Tan, 82506BR Brown, 82507BR Dark Brown, 82508BR Light, 82509BR Light Gray,

82510BR Gray

Manufacturer/ Supplier: Brutus

Address: 300 Cross Plains Blvd.

Dalton, GA 30721

Emergency Phone: (800) 424-9300 (24-hour Response / CHEMTREC)

Product Information: (706) 277-5294

Recommended Use: Coating

SECTION 2: Hazard(s) Identification

OSHA / HCS Status: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR

1910.1200)

Classification of the

substance or mixture: Category 1,1A

Signal Word: Danger

Hazard Statements: May Cause slight skin irritation

May cause slight eye irritation

May cause irritation of nose, throat and lungs

Ingestion of large amounts may product gastrointestinal disturbances including irritation, nausea

and diarrhea



Hazard Pictograms:

Precautionary Statements: Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection.

If exposed or concerned: Get medical advice/attention.

Disposal: Dispose of contents/container in accordance with local/regional/national/international

regulations

Storage: Store locked up

SECTION 3:	Composition / Information on Ingredients	CAS#	<u>% w/w</u>
Limestone		1317-65-3	64 ± 3
Acrylic polymer		25586-20-3	7 ± 2
Kaolin clay		1332-58-7	3 ± 1
Crystalline silica		14808-60-7	1.0 ± 0.2
Water and other	ingredients		25 ± 6

SECTION 4: First-Aid Measures

Inhalation: Move victim to fresh air. If symptoms persist, call a physician.

Skin Contact: Wash off immediately with soap and plenty of water removing all contaminated clothes and

shoes.

Eye Contact: Immediately flush eyes with plenty of water for 15 minutes. Call a physician if irritation persists. **Ingestion:** Clean mouth with water and afterwards drink plenty of water. Consult a physician if necessary.

SECTION 5: Fire-Fighting Measures

Flammability: In a fire, closed containers may rupture (due to build up of pressure) when exposed to extreme heat.

Extinguishing Media: Carbon dioxide, dry chemical, foam, water spray

Protection of Firefighters: Firefighters should wear appropriate protective equipment and self-contained breathing apparatus

(SCBA) with a full face-piece operated in positive pressure mode.

FLASH POINT,METHOD
AUTO IGNITION TEMPERATURE
UPPER FLAMMABLE LIMIT
LOWER FLAMMABLE LIMIT
Not applicable
EXPLOSION DATA
Not applicable
EXPLOSIVE POWER
RATE OF BURNING
Not applicable
Not applicable
Not applicable

SENSITIVITY TO STATIC DISCHARGE No SENSITIVITY TO IMPACT No

SECTION 6: Accidental Release Measures

Minor spills do not normally need any special cleanup measures.

In the event of a major spill, prevent spillage from entering drains or water courses. Wear suitable protective clothing.

Stop leak if safe to do so, and contain spill. Sweep up and shovel or collect recoverable product into labelled containers for recycling or salvage, and dispose of promptly. Consider vacuuming if appropriate. Recycle containers wherever possible after careful cleaning. After spills, wash area preventing runoff from entering drains. If a significant quantity of material enters drains, advise emergency services. This material may be suitable for approved landfill. Ensure legality of disposal by consulting regulations prior to disposal. Thoroughly launder protective clothing before storage or re-use. Advise laundry of nature of contamination when sending contaminated clothing to laundry.

SECTION 7: Handling and Storage

Handling Precautions: Always use appropriate personal protective equipment. Avoid contact with skin, eyes and clothing.

Avoid breathing vapors or mist. Use only with adequate ventilation.

Storage: Keep container tightly closed when not in use. Store in a cool well-ventilated area. Keep from

freezing.

SECTION 8: Exposure Control / Personal Protection

Engineering Measures: Ensure adequate ventilation, especially in confined areas

EYE/FACE: Safety goggles, safety glasses with side-shields

SKIN: Suitable protective clothing

RESPIRATORY: In case of insufficient ventilation wear suitable respiratory equipment

HYGIENE MEASURES: When using do not eat, drink or smoke. Wash hands, forearms and face after handling.

SECTION 9: Physical and Chemical Properties

Appearance: Colored thick paste

Odor: Mild
Specific Gravity (water=1): 1.7-1.8
Viscosity Ford Cup #4 (seconds): N/A

Solubility: miscible
pH: 8-8.5
% Volatile per weight: 25±1
Freezing Point: 0°C
Vapor Density: N/A (Air=1)
Vapor Pressure: 17.54 (water)

Evaporation Rate: N/A VOC: <50 Boiling Point: 100°C

SECTION 10: Stability and Reactivity

Chemical Stability: Stable under normal conditions of storage and use.

Incompatibilities: None known

Conditions to Avoid: Protect from freezing

Hazardous decomposition products: Under normal conditions of storage and use, hazardous decomposition

products should not be produced.

Possibility of hazardous reactions: Under normal conditions of storage and use, hazardous reactions will not occur.

SECTION 11: Toxicological Information

Limestone

LC50 Not available

LD50 6450 mg/kg –oral-rat

Can cause lung damage. Pre-existing respiratory disorders may be aggravated by exposure.

Crystalline Silica

LC50 Not available

LD50 500 mg/kg – oral-rat

Can cause cancer. Use of this product may generate silica dust (which may be invisible). Inhaled silica has been classified by IARC as a human carcinogen.

SECTION 12: Ecological Information

Environmental toxicity information Not available

SECTION 13: Disposal Considerations

Disposal: Disposal in accordance with applicable regional, national, and local laws and regulations.

SECTION 14: Transport Information

	TDG	DOT	IMDG	IATA
UN number	Not regulated	Not regulated	Not regulated	Not regulated
Proper shipping name				
Transport hazard class				
Packing group				
Limited quantity	No	No	No	No

SECTION 15: Regulatory Information

Status on Substance Lists: The concentrations shown in this document are maximum levels (weight %) to be used for

regulations.

TSCA:

All ingredients are listed on TSCA or in compliance with the inventory

DSL/NDSL:

All ingredients are listed on the DSL/NDSL or in compliance with the inventory

EINECS:

All ingredients are listed on the EINECS or in compliance with the inventory

California Proposition 65: Does not contain any listed chemical to the best of our knowledge.

SECTION 16: Other Information

This Safety Data Sheet is prepared to comply with the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200).

HMIS RATING: HEALTH- 1, FLAMMABILITY- 0, REACTIVITY- 0, PERSONAL PROTECTION- B

Prepared by: Brutus Product Safety & Regulatory Compliance Group, (706) 277-5294

The information herein is given in good faith, but no warranty expressed or implied is made. Brutus urges users of this product to evaluate its suitability and compliance with local regulations as Brutus cannot foresee the final use of the product, nor the final location of usage.

Date of issue: 05/28/2021