



# Technical Bulletin

2400 Boston Street, Suite 200, Baltimore, Maryland 21224  
Phone: 410-675-2100 or 800-543-3840

Revised: 5/20/2005

## DAP® Vinyl Spackling

- Heavy duty
- Resists cracking
- Easy to sand
- Interior/exterior use

**Packaging:** 5.5 oz squeeze tube, 1/2 pint tub, 24 oz. tub, 1 quart tub, 1 gallon tub, 237 ml tub, 946 ml tub, 3.8 L tub

**Color:** White

**UPC Number:** 12008, 12130, 12135, 12132, 12133, 20040, 20045, 20050, 20090

### Company Identification:

Manufacturer: DAP Inc., 2400 Boston Street, Baltimore, Maryland 21224

Usage Information: DAP HELPLINE: 888-DAP-TIPS, 9:00 am to 7:00 pm EST.

Order Information: 800-327-3339

Fax Number: 410-534-2650

Also, visit the DAP website at [www.dap.com](http://www.dap.com).

### Product Description:

DAP® Vinyl Spackling may be used to fill holes and cracks in surfaces such as drywall, plaster, wood, brick and stone. Its ready-to-use formula spreads easily for fast, professional repairs that will not crack, crumble or flake. DAP® Vinyl Spackling dries hard, sands easily and can be painted.

### Suggested Uses:

Ideal for filling holes, cracks and defects on:

- Drywall/Plaster
- Wood
- Brick
- Stone

### Surface Preparation & Application:

- Surface must be clean, dry and free of foreign material.
- Stir before use. Apply with a clean putty knife.
- For a smoother finish, dip putty knife in water and lightly smooth spackling.
- One application is usually sufficient for small repairs. For repairs deeper than 1/4", apply two or more layers allowing spackling to dry between applications.
- May be sanded or painted in 1 to 5 hours depending on temperature, humidity and depth of fill. Wet sanding is recommended to avoid generation of dust.
- Clean tools immediately with water.

***For Best Results:***

- Do not apply when temperatures are below 50°F.
- Do not apply outside if rain is expected within 24 hours.
- Do not use on floors or as caulk, sealant or joint filler over cracks and joints where expansion and contraction may occur.
- **DO NOT USE AS A SKIM COAT.**
- For exterior applications, always topcoat with a good quality paint.
- If a textured finish is desired, add clean sand to spackling compound prior to application.
- Do not use for tuck pointing applications on brick.
- For larger areas to be patched on bare concrete, use a latex fortified Portland cement-based dry mix.

**Physical & Chemical Characteristics:**

Consistency:	Paste
Vehicle:	Water
Volatile:	Water
Filler:	Inert Filler
Odor:	Slight Acetate
Weight/Gallon:	15.5 ± .2 Pounds
Solids:	76% by weight
Application Temperature:	50°F Minimum
Service Temperature:	0°F to 150°F
Shelf Life:	1 Year
Freezing:	Freeze/Thaw Stable 5 Cycles at 0°F
Drying Time:	1 to 5 hours depending on temperature and relative humidity and depth of fill.
Painting:	Takes either oil or latex-base paint when dry.
MSDS No.:	000 10405 001

**Clean Up & Storage:**

Wash tools immediately after use with water. Be sure container is closed and tightly sealed. Store in a cool, dry place.

**Safety:**

See product label and Material Safety Data Sheet (MSDS) for safety information. You can request an MSDS by visiting our website at [www.dap.com](http://www.dap.com) or by calling 888-DAP-TIPS.

**Satisfaction Guaranteed:**

If you are not satisfied with this product's performance when used as directed, return used container and sales receipt to DAP Inc., Technical Customer Service, 2400 Boston Street, Suite 200, Baltimore, MD 21224 for product replacement or sales price refund. DAP will not be liable for incidental or consequential damages.