



## Krud Kutter® Multi-Purpose House Wash



# 2013

## Technical Data

### Physical Data:

**Contains:** Proprietary Ingredients in a water based solution.

**Physical State:** Liquid

**Color:** Clear

**Odor:** Mild

**pH:** <12

**Flash Point:** Non-Flammable

**Shelf Life:** N/A

**VOC:** 0% (0g/L)

### FOR EMERGENCY CALL:

**CHEMTREC:** 800.424.9300

**INTERNATIONAL:** 703.527.3887  
(COLLECT CALLS ACCEPTED)

### Availability:

Krud Kutter brand products can be found mainly in paint and cleaning departments of leading home improvement, hardware, paint, and general merchandise stores in the US and CANADA. For a list of retailers please visit [krudkutter.com](http://krudkutter.com) or call 800-466-7126.

### KRUD KUTTER, INC.

1535 Oak Industrial Lane | Suite B  
Cumming, GA 30041

### PHONE

1.800.466.7126

### WEB

[www.krudkutter.com](http://www.krudkutter.com)

## A MAJOR BREAKTHROUGH IN HOUSE WASH TECHNOLOGY

The proprietary formulation contains "Sporex", a unique additive which removes tough stains from mildew, mold, algae, fungus and moss, and leaves the surface completely clean. In addition, special surfactants penetrate the surface to safely and easily dissolve the toughest stains from dirt, oil, grease, bird droppings, tree sap, and acid rain. Even removes gray weathering on wood, chalking, and oxidation.

### SAFE•FAST•EFFECTIVE ON MOST SURFACES

Recommended for exterior siding (wood, vinyl, aluminum), roofing of all types (asphalt shingles, fiberglass shingles, cedar, tile), gutters, stucco, brick and cement block, masonry, walkways and walls.

### COST EFFECTIVE & EASY TO USE

For manual application mix 1 cup of concentrate with 1 gallon of water. Can be applied by pump up sprayer, brush or roller. Simply apply to the surface, leave for 5 to 10 minutes, and wash off.

### DIRECTIONS FOR HOSE END SPRAYER: For best results use on a wet surface.

1. Attach garden hose to back of sprayer with valve in "OFF" position.
2. Turn on water to the hose. With valve in "RINSE" position wet the surface to be cleaned.
3. With valve in "CLEAN" position, apply the cleaner to the surface from the top down.
4. Allow to work for 5-10 minutes. Do not allow to dry on surface.
5. Rinse off treated surface with valve in "RINSE" position. Turn hose on full pressure for best results. Rinse surrounding areas and vegetation with water.
6. On extremely soiled or mildewed surfaces, it may be necessary to scrub with a bristle brush, and a second application may be needed.

### DIRECTIONS: PRESSURE WASHER APPLICATION

Contains anti-corrosive agents to safeguard pressure washer parts (bleach can erode O-rings).

1. Rinse surrounding plants with water, before and after application.
2. Wet surface to be cleaned, prior to applying the product.
3. Place detergent application siphon tube and screen filter directly into container. Open meter valve (if applicable) for maximum product flow. For reservoir machines, pour product (full

strength) into pressure washer.

4. Spray at low pressure onto a wet surface.
5. On vertical surfaces, always spray from the top down.
6. Allow product to remain on the surface for 5 to 10 minutes to penetrate. Do not allow product to dry on surface.
7. Remove siphon tube from solution and rinse surface with high-pressure spray thoroughly.
8. Flush siphon tube with clean water prior to storage.

### IMPORTANT - READ ENTIRE LABEL BEFORE USE

- When using a pressure washer to clean painted surfaces, please be aware that water pressure alone may remove paint, or highlight existing discoloration caused by the sun's UV rays.
- From the garden hose, rinse any nearby plants with clean water.
- Always test on an inconspicuous area first.
- Any overspray can be neutralized with large volumes of water.
- On extremely soiled or mildewed surfaces it may be necessary to scrub with a bristle brush, and a second application may be needed. Mildew may not be completely removed from porous surfaces.
- For best results when cleaning decks, apply by pump-up garden sprayer, leave for 5 to 10 minutes, and rinse off with water.
- For heavy oil and grease stains (such as on driveways and garage floors), pour product directly onto the stain. Allow to penetrate for 10 minutes, then follow normal application procedures.
- In case of severe oil and grease stains on porous surfaces, oil may bleed to the surface or leave a residual stain. Repeat applications may lighten stains, but not remove completely.
- Do not mix this product with any other chemicals.

### NO BLEACH OR AMMONIA

**CAUTION:** This product contains alkaline detergents. **EYE AND SKIN IRRITANT.** Do not take internally. **FIRST AID:** In case of contact with eyes or skin, flush with water for 15 minutes. If irritation persists, seek medical attention. If swallowed, take large amounts of water. Do not induce vomiting. Get medical attention. Material Safety Data Sheet available.

**KEEP OUT OF REACH OF CHILDREN.**