



WILSONART®
I N T E R N A T I O N A L

COLOR MATCHED CAULK FOR KITCHENS, BATHROOMS AND FLOORING!

- Stain, Mold & Mildew Resistant
- Stays Flexible
- Easy Water Clean-up
- Water Resistant
- Professional & Consumer Applications
- Contains No Ethylene Glycol
- Available sizes:
5.5 oz Squeeze Tubes (6-pack)
10.5 oz Cartridges (6-pack)

Wilsonart® Color Matched Caulk is a 100% siliconized acrylic that is formulated to color match Wilsonart® Laminate and other high pressure countertops, floors, casework, sinks, tubs and showers.

Physical Properties

Vapor Density (Air=1):	> 1
Solubility in Water:	Soluble
Appearance:	Smooth, viscous paste
Odor:	Mild acrylic odor
Specify Gravity (H ₂ O =1):	~ 1.60 -1.56
Percent Volatiles by weight (%):	~ 16 -18
pH:	~ 7.0 -7.5
Total Non-Volatile % Solids (Weight):	82% (Computrac Analyzer)
Flexibility:	Conforms to ASTM 734
Tack Free Time:	< 1 hr @ 77°F (ASTM D-2377)
Shelf Life:	18 months



**COLOR MATCHED
CAULK**



COLOR MATCHED CAULK

Description

Wilsonart® Color Matched Caulk is a 100% siliconized acrylic that is formulated to color match Wilsonart and other high pressure laminate products. Applications include countertops, floors, casework, sinks, tubs and showers.

Surface Preparation

Surface must be clean, dry and free from dirt, dust, grease, oil, mildew, wax, loose paint and old caulking. Apply only when caulk, air and substrate temperatures are above 50°F. Thoroughly rinse surface and allow to dry completely before caulking and painting.

Directions

1. Clip off tip of spout at a 45° angle to desired size.
2. Apply using steady, even pressure to completely bridge joints.
3. Smooth caulk using wet finger for a neat appearance.
4. Wipe away excess with a damp cloth before surface skins over.
5. Protect from water until cured (72 hours). May be painted over in 4-6 hours depending on climatic conditions. Larger beads may require longer drying time. Cool, humid conditions will prolong drying time.

For Best Results

- Apply caulk in temperatures between 50°F and 90°F.
- Store caulk at temperatures between 50°F and 90°F.
- Do not use for constant water exposure applications.
- Do not use for joints subject to heavy abrasion or wear.
- Do not attempt to thin caulk
- For a neat, straight bead edge, mask both sides of joint with masking tape.
- Do not "overtool" the applied caulk, leaving too little caulk to perform, following cure.

Clean-up

Clean skin and equipment immediately after use with warm water and a mild soap.

Volatile Organic Compounds (VOC):

The use, supply, sale or offer for sale of this product in certain states and localities may be prohibited if it exceeds certain VOC limits. Please check state and local regulations for any prohibitions on the sale and use of this product.

Safety

Inhalation of vapors may irritate respiratory tract. May cause skin and eye irritations. Keep out of reach of children.

HMIS Rating: Health 1, Flammability 1, Reactivity 0

24-hour Chemtrec Emergency Number:

1-800-424-9300 (US); 1-703-527-3887 (International)

Wilsonart Warranty

Wilsonart International, Inc. warrants to the user that this product is free of defects for a period of one (1) year from the date of manufacture when it is applied in accordance with manufacturer's instructions or the manufacturer will replace the container at no cost or additional charge to the user, provided the unused portion of the product is returned to the place of purchase within 15 days of the date of purchase. This warranty does not apply to (I) products that are purchased after the expiration of the manufacturer's recommended shelf life as stated on this technical data sheet, (II) misuse or mishandling of the product, (III) improper storage, or (IV) improper fabrication using this product. NO OTHER WARRANTIES, EXPRESS OR IMPLIED ARE MADE, INCLUDING MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. UNDER NO CIRCUMSTANCES SHALL THE MANUFACTURER BE LIABLE FOR ANY LOSS OR DAMAGE ARISING FROM THE PURCHASE, USE, OR INABILITY TO USE THIS PRODUCT, OR FOR ANY SPECIAL, INDIRECT, INCIDENTAL OR CONSEQUENTIAL DAMAGES. NO FABRICATOR, INSTALLER, DEALER, AGENT OR EMPLOYEE OF WILSONART INTERNATIONAL, INC. HAS THE AUTHORITY TO MODIFY THE OBLIGATIONS OR LIMITATION OF THIS WARRANTY. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state. Therefore, some of the limitations stated above may not apply to you. It is your benefit to save your documentation upon purchase of product.

For More Information

- www.wilsonartadhesives.com for:
 - Tech Data Sheets
 - Material Safety Data Sheets (MSDS)
 - Adhesive Quick Reference Chart
 - Certified Product Data Sheets (CPDS)
- Customer Service Line 1-800-433-3222
- Wilsonart Adhesives Division
10601 NW HK Dodgen Loop
Temple, TX 76503-6110