

E L E M E N T A L N A T U R A L S

Siena Springs™



ColorBody™ Porcelain Tile



Siena Springs™

Features

- Emulates look of natural stone
- Modular for pattern layouts
- Strong color and shading
- Slip and stain resistant

Field Tile



Cascade SG50



Riverbed SG51



Boulder SG52



Cavern SG53

Decorative Tile



Cascade SG50
Mosaic
3" x 3"



Riverbed SG51
Mosaic
3" x 3"




Boulder SG52
Mosaic
3" x 3"



Cavern SG53
Mosaic
3" x 3"



Cascade SG50
Random Linear Brickjoint
10" x 20"



Riverbed SG51
Random Linear Brickjoint
10" x 20"



Boulder SG52
Random Linear Brickjoint
10" x 20"



Cavern SG53
Random Linear Brickjoint
10" x 20"



Cascade SG50
Decorative Border
1 1/4" x 13"



Riverbed SG51
Decorative Border
1 1/4" x 13"



Boulder SG52
Decorative Border
1 1/4" x 13"



Cavern SG53
Decorative Border
1 1/4" x 13"


COORDINATING TILE SUGGESTIONS



Legacy Glass
Sable LG05



Tumbled Slate
China Multicolor TU70




Candalaria Glass
Black Pearl CL54



Tumbled Stone
Azteca TU05

SIZES



20" x 20" Field Tile
(19 3/4" x 19 3/4" nominal)
(50.2 cm x 50.2 cm nominal)




13" x 20" Field Tile
(13 1/8" x 19 3/4" nominal)
(33.3 cm x 50.2 cm nominal)




13" x 13" Field Tile
(13 1/8" x 13 1/8" nominal)
(33.3 cm x 33.3 cm nominal)



6 1/2" x 6 1/2" Field Tile
(6 1/2" x 6 1/2" nominal)
(16.4 cm x 16.4 cm nominal)



3" x 3" Mosaic
(13 1/8" x 13 1/8" sheet nominal)
(33.3 cm x 33.3 cm sheet nominal)




10" x 20" Random Linear Brickjoint
(9 7/8" x 19 3/4" sheet nominal)
(25.0 cm x 50.2 cm sheet nominal)




1 1/4" x 13" Decorative Border
(1 1/4" x 13 1/8" nominal)
(3.1 cm x 33.3 cm nominal)


TRIM



Bullnose 3" x 13"
S43E9



Cove Base 6" x 13"
S36E9T



Cove Base Corner 1" x 6"
SC36E9T

Tile Thickness: 3/8" Recommended grout joint: 3/16"



Shade Variation: High



Information

Applications

	Residential	Light Commercial	Commercial
Floors†	X	X	X
Walls	X	X	X
Countertops	X	X	X
Backsplashes	X	X	X

† Water, oil, grease etc. create slippery conditions. Floor applications with exposure to these conditions require extra caution in product selection. For additional information, refer to "Factors to Consider" at www.americanolean.com/ResidentialFactors

- Suitable for exterior walls in freezing and non-freezing climates when proper installation methods are followed

Price Structure

Premier

Preferred

Stylish and elegant looks. Each tile is created through traditional firing processes and glaze techniques.

Premium

Sophisticated visuals and detailed surfacing. A process of multiple glazes results in an attractive, cultured surface.

Premier

Inherent visual color and depth. A complex process of design brings out the rich, more upscale texture and look of elegant porcelain as well as a variety of other tiles.

Prestige

Natural characteristics and realistic attributes. Captures the inherent beauty of natural stone. Highly complex design techniques are also applied to rich porcelains, unique glasses and other materials to create surfaces with distinctive physical and natural qualities.


Performance characteristics

C.O.F. Wet	C.O.F. Dry	Moisture Absorption	Breaking Strength	MOH's	Chemical Resistance
≥0.60	≥0.76	<0.5%	>400 lbs.	8.0	Resistance



This tile meets or exceeds ANSI A137.1 standards


Patterns



Modified Hopscotch

17 pcs. per 100 s/f 20" x 20"	46%
17 pcs. per 100 s/f 13" x 20"	30%
17 pcs. per 100 s/f 13" x 13"	19%
17 pcs. per 100 s/f 6-1/2" x 6-1/2"	5%

* Dark lines indicate repeat



Modified Hopscotch

24 pcs. per 100 s/f 20" x 20"	65%
24 pcs. per 100 s/f 13" x 13"	28%
24 pcs. per 100 s/f 6-1/2" x 6-1/2"	7%

Cleaning Procedures

- Remove loose dust and dirt with a damp cloth or a sponge
- Use a neutral, non-abrasive cleaner suitable for ceramic tile
- Remove cleaning solution with a clean, damp sponge or mop

Special Notes

Special care should be taken when grouting with dark pigmented colors. A grout release is recommended to prevent finely powdered pigments from lodging in the pores of the tile surface.

Special installation requirement: For proper bonding, medium bed mortar should be utilized in installing tiles with a dimensional length size greater than 20" x 20", large rectangles or tiles with a greater dimensional thickness than normal. Back buttering tiles of this nature in the installation process will also assure proper coverage for bonding.

Since there is shade variation in all fired ceramic products, the tile and trim supplied for your particular installation may not match these samples. Final selection should be made from actual tiles and trim and not from tile and trim samples or color reproductions.

Use of a latex modified thinset is recommended for installations.