

C O N T I N E N T A L   R U S T I C S

Vallano™



Glazed Floor and Wall Tile





# Vallano<sup>TM</sup>

## Features

- The rustic look of lightly weathered stone
- A color palette of rich browns that work well in any combination or stand alone
- Multiple glaze applications for added visual depth
- A variety of sizes and trim shapes for easy patterning
- Natural stone borders and carved leaf decorative accents

## Field Tile



Macadamia VL01



Caramel VL02



Milk Chocolate VL03



Dark Chocolate VL04

## Decorative Tile



Universal VL10 Wall Accent 6" x 6"



Universal VL10 Wall Accent Strip 3" x 8"



Universal VL10 Mosaic Stone Floor Border 3" x 12"

## Tile Patterning Combinations



Caramel VL02\*




Macadamia VL01  
Caramel VL02\*



Macadamia VL01  
Caramel VL02  
Milk Chocolate VL03  
Dark Chocolate VL04\*

\*With Vallano's unique color palette, your design can range from limited variation utilizing one color to random variation using a mixture of colors.

## SIZES



18" x 18" Field Tile ◆  
(17 3/4" x 17 3/4" nominal)  
(45.2 cm x 45.2 cm nominal)



12" x 12" Field Tile ◆  
(11 13/16" x 11 13/16" nominal)  
(30.0 cm x 30.0 cm nominal)



6" x 6" Field Tile/Wall Accent ▲  
(5 13/16" x 5 13/16" nominal)  
(14.8 cm x 14.8 cm nominal)



3" x 12" Floor Border  
(2 3/4" x 11 13/16" nominal)  
(7.0 cm x 30.0 cm nominal)



3" x 8" Wall Accent Strip ▲  
(2 5/8" x 7 7/8" nominal)  
(6.5 cm x 20.0 cm nominal)

◆ Porcelain Tile  
▲ Clay Tile

Tile Thickness: 5/16"

Recommended Grout Joint: 3/16"



Shade Variation: Medium to Random





Information

Applications

	Residential	Light Commercial	Commercial
Floors †	X	X	X
Walls/Backsplashes	X	X	X
Countertops	X	X	X
Pool Linings	X	X	X

† Water, oil, grease, etc. create slippery conditions. Floor applications with exposure to these conditions require extra caution in product selection and proper maintenance. For additional information, refer to "Factors to Consider" at [www.americanolean.com/ResidentialFactors](http://www.americanolean.com/ResidentialFactors).

- Suitable for exterior walls in non-freezing climates only when proper installation methods are followed
- Not for use on ramps.

Price Structure

Premium

Preferred

Stylish and elegant looks. Each tile is created through traditional firing processes and glaze techniques.

Premium

Sophisticated visuals and detailed surfacing. A process of multiple glazes results in an attractive, cultured surface.

Premier

Inherent visual color and depth. A complex process of design brings out the rich, more upscale texture and look of elegant porcelain as well as a variety of other tiles.

Prestige

Natural characteristics and realistic attributes. Captures the inherent beauty of natural stone. Highly complex design techniques are also applied to rich porcelains, unique glasses and other materials to create surfaces with distinctive physical and natural qualities.

Performance Characteristics


	C.O.F.		Moisture Absorption	Breaking Strength	MOH's	Chemical Resistance	Abrasion Resistance
	Wet	Dry					
Porcelain Body	≥0.60	≥0.70	<0.5%	>325 lbs.	8.5	Resistant	4 (VL01) 3 (VL02-VL04)
Clay Body	≥0.60	≥0.70	<3.0%	>250 lbs.	7.0	Resistant	4 (VL01) 3 (VL02-VL04)

This tile meets or exceeds ANSI A137.1 standards


**Abrasion Resistance** Application Classifications ISO 10545-7

**1** Light Residential **2** Heavy Residential **3** Light Commercial **4** Heavy Commercial

Trim

 Bullnose P43C9 3" x 12"	 Surface Bullnose S4669 6" x 6"	 Surface Bullnose Corner SCRL4669 6" x 6"	 Quarter Round A106 3/4" x 6"	 Quarter Round Corner UC106 3/4" x 3/4"
 Counter Rail 26CR 2" x 6"	 Counter Rail Corner 22CRC 2" x 2"			

Patterns




Diamond

100 pcs. per 100 s/f  
12" x 12" 100%

or

45 pcs. per 100 s/f  
18" x 18" 100%




Brickwork

100 pcs. per 100 s/f  
12" x 12" 100%

or

45 pcs. per 100 s/f  
18" x 18" 100%




Hopscotch

80 pcs. per 100 s/f  
12" x 12" 80%

80 pcs. per 100 s/f  
6" x 6" 20%

\* Dark lines indicate repeat



Grid with Border

Cleaning Procedures

- Remove loose dust and dirt with a damp cloth or a sponge
- Use a neutral, non-abrasive cleaner suitable for ceramic tile
- Remove cleaning solution with a clean, damp sponge or mop

Special Notes

Since there are variations in all fired ceramic products, the tile and trim supplied for your particular installation may not match these samples. Final selection should be made from actual tiles and trim and not from tile and trim samples or color reproductions. Manufactured in accordance with ANSI A137.1 standards.