

Dimmable CFL & LED bulbs

Compatible with Lutron 100W & 150W C-L® dimmers



Dimmable CFL & LED bulbs

Compatible with C·L[®] dimmers

This list is designed to help you select bulbs that are compatible with Lutron C·L dimmers. The CFL and LED bulbs on this list were extensively tested by Lutron; the Lutron C·L dimmers were evaluated by UL and meet applicable safety standards.

How to use this list

If you already have a bulb:

Use the “Find” tool in your browser or PDF viewer to search for the model number that’s printed on the bulb. Then choose a C·L dimmer that’s compatible with that bulb.

If you already have a C·L dimmer:

Use the table of contents to find the corresponding pages for that control, and then select a bulb from that list.

What does “compatible” mean?

Compatible means that the bulbs can be dimmed, although the bulb’s dimming performance may not match what you’re used to seeing when dimming an incandescent or halogen bulb. These bulbs have also been electrically tested to confirm that the control may be used up to its full rated CFL/LED load without affecting the life of the control.

Products on this list are considered compatible with the respective Lutron C·L dimmers. Depending on the quality of the bulb you select, compatible bulbs may still:

- have less dimming range than an incandescent or halogen bulb
- dim less smoothly than an incandescent or halogen bulb
- flicker or shimmer at certain light levels
- buzz

Dimmable CFL & LED bulbs

Compatible with C·L[®] dimmers

Warranty on your Lutron 100W C·L dimmer or 150W C·L dimmer will be void if used with bulbs that are not on this Lutron compatible bulb list.





Please note: Bulb variations in lamp design and construction affect performance. Bulb manufacturers can modify their bulbs at any time, without notice to Lutron. This prevents Lutron from ensuring ongoing compatibility. For up-to-date specifications, performance, and/or any related recall information about the bulb, please visit the bulb manufacturer's website.

This document provides information from manufacturers who are not Lutron agents or affiliates. The listing of a manufacturer or the existence of any external link to another website does not suggest that Lutron is endorsing the linked company, its products and/or its services. Purchasers should ask appropriate questions and request references before buying any products and/or entering a contract with any party. The information contained in this document is intended for illustrative and comparative purposes only, and is subject to change at any time. Lutron does not warrant that (a) the list of manufacturers is all-inclusive; (b) the information is complete, up-to-date, accurate and/or error-free; (c) the products and Lutron controls listed will always be compatible; and (d) that the information provided will be a viable or appropriate solution for your project needs. You are entirely responsible for and assume all risk for the use of the information.

Dimmable CFL & LED bulbs

Compatible with C·L® dimmers

Table of Contents

| | | |
|--|-------------|---|
| Maestro® occupancy sensor C·L dimmers | |  |
| • LED Bulbs | pages 1–16 | |
| • CFL Bulbs | pages 17–18 | |
| Maestro C·L dimmers | |  |
| • LED Bulbs | pages 19–36 | |
| • CFL Bulbs | pages 37–38 | |
| Diva® C·L dimmers* | |  |
| • LED Bulbs | pages 39–57 | |
| • CFL Bulbs | pages 58–59 | |
| Skylark Contour® C·L dimmers* | |  |
| • LED Bulbs | pages 39–57 | |
| • CFL Bulbs | pages 58–59 | |
| Skylark® C·L dimmers | |  |
| • LED Bulbs | pages 39–57 | |
| • CFL Bulbs | pages 58–59 | |
| Lumea® C·L dimmers* | |  |
| • LED Bulbs | pages 39–57 | |
| • CFL Bulbs | pages 58–59 | |
| Toggler®/Ariadni® C·L dimmers* | |  |
| • LED Bulbs | pages 39–57 | |
| • CFL Bulbs | pages 58–59 | |
| Credenza® C·L dimmers | |  |
| • LED Bulbs | pages 60–61 | |
| • CFL Bulbs | page 62 | |
| Maestro Wireless® C·L dimmers | |  |
| • LED Bulbs | pages 63–70 | |
| • CFL Bulbs | page 71 | |
| Caséta® Wireless C·L in-wall dimmers | |  |
| • LED Bulbs | pages 72–79 | |
| • CFL Bulbs | page 80 | |
| Caséta® Wireless C·L plug-in dimmers | |  |
| • LED Bulbs | pages 81–83 | |
| • CFL Bulbs | page 83 | |

Dimmable CFL & LED bulbs

Compatible with C•L® dimmers



LED bulbs for Maestro® occupancy sensor C•L dimmers

Maestro occupancy sensor C•L: MSCL-OP153M, MSCL-VP153M

Maximum wattage controlled: 150W



| Brand | Wattage | Model | Description |
|----------------------------|----------------------------|----------------------------------|---|
| Commercial Electric | 12.5W | CE-JB4-600L-27K (T47) | 4" Downlight, 600 Lumen, Soft White, 2700K |
| | 12.5W | CE-JB6-650L-27K (T67) | 6" Downlight, 650 Lumen, Soft White, 2700K |
| Cooper | 9.4W | RL560WH-R | Halo® Downlight, 600 Lumen, Warm White, 3000K |
| Cree | 6W | BA19-04527OMF-12DE26-1U100 | A19, Warm Soft White, 2700K, 450 Lumen, Medium base |
| | 6W | BA19-04527OMF-12DE26-2U100 | A19, Warm Soft White, 2700K, 450 Lumen, Medium base |
| | 6W | BA19-04550OMF-12DE26-2U500 | A19, 5000K, 450 Lumen, 40WE, 4pk |
| | 9W | BA19-08050OMF-12DE26-1U100 | A19, Daylight, 5000K, 800 Lumen, Medium base |
| | 9W | BA19-08050OMF-12DE26-2U100 | A19, Daylight, 5000K, 800 Lumen, Medium base |
| | 9.5W | BA19-08027OMF-12DE26-1U100 | A19, Warm Soft White, 2700K, 800 Lumen, Medium base |
| | 9.5W | BA19-08027OMF-12DE26-2U100 | A19, Soft White, 2700K, 800 Lumen, Medium base |
| | 9.5W | BA19-08027OMF-12DE26-2U500 | A19, 2700K, 800 Lumen, E26, 60WE, 4pk |
| | 9.5W | BBR30-06527FLF-12DE26-1U100 | BR30, 650 Lumen, Soft White, 2700K |
| | 9.5W | BBR30-06550FLF-12DE26-1U100 | BR30, Daylight, 5000K 650 Lumen, 9.5W |
| | 9.5W | CR4-575L | 4" Downlight, 2700K, 575 Lumen, Medium Base |
| | 9.5W | CR6-575L | 6" Downlight, 2700K, Medium Base |
| | 9.5W | CR6-575L-GU24 | 6" Downlight, 2700K, GU24 Base |
| | 9.5W | H1CR6TW62527E04 | 6" Downlight, 2700K, 625 Lumen |
| | 18W | BA21-16027OMF-12DE26-1U100 | A21, 2700K, 1600 Lumen, E26, 18W |
| 18W | BA21-16050OMF-12DE26-1U100 | A21, 5000K, 1600 Lumen, E26, 18W | |
| EcoSmart | 6W | ECS GP19 WW 40WE 120† | A19, 3000K |
| | 8W | ECS 19 CW 120† | A19, Cool White, 5000K |
| | 8W | ECS 19 WW 120† | A19, Warm White, 3000K |
| | 8W | ECS 20 CW FL 120 | PAR20, Daylight, 5000K, 490 Lumen |
| | 8W | ECS 20 CW FL 50WE 120† | PAR20, 5000K, 490 Lumen |
| | 8W | ECS 20 WW FL 120 | PAR20, Warm White, 3000K |
| | 8W | ECS 20 WW FL 50WE 120† | PAR20, 3000K, 450 Lumen |
| | 8W | ECS 25 WW 120 | G25, Warm White, 3000K |

† Requires a minimum of 2 lamps

© 02/2015 Lutron Electronics Co., Inc. | P/N 368-3266 REV I

Dimmable CFL & LED bulbs

Compatible with C•L® dimmers



LED bulbs for Maestro® occupancy sensor C•L dimmers

Maestro occupancy sensor C•L: MSCL-OP153M, MSCL-VP153M

Maximum wattage controlled: 150W



| Brand | Wattage | Model | Description |
|----------|---------|------------------------------|--|
| EcoSmart | 8W | ECS A19 CW 40WE 120† | A19, 5000K, 480 Lumen |
| | 8W | ECS A19 V1 CW 120 | A19, Daylight, 5000K |
| | 8W | ECS A19 V1 WW 120 | A19, Warm White, 3000K |
| | 8W | ECS A19 WW 40WE 120† | A19, 3000K, 450 Lumen |
| | 8W | ECS BR20 50WE CW 120 DG† | BR20, Daylight, 5000K, 600 Lumen, E26 |
| | 8W | ECS BR20 50WE WW 120 DG† | BR20, Warm White, 3000K, 550 Lumen, E26 |
| | 8W | ECS BR20 50WE W27 120 | BR20, Soft White, 2700K |
| | 9.5W | ECO4-575L | 4" Downlight, 2700K, 575 Lumen, Medium Base |
| | 9.5W | ECO4-575L-50K | 4" Downlight, 5000K, 575 Lumen, Medium Base |
| | 9.5W | ECO4-575L-50K-GU24 | 4" Downlight, 5000K, GU24 Base |
| | 9.5W | ECO-575L | 6" Downlight, 2700K, Medium Base |
| | 9.5W | ECO-575L-50K | 6" Downlight, 5000K, Medium Base |
| | 9.5W | ECO-575L-50K-GU24 | 6" Downlight, 5000K, GU24 Base |
| | 9.5W | ECO-575L-GU24 | 6" Downlight, 2700K, GU24 Base |
| | 10W | ECS BR30 65WE CW 120 DG | BR30, Daylight, 5000K, 700 Lumen, E26 |
| | 10W | ECS BR30 65WE CW 120 DG 3PK | BR30, Daylight, 5000K, 700 Lumen, E26, 3pk |
| | 10W | ECS BR30 65WE WW 120 DG | BR30, Warm White, 3000K, 650 Lumen, E26 |
| | 10W | ECS BR30 65WE W27 120 DG | BR30, Soft White, 2700K, 650 Lumen, E26 |
| | 10W | ECS BR30 65WE W27 120 DG 3BX | BR30, Soft White, 2700K, 650 Lumen, E26, 3pk |
| | 10.5W | ECS 30 75WE WW GB FL 120 | PAR30 Gimbal, 3000K, 750 Lumen, E26, 75WE |
| | 10.5W | ECS 30 75WE xxx GB xx 120* | PAR30 Gimbal, Various color temperatures, 75WE |
| | 11W | ECS RFK6 65WE W27 120 REC† | Downlight, Soft White, 2700K, 600 Lumen, E26 |
| | 11.5W | ECS BR30 65WE CW 120† | BR30, 5000K, Medium Base |
| | 11.5W | ECS BR30 65WE W27 120† | BR30, 2700K, 650 Lumen, Medium Base |
| | 12W | ECS A19 CW 60WE 120† | A19, 5000K, 850 Lumen |
| | 12W | ECS A19 WW 60WE 120† | A19, 3000K, 800 Lumen |

* "xx" and "xxx" denote other characters which may be included in the model number.

† Requires a minimum of 2 lamps

© 02/2015 Lutron Electronics Co., Inc. | P/N 368-3266 REV I

Dimmable CFL & LED bulbs

Compatible with C•L® dimmers



LED bulbs for Maestro® occupancy sensor C•L dimmers

Maestro occupancy sensor C•L: MSCL-OP153M, MSCL-VP153M

Maximum wattage controlled: 150W



| Brand | Wattage | Model | Description |
|----------|---------|--------------------------|---|
| EcoSmart | 13W | ECS 30 CW FL 75WE 120 | PAR30, 5000K, 810 Lumen |
| | 13W | ECS 30 WW FL 75WE 120 | PAR30, 3000K, 750 Lumen |
| | 13W | ECS A19 V2 CW 120 | A19, Daylight, 5000K |
| | 13W | ECS A19 V2 WW 120 | A19, Warm White, 3000K |
| | 14W | ECS BR40 90WE CW 120 DG | BR40, Daylight, 5000K, 1050 Lumen, E26 |
| | 14W | ECS BR40 90WE W27 120 DG | BR40, 2700K, 1000 Lumen, E26 |
| | 15W | ECS 38 CW FL 90WE 120 | PAR38, 5000K, 970 Lumen |
| | 15W | ECS 38 WW FL 90WE 120 | PAR38, 3000K, 900 Lumen |
| | 15W | ECS BR30 W27 FL 120 | BR30, Soft White, 2700K |
| | 16W | ECS BR40 W27 FL 120† | BR40, Soft White, 2700K |
| | 17W | ECS 30 V2 WW FL 120 | PAR30, Warm White, 3000K |
| | 18W | ECS 38 CW FL 120† | PAR38, Daylight, 5000K |
| | 18W | ECS 38 WW FL 120† | PAR38, Warm White, 3000K |
| | 24W | ECS 38 V2 WW FL 120 | PAR38, Warm White, 3000K |
| Feit | 3.5W | CFCDM/LED† | Candle, Flame Tip Clear, 3000K, Candelabra Base |
| | 3.5W | EFCDM/LED† | Candle, Flame Tip Clear, 3000K, Medium Base |
| | 4.5W | R14DM/LED | R14, Soft White, 2700K, 300 Lumen, E26, 40WE |
| | 4.8W | CFCDM/300/LED†† | Candle, 3000K, 310 Lumen, Candelabra Base |
| | 4.8W | EFCDM/300/LED†† | Candle, 3000K, 310 Lumen, Medium Base |
| | 6.5W | BPMR16/GU10/DM/LED† | MR16, GU10 base |
| | 6.5W | MR16/GU10/DM/LED† | MR16, GU10 base |
| | 6.5W | R16DM/LED | R16, Soft White, 2700K, 400 Lumen, E26, 40WE |
| | 7.5W | PAR20DM/5K/LED | PAR20, 5000K |
| | 7.5W | PAR20DM/LED | PAR20, 3000K |
| | 8W | A19/DM/GU24/LED | A19, 3000K, GU24 Base |
| | 8W | A19/DM/LED | A19, 3000K |
| | 8W | A19/DM/LED/CAN | A19 |
| | 8W | A19/DM/LED/RP/CAN | A19 |

† Requires a minimum of 2 lamps

†† Requires a minimum of 3 lamps

© 02/2015 Lutron Electronics Co., Inc. | P/N 368-3266 REV I

Dimmable CFL & LED bulbs

Compatible with C•L® dimmers



LED bulbs for Maestro® occupancy sensor C•L dimmers

Maestro occupancy sensor C•L: MSCL-OP153M, MSCL-VP153M

Maximum wattage controlled: 150W



| Brand | Wattage | Model | Description |
|-------|---------|-----------------------|--|
| Feit | 8W | A19DM/5K/LED | A19, 5000K |
| | 8W | BPCEA19/DM/LED | A19 |
| | 8W | BPCER20/DM/LED | R20, 2700K, 450 Lumen, E26 Medium base (70mA smooth reflector version) |
| | 8W | R20/927/LED | R20, 2700K |
| | 8W | R20/930/LED | R20, 3000K |
| | 8W | R20/950/LED | R20, 5000K |
| | 8W | R20DM/LEDG2/CAN | R20, 2700K |
| | 9.5W | BPCER20/DM/LED | PAR20 |
| | 9.5W | PAR20/5K/LEDG5 | PAR20, 5000K |
| | 9.5W | PAR20/5K/LEDG5/CAN | PAR20, 5000K |
| | 9.5W | PAR20/LEDG5 | PAR20, 3000K, 450 Lumen |
| | 9.5W | PAR20/LEDG5/CAN | PAR20 |
| | 10W | BPAG800/5K/LED | A19, 5000K |
| | 10W | BPAG800/LED | A19, 3000K, 800 Lumen |
| | 10W | G25/DM/LED† | G25, 3000K |
| | 13W | BPCEBR30LED | BR30 |
| | 13.5W | A19/OM800/5K/LED | A19, 5000K, Omni Directional |
| | 13.5W | A19/OM800/LED | A19, 3000K, Omni Directional |
| | 13.5W | A19DM/800/LED | A19, 3000K |
| | 13.5W | BPCEA19/OM800/LED | A19, Omni Directional |
| | 13.5W | BPCEA19/OM800/LED/CAN | A19, Omni Directional |
| | 15W | BPCEPAR30/LEDG5 | PAR30 |
| | 15W | PAR30L/5K/LEDG5 | PAR30, 5000K |
| | 15W | PAR30L/5K/LEDG5/CAN | PAR30, 5000K |
| | 15W | PAR30L/LEDG5 | PAR30 |
| | 15W | PAR30L/LEDG5/CAN | PAR30 |
| | 16W | A19/OM1100R/LED | A19, 3000K, 1100 Lumen, Omni Directional |
| | 16.8W | LEDR56/3K | 5" or 6" Downlight, 3000K, 840 Lumen |
| | 17W | BPCEBR40/LED | BR40, 2700K, 1065 Lumen |
| | 17W | BR40/DM/LED† | BR40, 2700K, 1065 Lumen |
| | 18W | 18PAR38/DM/LED | PAR38, 3000K |
| | 18W | PAR38DM/5K/LED | PAR38, 5000K |

† Requires a minimum of 2 lamps

© 02/2015 Lutron Electronics Co., Inc. | P/N 368-3266 REV I

Dimmable CFL & LED bulbs

Compatible with C·L® dimmers



LED bulbs for Maestro® occupancy sensor C·L dimmers

Maestro occupancy sensor C·L: MSCL-OP153M, MSCL-VP153M

Maximum wattage controlled: 150W



| Brand | Wattage | Model | Description | |
|-------|---------|--------------------|---|---------------------------------------|
| Feit | 18W | PAR38DM/LED | PAR38, 3000K | |
| | 20W | 20PAR38/LEDG5 | PAR38 | |
| | 20W | BPCEPAR38/LEDG5 | PAR38 | |
| | 20W | PAR38/5K/LEDG5 | PAR38, 5000K | |
| | 20W | PAR38/5K/LEDG5/CAN | PAR38, 5000K | |
| | 20W | PAR38/LEDG5 | PAR38 | |
| | 20W | PAR38/LEDG5/CAN | PAR38 | |
| | 20.5W | LEDR56/827 | 5" or 6" Downlight, 2700K, 1245 Lumen | |
| | 22W | A/OM1600R/27K/LED | A21, 2700K, 1600 Lumen | |
| | 22W | A/OM1600R/5K/LED | A21, Daylight, 5000K, 1600 Lumen | |
| | 22W | A/OM1600R/LED | A21, Warm White, 3000K, 1600 Lumen | |
| | GE | 8W | LED8DA19/827 | A19, 2700K, 450 Lumen, E26 |
| | | 10W | LED10DP30S827/20 | PAR30, 2700K, Short Neck, Silver Base |
| 10W | | LED10DP30S830/20 | PAR30, 3000K, Short Neck, Silver Base | |
| 10W | | LED10DP30W827/20 | PAR30, 2700K, Short Neck, White Base | |
| 11W | | LED11DA19RVL/TP | A19, 2700K, 570 Lumen | |
| 11W | | LED11DA19V2 | A19, 2700K, 800 Lumen | |
| 12W | | LED12DR30RVL/BK | BR30, Reveal | |
| 12W | | LED12DR30RVL/CDN | BR30, Reveal | |
| 12W | | LED12DR30RVL/TP | BR30, Reveal 2850K, 630 Lumen | |
| 18W | | LED18D38W827/15 | PAR38, 2700K, E26, 15° Beam | |
| 18W | | LED18D38W827/25 | PAR38, 2700K, E26, 25° Beam | |
| 18W | | LED18D38W827/40 | PAR38, 2700K, E26, 40° Beam | |
| 18W | | LED18D38W830/15 | PAR38, 3000K, 1400 Lumen, E26, 15° Beam | |
| 18W | | LED18D38W830/25 | PAR38, 3000K, 1400 Lumen, E26, 25° Beam | |
| 18W | | LED18D38W830/40 | PAR38, 3000K, 1400 Lumen, E26, 40° Beam | |
| 18W | | LED18D38W927/15 | PAR38, 2700K, 1100 Lumen, E26, 15° Beam | |
| 18W | | LED18D38W927/25 | PAR38, 2700K, 1100 Lumen, E26, 25° Beam | |
| 18W | | LED18D38W927/40 | PAR38, 2700K, 1100 Lumen, E26, 40° Beam | |
| 18W | | LED18D38W930/15 | PAR38, 3000K, 1200 Lumen, E26, 15° Beam | |
| 18W | | LED18D38W930/25 | PAR38, 3000K, 1200 Lumen, E26, 25° Beam | |
| 18W | | LED18D38W930/40 | PAR38, 3000K, 1200 Lumen, E26, 40° Beam | |

Dimmable CFL & LED bulbs

Compatible with C•L® dimmers



LED bulbs for Maestro® occupancy sensor C•L dimmers

Maestro occupancy sensor C•L: MSCL-OP153M, MSCL-VP153M

Maximum wattage controlled: 150W



| Brand | Wattage | Model | Description |
|-------------------------|---------|--------------------|--------------------------------|
| Halco | 20W | PAR38FL20/827/LED | PAR38, 2700K, 1150 Lumen Flood |
| | 20W | PAR38FL20/830/LED | PAR38, 3000K, 1200 Lumen Flood |
| | 20W | PAR38FL20/840/LED | PAR38, 4000K, 1250 Lumen Flood |
| | 20W | PAR38FL20/850/LED | PAR38, 5000K, 1300 Lumen Flood |
| Halco | 20W | PAR38NFL20/827/LED | PAR38, 2700K, 1150 Lumen Flood |
| | 20W | PAR38NFL20/830/LED | PAR38, 3000K, 1200 Lumen Flood |
| | 20W | PAR38NFL20/840/LED | PAR38, 4000K Flood |
| | 20W | PAR38NFL20/850/LED | PAR38, 5000K, 1300 Lumen Flood |
| | 20W | PAR38SP20/827/LED | PAR38, 2700K, 1150 Lumen Spot |
| | 20W | PAR38SP20/830/LED | PAR38, 3000K, 1200 Lumen Spot |
| | 20W | PAR38SP20/840/LED | PAR38, 4000K Spot |
| | 20W | PAR38SP20/850/LED | PAR38, 5000K, 1300 Lumen Spot |
| Lighting Science | 8W | DFN 19 CW 120† | A19, Cool White, 5000K |
| | 8W | DFN 19 NW 120† | A19, Neutral White, 4000K |
| | 8W | DFN 19 W27 120† | A19, Warm White, 2700K |
| | 8W | DFN 19 WW 120† | A19, Warm White, 3000K |
| | 8W | DFN 20 CW FL 120 | PAR20, Cool White, 5000K |
| | 8W | DFN 20 CW NFL 120 | PAR20, Cool White, 5000K |
| | 8W | DFN 20 NW FL 120 | PAR20, Neutral White, 4000K |
| | 8W | DFN 20 NW NFL 120 | PAR20, Neutral White, 4000K |
| | 8W | DFN 20 W27 FL 120 | PAR20, Warm White, 2700K |
| | 8W | DFN 20 W27 NFL 120 | PAR20, Warm White, 2700K |
| | 8W | DFN 20 WW FL 120 | PAR20, Warm White, 3000K |
| | 8W | DFN 20 WW NFL 120 | PAR20, Warm White, 3000K |
| | 8W | DFN 25 CW 120 | G25, Cool White, 5000K |
| | 8W | DFN 25 NW 120 | G25, Neutral White, 4000K |
| | 8W | DFN 25 W27 120 | G25, Warm White, 2700K |
| | 8W | DFN 25 WW 120 | G25, Warm White, 3000K |
| | 8W | DFN A19 V1 CW 120 | A19, Cool White, 5000K |
| | 8W | DFN A19 V1 NW 120 | A19, Neutral White, 4000K |
| | 8W | DFN A19 V1 W27 120 | A19, Warm White, 2700K |
| | 8W | DFN A19 V1 WW 120 | A19, Warm White, 3000K |

† Requires a minimum of 2 lamps

© 02/2015 Lutron Electronics Co., Inc. | P/N 368-3266 REV I

Dimmable CFL & LED bulbs

Compatible with C•L® dimmers



LED bulbs for Maestro® occupancy sensor C•L dimmers

Maestro occupancy sensor C•L: MSCL-OP153M, MSCL-VP153M

Maximum wattage controlled: 150W



| Brand | Wattage | Model | Description |
|------------------|---------|---------------------------|---|
| Lighting Science | 10.5W | LS 30 75WE xxx GB xx 120* | PAR30, various color temperatures |
| | 11.5W | DFN BR30 65WE CW 120† | BR30, Cool White, 5000K, Medium base |
| | 11.5W | DFN BR30 65WE NW 120† | BR30, Neutral White, 4000K, Medium base |
| | 11.5W | DFN BR30 65WE W27 120† | BR30, Warm White, 2700K, Medium base |
| | 11.5W | DFN BR30 65WE WW 120† | BR30, Warm White, 3000K, Medium base |
| | 13W | LS GLP6 W27 120 WH S1 BX | 6" Downlight, 2700K, E26 retrofit |
| | 13.5W | DFN A19 V2 CW 120 | A19, Cool White, 5000K |
| | 13.5W | DFN A19 V2 NW 120 | A19, Neutral White, 4000K |
| | 13.5W | DFN A19 V2 W27 120 | A19, Warm White, 2700K |
| | 13.5W | DFN A19 V2 WW 120 | A19, Warm White, 3000K |
| | 15W | DFN BR30 CW FL 120 | BR30, Cool White, 5000K |
| | 15W | DFN BR30 NW FL 120 | BR30, Neutral White, 4000K |
| | 15W | DFN BR30 W27 FL 120 | BR30, Warm White, 2700K |
| | 15W | DFN BR30 WW FL 120 | BR30, Warm White, 3000K |
| | 16W | DFN BR40 CW 120† | BR40, Cool White, 5000K |
| | 16W | DFN BR40 NW 120† | BR40, Neutral White, 4000K |
| | 16W | DFN BR40 W27 120† | BR40, Warm White, 2700K |
| | 16W | DFN BR40 WW 120† | BR40, Warm White, 3000K |
| | 17W | DFN 30 CW V2 FL 120 | PAR30, Cool White, 5000K |
| | 17W | DFN 30 CW V2 NFL 120 | PAR30, Cool White, 5000K |
| | 17W | DFN 30 NW V2 FL 120 | PAR30, Neutral White, 4000K |
| | 17W | DFN 30 NW V2 NFL 120 | PAR30, Neutral White, 4000K |
| | 17W | DFN 30 W27 V2 FL 120 | PAR30, Warm White, 2700K |
| | 17W | DFN 30 W27 V2 NFL 120 | PAR30, Warm White, 2700K |
| | 17W | DFN 30 WW V2 FL 120 | PAR30, Warm White, 3000K |
| | 17W | DFN 30 WW V2 NFL 120 | PAR30, Warm White, 3000K |
| | 18W | DFN 38 CW FL 120† | PAR38, Cool White, 5000K |
| | 18W | DFN 38 CW NFL 120† | PAR38, Cool White, 5000K |
| | 18W | DFN 38 NW FL 120† | PAR38, Neutral White, 4000K |
| | 18W | DFN 38 NW NFL 120† | PAR38, Neutral White, 4000K |
| | 18W | DFN 38 W27 FL 120† | PAR38, Warm White, 2700K |
| | 18W | DFN 38 W27 NFL 120† | PAR38, Warm White, 2700K |

* "xx" and "xxx" denote other characters which may be included in the model number.

† Requires a minimum of 2 lamps

© 02/2015 Lutron Electronics Co., Inc. | P/N 368-3266 REV I

Dimmable CFL & LED bulbs

Compatible with C•L® dimmers



LED bulbs for Maestro® occupancy sensor C•L dimmers

Maestro occupancy sensor C•L: MSCL-OP153M, MSCL-VP153M

Maximum wattage controlled: 150W



| Brand | Wattage | Model | Description |
|------------------|---------|-------------------------------------|--|
| Lighting Science | 18W | DFN 38 WW FL 120 [†] | PAR38, Warm White, 3000K |
| | 18W | DFN 38 WW NFL 120 [†] | PAR38, Warm White, 3000K |
| | 24W | DFN 38 CW V2 FL 120 | PAR38, Cool White, 5000K |
| | 24W | DFN 38 CW V2 NFL 120 | PAR38, Cool White, 5000K |
| | 24W | DFN 38 NW V2 FL 120 | PAR38, Neutral White, 4000K |
| | 24W | DFN 38 NW V2 NFL 120 | PAR38, Neutral White, 4000K |
| | 24W | DFN 38 W27 V2 FL 120 | PAR38, Warm White, 2700K |
| | 24W | DFN 38 W27 V2 NFL 120 | PAR38, Warm White, 2700K |
| | 24W | DFN 38 WW V2 FL 120 | PAR38, Warm White, 3000K |
| | 24W | DFN 38 WW V2 NFL 120 | PAR38, Warm White, 3000K |
| Litetronics | 14W | LP14550FL2D | BR30, 2700K, 925 Lumen |
| | 14W | LP14550FL4D | BR30, 3000K, 925 Lumen |
| | 14W | LP14550FL6D | BR30, 4000K, 925 Lumen |
| Lumapro | 8W | 8A19/LED/DIM/30 [†] | A19, Warm White, 3000K (6GEM2) |
| | 8W | 8A19/LED/DIM/50 [†] | A19, Cool White, 5000K (6GEM3) |
| | 8W | 8PAR20/LED/DIM30/NFL | PAR20, Warm White, 3000K (6GEM4) |
| | 8W | 8PAR20/LED/DIM50/NFL | PAR20, Cool White, 5000K (6GEM5) |
| | 18W | 18PAR38/LED/DIM/30/NFL [†] | PAR38, Warm White, 3000K |
| | 18W | 18PAR38/LED/DIM/50/NFL [†] | PAR38, Cool White, 5000K |
| Philips | 4W | 9290002120 | MR16, Bright White, 3000K, 200 Lumen, GU10, 4W |
| | 4.5W | 9290002439 | Candle, Warm White, 2700K, 320 Lumen, E26 base, Post Light |
| | 4.5W | 9290002797 ^{††} | Candle, 2700K, 330 Lumen, E26, blunt tip |
| | 4.5W | 9290002889 ^{††} | Candle, 2700K, 330 Lumen, E12, blunt tip |
| | 4.5W | 9290002890 ^{††} | A15, 2700K, 330 Lumen, E12 |
| | 4.5W | 9290002891 ^{††} | A15, 2700K, 330 Lumen, E26 |
| | 6W | 9290002443 | PAR16, 3000K, 300 Lumen, E26 |
| | 6W | 9290002242 | MR16, 3000K, 300 Lumen, GU10 base |
| | 7W | 9290002020 | PAR20, 2700K, 280 Lumen, Medium Base |
| | 7W | 9290002706 | A19 SlimStyle, Daylight, 5000K, 450 Lumen, E26 |

[†] Requires a minimum of 2 lamps

^{††} Requires a minimum of 3 lamps

© 02/2015 Lutron Electronics Co., Inc. | P/N 368-3266 REV I

Dimmable CFL & LED bulbs

Compatible with C·L® dimmers



LED bulbs for Maestro® occupancy sensor C·L dimmers

Maestro occupancy sensor C·L: MSCL-OP153M, MSCL-VP153M

Maximum wattage controlled: 150W



| Brand | Wattage | Model | Description |
|---------|---------|-----------------|---|
| Philips | 7W | 7E26A55-E | A19, 2700K, 240 Lumen |
| | 7W | 7E26PAR20D-1 | PAR20, 2700K, 280 Lumen, Medium Base |
| | 7W | 7E26PAR20-E | PAR20, 2700K |
| | 8W | 9290002192 | R20, 2700K, 530 Lumen, Medium base |
| | 8W | 9290002267 | A19, 2700K, 470 Lumen |
| | 8W | 9290002295 | A19, 5000K, 470 Lumen |
| | 8W | 9290002329 | PAR20, 3000K, 470 Lumen, E26 |
| | 8W | 9290002330 | PAR20 |
| | 8W | 9290002331 | PAR20 |
| | 8W | 9290002332 | PAR20 |
| | 8W | 9290002333 | PAR20 |
| | 8W | 9290002334 | PAR20 |
| | 8W | 9290002335 | PAR20 |
| | 8W | 9290002704 | A19 SlimStyle, 2700K, 450 Lumen, E26, 40WE |
| | 8W | 9E26A19DCCAAAA | A19, 2700K, 507 Lumen |
| | 8.5W | 9290002543 | BR30, 5000K, 730 Lumen, 8.5W |
| | 9.5W | 9290011117 | BR30, 2700K, 730 Lumen, WarmGlow to 2200K (Nov 2014 or later) |
| | 9.5W | 9290011118 | BR30 SlimStyle, 2700K, 650 Lumen, E26, 65WE |
| | 9.5W | 9290011119 | BR30 SlimStyle, 5000K, 650 Lumen, E26, 65WE |
| | 10.5W | 9290002544 | BR30, 2700K, 730 Lumen |
| | 11W | 9290002268 | A19, 2700K, 830 Lumen |
| | 11W | 9290002296 | A19, 5000K, 830 Lumen |
| | 11W | 9290011113 | PAR30L, 3000K, E26 |
| | 12W | 12E26PAR30L-E2 | PAR30, 3000K |
| | 12.5W | 9290001829 | A19, 2700K, 908 Lumen |
| | 12.5W | 12E26A60 | A19, 2700K |
| | 13W | 9290002233 | PAR30, 2700K, 784 Lumen |
| | 13W | 9290002234 | PAR30, 2700K, 770 Lumen |
| | 13W | 13E26B30DAAABAA | BR30, 3000K |

Dimmable CFL & LED bulbs

Compatible with C·L® dimmers



LED bulbs for Maestro® occupancy sensor C·L dimmers

Maestro occupancy sensor C·L: MSCL-OP153M, MSCL-VP153M

Maximum wattage controlled: 150W



| Brand | Wattage | Model | Description | |
|---------|---------|---------------|---|-------------------------|
| Philips | 13W | 9290002197 | BR30, 2700K, 721 Lumen | |
| | 13W | 9290002201 | PAR30, 3000K, 750 Lumen | |
| | 13W | 9290002323 | PAR30, 5000K, 850 Lumen | |
| | 13W | 9290002523 | 13PAR38/F25 3000 DIM AF RO | PAR38, 3000K, 950 Lumen |
| | 14.5W | 9290002199 | BR40, 2700K, 832 Lumen | |
| | 15W | 9290002426 | A21, 2700K, 1180 Lumen | |
| | 15W | 9290002595 | A21, Soft White, 2700K, 1180 Lumen, E26 | |
| | 15W | 9290011111 | PAR38, 3000K, 1050 Lumen, E26, Flood | |
| | 15W | 9290011112 | PAR38, 5000K, 1050 Lumen, E26, Flood | |
| | 17W | 9290002018 | A21, 2700K | |
| | 17W | 17E26A21D | A21, 2700K | |
| | 17W | 17E26PAR38-E2 | PAR38, 3000K | |
| | 18W | 9290002202 | PAR38, 3000K, 951 Lumen, Medium Base | |
| | 18W | 9290002236 | PAR38 | |
| | 18W | 9290002237 | PAR38 | |
| | 18W | 9290002245 | PAR38, 2700K, 938 Lumen | |
| | 18W | 9290002246 | PAR38 | |
| | 18W | 9290002307 | PAR38 | |
| | 18W | 9290002308 | PAR38 | |
| | 18W | 9290002309 | PAR38 | |
| | 18W | 9290002310 | PAR38 | |
| | 18W | 9290002311 | PAR38 | |
| | 18W | 18E26PAR38-3 | PAR38 | |
| | 18W | 18E26PAR38-4 | PAR38 | |
| | 19W | 9290002473 | PAR38, 3000K, 1250 Lumen | |
| | 19.5W | 9290002251 | PAR38, 3000K, 1210 Lumen | |
| | 19.5W | 9290002252 | PAR38, 2700K, 1183 Lumen | |
| | 19.5W | 9290002253 | PAR38, 3000K, 1212 Lumen | |
| | 19.5W | 9290002291 | PAR38, 4000K, 1207 Lumen | |
| | 19.5W | 9290002312 | PAR38, 2700K, 1100 Lumen | |
| | 19.5W | 9290002313 | PAR38, 2700K, 1196 Lumen | |
| | 19.5W | 9290002314 | PAR38, 3000K, 1200 Lumen | |

Dimmable CFL & LED bulbs

Compatible with C·L® dimmers



LED bulbs for Maestro® occupancy sensor C·L dimmers

Maestro occupancy sensor C·L: MSCL-OP153M, MSCL-VP153M

Maximum wattage controlled: 150W



| Brand | Wattage | Model | Description |
|---------|---------|---------------------|--|
| Philips | 19.5W | 9290002315 | PAR38, 3000K, 1225 Lumen |
| | 19.5W | 9290002316 | PAR38, 4000K, 1200 Lumen |
| | 19.5W | 9290002317 | PAR38, 4000K, 1245 Lumen |
| | 19.5W | 9290002321 | PAR38, 2700K, 1172 Lumen |
| | 19.5W | 9290002322 | PAR38, 5000K, 1300 Lumen |
| | 22W | 9290002290 | A21, 2700K, 1780 Lumen, Medium base |
| Satco | 11W | S9084 | PAR30, 3000K, 780 Lumen, E26, short neck, 25° Beam |
| | 11W | S9085 | PAR30, 4000K, 780 Lumen, E26, short neck, 25° Beam |
| | 11W | S9086 | PAR30, 3000K, 780 Lumen, E26, short neck, 40° Beam |
| | 11W | S9087 | PAR30, 4000K, 780 Lumen, E26, short neck, 40° Beam |
| | 11W | S9088 | PAR30, 3000K, 780 Lumen, E26, long neck, 25° Beam |
| | 11W | S9089 | PAR30, 4000K, 780 Lumen, E26, long neck, 25° Beam |
| | 11W | S9090 | PAR30, 3000K, 780 Lumen, E26, long neck, 40° Beam |
| | 11W | S9091 | PAR30, 4000K, 780 Lumen, E26, long neck, 40° Beam |
| | 17W | S8977-S8979 | PAR38 |
| | 17W | S8984-S8986 | PAR38 |
| | 17W | S9092 | PAR38, 3000K, 1200 Lumen, E26, 25° beam |
| | 17W | S9093 | PAR38, 4000K, 1200 Lumen, E26, 25° beam |
| | 17W | S9094 | PAR38, 3000K, 1200 Lumen, E26, 40° beam |
| | 17W | S9095 | PAR38, 4000K, 1200 Lumen, E26, 40° beam |
| | 28W | LR38/15/27K/2000/xx | PAR38, 2700K, 2000 Lumen, E26 |
| | 28W | LR38/15/30K/2100/xx | PAR38, 3000K, 2100 Lumen, E26 |
| | 28W | LR38/25/27K/2000/xx | PAR38, 2700K, 2000 Lumen, E26 |
| | 28W | LR38/25/30K/2100/xx | PAR38, 3000K, 2100 Lumen, E26 |
| | 28W | LR38/40/27K/2000/xx | PAR38, 2700K, 2000 Lumen, E26 |
| | 28W | LR38/40/30K/2100/xx | PAR38, 3000K, 2100 Lumen, E26 |

Dimmable CFL & LED bulbs

Compatible with C•L® dimmers



LED bulbs for Maestro® occupancy sensor C•L dimmers

Maestro occupancy sensor C•L: MSCL-OP153M, MSCL-VP153M

Maximum wattage controlled: 150W



| Brand | Wattage | Model | Description |
|--------|--------------|---|---|
| Solais | 7W | LRP20/25/27K | PAR20, 2700K, 475 Lumen, E26, 25° Beam |
| | 7W | LRP20/25/30K | PAR20, 3000K, 500 Lumen, E26, 25° Beam |
| | 7W | LRP20/40/27K | PAR20, 2700K, 475 Lumen, E26, 40° Beam |
| | 7W | LRP20/40/30K | PAR20, 3000K, 500 Lumen, E26, 40° Beam |
| | 11W | LR20/25/27K/675/xx | PAR20, 2700K, 675 Lumen, E26, narrow flood |
| | 11W | LR20/25/30K/750 | PAR20, 3000K, 750 Lumen, E26, narrow flood |
| | 11W | LR20/40/27K/675/xx | PAR20, 2700K, 675 Lumen, E26, wide flood |
| | 11W | LR20/40/30K/750/xx | PAR20, 3000K, 750 Lumen, E26, wide flood |
| | 16W | LR30/10/27K/1100/xx | PAR30, 2700K, 1100 Lumen, E26, short neck, 10° Beam |
| | 16W | LR30/10/30K/1125/xx | PAR30, 3000K, 1125 Lumen, E26, short neck, 10° Beam |
| | 16W | LR30/10/30K/1200/xx | PAR30, 3000K, 1200 Lumen, E26, short neck, 10° Beam |
| | 16W | LR30/15/27K/1100/xx | PAR30, 2700K, 1100 Lumen, E26, short neck, 15° Beam |
| | 16W | LR30/15/30K/1125/xx | PAR30, 3000K, 1125 Lumen, E26, short neck, 15° Beam |
| | 16W | LR30/15/30K/1200/xx | PAR30, 3000K, 1200 Lumen, E26, short neck, 15° Beam |
| | 16W | LR30/25/27K/1100/xx | PAR30, 2700K, 1100 Lumen, E26, short neck, 25° Beam |
| | 16W | LR30/25/30K/1125/xx | PAR30, 3000K, 1125 Lumen, E26, short neck, 25° Beam |
| | 16W | LR30/25/30K/1200/WH | PAR30, 3000K, 1200 Lumen, E26, short neck, 25° Beam |
| | 16W | LR30/40/27K/1100/xx | PAR30, 2700K, 1100 Lumen, E26, short neck, 40° Beam |
| | 16W | LR30/40/30K/1125/xx | PAR30, 3000K, 1125 Lumen, E26, short neck, 40° Beam |
| | 16W | LR30/40/30K/1200/xx | PAR30, 3000K, 1200 Lumen, E26, short neck, 40° Beam |
| 16W | LRP38/25/27K | PAR38, 2700K, 1025 Lumen, E26, 25° Beam | |

Dimmable CFL & LED bulbs

Compatible with C•L® dimmers



LED bulbs for Maestro® occupancy sensor C•L dimmers

Maestro occupancy sensor C•L: MSCL-OP153M, MSCL-VP153M

Maximum wattage controlled: 150W



| Brand | Wattage | Model | Description |
|-----------------|---------|------------------------------------|--|
| Solais | 16W | LRP38/25/30K | PAR38, 3000K, 1100 Lumen, E26, 25° Beam |
| | 16W | LRP38/40/27K | PAR38, 2700K, 1025 Lumen, E26, 40° Beam |
| | 16W | LRP38/40/30K | PAR38, 3000K, 1100 Lumen, E26, 40° Beam |
| | 20W | LR38/25/30K/1450/SL | PAR38, 3000K, 1450 Lumen, E26, 15° Beam |
| Switch | 10W | A260FUS27B1 | A19, 800 Lumen |
| | 13W | 75FU202 | A19, 3000K, 1100 Lumen, E26 |
| Sylvania | 7W | 79120 | PAR20, 2700K, 500 Lumen, E26 |
| | 8W | LED8A19DIM0827RP | A19, 2700K, 470 Lumen, E26 |
| | 8W | LED8A/DIM/F/827† | A19, 2700K |
| | 8W | LED8A/DIM/F/830† | A19, 3000K |
| | 8W | LED8A15/DIM/827† | A15, 2700K, 450 Lumen, Medium Base |
| | 8W | LED8A15C/DIM/827† | A15, 2700K, 450 Lumen, Candelabra Base |
| | 8W | LED8G25/DIM/F/827 | G25, 2700K |
| | 8W | LED8G25/DIM/F/830 | G25, 3000K |
| | 8W | LED8PAR16/DIM/930/FL36/P/LW | PAR16, Soft White, 390 Lumen |
| | 8W | LED8PAR16/GU10/DIM/930/FL36/RP | PAR16, GU10, Soft White, 390 Lumen |
| | 8W | LED8PAR20/DIM/827/FL36 | PAR 20, 2700K |
| | 8W | LED8PAR20/DIM/827/NFL25 | PAR 20, 2700K |
| | 8W | LED8PAR20/DIM/830/FL36 | PAR 20, 3000K |
| | 8W | LED8PAR20/DIM/830/NFL25 | PAR 20, 3000K |
| | 8W | LED8R20/DIM/SE/830/RP | R20, Soft White, 2700K to 2000K, 520 Lumen |
| | 9W | LED/550/RT4/827/FL80/WRFL† | 4" Downlight, 2700K |
| | 9W | LED/550/RT4/830/FL80/WRFL† | 4" Downlight, 3000K |
| | 10W | LED/600/RT4/830/FL80/RP† | Recessed lighting kit, 3000K, 600 Lumen |
| | 10W | LED/700/RT6/830/FL80/RP | Recessed lighting kit, 3000K, 625 Lumen |
| | 10W | LED/RT4/600/827/FL80† | Recessed lighting kit, 2700K, 600 Lumen |
| | 10W | LED/RT6/700/830/FL80 | Recessed lighting kit, 3000K, 700 Lumen |
| | 10W | LED10PAR20/DIM//P/930/FL30 | PAR20, 3000K, 550 Lumen |
| | 11W | LED11BR30/DIM/HO/827/G3 (78413) | BR30, 2700K, 800 Lumen, E26 |
| | 11W | LED11BR30/DIM/HO/827/G3/RP (78415) | BR30, 2700K, 800 Lumen, E26 |
| | 11W | LED11BR30/DIM/HO/827/G3/RP (79121) | BR30, 2700K, 800 Lumen, E26 |

† Requires a minimum of 2 lamps

© 02/2015 Lutron Electronics Co., Inc. | P/N 368-3266 REV I

Dimmable CFL & LED bulbs

Compatible with C•L® dimmers



LED bulbs for Maestro® occupancy sensor C•L dimmers

Maestro occupancy sensor C•L: MSCL-OP153M, MSCL-VP153M

Maximum wattage controlled: 150W



| Brand | Wattage | Model | Description |
|-----------|---------|--------------------------------|--|
| Sylvania | 12W | LED12BR30/DIM/HO/827 | BR30, 2700K, Medium base |
| | 12W | LED12BR30/DIM/HO/827/HVP | BR30, 2700K, Medium base |
| | 12W | LED12BR30/DIM/SE/830/RP | BR30, Soft White, 2700K to 2000K, 850 Lumen |
| | 15W | LED15BR40/DIM/HO/827/G3/RP | BR40, Soft White, 2700K, 1100 Lumen, E26, Flood |
| | 15W | LED15PAR30/DIM/P/930/FL40 | PAR30, 3000K |
| | 15W | LED15PAR30LN/DIM/827/FL40 | PAR30, 2700K |
| | 15W | LED15PAR30LN/DIM/830/NFL25 | PAR30, 3000K |
| | 16W | LED16BR40DIMHO827 | BR40, 2700K, 1100Lumen |
| | 17W | LED17PAR30LN/DIM/830/WSP15/P | PAR30, 3000K, 1200 Lumen, E26, spot |
| | 17W | LED17PAR30LN/DIM/830/WSP20 | PAR30, 3000K, 1200 Lumen, E26, wide spot |
| | 17W | LED17PAR30LN/DIM/P/930/NFL25 | PAR30, 3000K, 900 Lumen |
| | 20W | LED20PAR38/DIM/930/FL40/P2 | PAR38, 3000K, 1000 Lumen |
| | 20W | LED20PAR38DIM830FL40 | PAR38, 3000K, 1300 Lumen |
| | 21W | LED21/PAR38/DIM/P/930/FL30/HVP | PAR38, Warm White, 3000K, 1100 Lumen, E26, 21W |
| | 21W | LED21PAR38/DIM/P/930/FL30 | PAR38, 3000K, 1100 Lumen |
| Toshiba | 13W | LDRB1327WE6USD2 (13BR40/27K-T) | BR40, 2700K, 950 Lumen |
| | 13W | LDRB1340WE6USD2 (13BR40/40L-T) | BR40, 4000K, 1050 Lumen |
| Utilitech | 3W | LG161/2DM/IF/LED† | G16.5, Warm White, 3000K, 200 Lumen, E12 base, frosted |
| | 3.5W | LCFCDM/LED† | Candle, Flame Tip Clear, 3000K, Candelabra Base |
| | 3.5W | LEFCDM/LED† | Candle, Flame Tip Clear, 3000K, Medium Base |
| | 4.5W | LR14DMLED | R14, Soft White, 2700K, 300 Lumen, E26, 40WE |
| | 4.8W | LA15DM/CL/300/LED† | A15, Warm White, 3000K, 300 Lumen, E26, clear |
| | 4.8W | LA15DM/IF/300/LED† | A15, Warm White, 3000K, 300 Lumen, E26, frosted |
| | 4.8W | LA15DMC/CL/300/LED† | A15, Warm White, 3000K, 300 Lumen, E12 base, clear |

† Requires a minimum of 2 lamps

© 02/2015 Lutron Electronics Co., Inc. | P/N 368-3266 REV I

Dimmable CFL & LED bulbs

Compatible with C•L® dimmers



LED bulbs for Maestro® occupancy sensor C•L dimmers

Maestro occupancy sensor C•L: MSCL-OP153M, MSCL-VP153M

Maximum wattage controlled: 150W



| Brand | Wattage | Model | Description |
|-----------|---------|-----------------------------------|--|
| Utilitech | 4.8W | LCFCDM/300/LED ^{††} | Candle, 3000K, 310 Lumen, E26, flame tip, clear |
| | 4.8W | LCFFDM/300/LED [†] | Candle, Warm White, 3000K, 300 Lumen, E12 base, frosted flame tip |
| | 4.8W | LEFCDM/300/LED ^{††} | Candle, 3000K, 310 Lumen, E26, Flame tip, clear |
| | 4.8W | LG161/2DM/CL/300/LED [†] | G16.5, Warm White, 3000K, 300 Lumen, E12 base, clear |
| | 4.8W | LG161/2DM/IF/300/LED [†] | G16.5, Warm White, 3000K, 300 Lumen, E12 base, frosted |
| | 4.8W | LGMDM/CL/300/LED [†] | G16.5, Warm White, 3000K, 300 Lumen, E26, clear |
| | 6.5W | LMR16/GU10/DM/LED [†] | MR16, GU10 base |
| | 6.5W | LMR16DMGU10 [†] | MR16, GU10 base |
| | 6.5W | LR16DMLED | R16, Soft White, 2700K, 400 Lumen, E26, 40WE |
| | 7.5W | LA19DM/LED | A19, 3000K, 450 Lumen, E26 |
| | 7.5W | LA19DM/GU24/LED | A19, 3000K, GU24 |
| | 7.5W | LPAR20DM/5K/LED | PAR20, 5000K |
| | 7.5W | LPAR20DM/LED | PAR20, 3000K |
| | 8W | LA19DM/5K/LED | A19, 5000K |
| | 8W | LG25DM/LEDG2 | G25, Warm White, 3000K, 510 Lumen, E26 |
| | 8W | LR20DMLEDG2 | R20, 2700K, 450 Lumen, E26 Medium base (70mA smooth reflector version) |
| | 9.5W | LPAR20/5K/LEDG5 | PAR20, 5000K, 500 Lumen |
| | 9.5W | LPAR20DM/SP/LED | PAR20, 3000K, 465 Lumen, Spot |
| | 9.5W | LPAR20/LEDG5 | PAR20, 3000K, 450 Lumen |
| | 9.8W | LA19DM/800/LED/G2 | A19, 3000K, 800 Lumen |
| | 10W | LA19DM/800/5K/LEDG2 | A19, 5000K |
| | 10W | LA19DM/800/LEDG2 | A19, 3000K, 800 Lumen |
| | 10W | LG25/DM/LED [†] | G25, 3000K |
| | 11W | DLS02-41127D1E-WF1 | 4" Downlight, Soft White, 2700K, 650 Lumen, E26 retrofit |

[†] Requires a minimum of 2 lamps

^{††} Requires a minimum of 2 lamps

© 02/2015 Lutron Electronics Co., Inc. | P/N 368-3266 REV I

Dimmable CFL & LED bulbs

Compatible with C•L® dimmers



LED bulbs for Maestro® occupancy sensor C•L dimmers

Maestro occupancy sensor C•L: MSCL-OP153M, MSCL-VP153M

Maximum wattage controlled: 150W



| Brand | Wattage | Model | Description |
|-----------|--------------|-------------------------|--|
| Utilitech | 13W | DLS02-61327D1E-WF1 | 5" or 6" Downlight, Soft White, 2700K, 800 Lumen, E26 retrofit |
| | 13W | DLS02-61350D1E-WF1 | 5" or 6" Downlight, Daylight, 5000K, 800 Lumen, E26 retrofit |
| | 13W | LBR30DM/LEDG2 | BR30 |
| | 13.5W | LA19/OM800/LED | A19, 3000K, 800 Lumen, Omni Directional |
| | 13.5W | LA19DM/800/LED | A19, 3000K |
| | 15W | LPAR30L/5K/LEDG5 | PAR30, 5000K, 800 Lumen, long neck flood |
| | 15W | LPAR30L/LEDG5 | PAR30, 3000K, 790 Lumen, long neck flood |
| | 15W | LPAR30LDM/SP/LED | PAR30, 3000K, 790 Lumen, long neck, spot |
| | 15W | LPAR30S/LEDG5 | PAR30, 3000K, 750 Lumen, short neck flood |
| | 16W | LA19/OM1100R/LED | A19, 3000K, 1100 Lumen, Omni Directional |
| | 16W | LBR40DMLEDG2† | BR40, 2700K, 1065 Lumen |
| | 17W | BPCEBR40/DM/LED† | BR40 |
| | 17W | LBR40DM/LED† | BR40, 2700K, 1065 Lumen |
| | 18W | LPAR38DM/5K/LED | PAR38, 5000K |
| | 18W | LPAR38DM/LED | PAR38, 3000K |
| | 20W | L20PAR38/LEDG5 | PAR38, 3000K, 1000 Lumen, flood |
| | 20W | LPAR38/5K/LEDG5 | PAR38, 5000K, 1000 Lumen, flood |
| | 20W | LPAR38/LEDG5 | PAR38, 3000K, 1000 Lumen, flood |
| | 20W | LPAR38DM/SP/LED | PAR38, 3000K, 1000 Lumen, Spot |
| | Westinghouse | 22W | LA/OM1600R/5K/LED |
| 22W | | LA/OM1600R/LED | A21, Warm White, 3000K, 1600 Lumen |
| 23W | | LPAR38/1400/5K/LEDG5 | PAR38, 5000K, 1400 Lumen |
| 23W | | LPAR38/1400/LEDG5 | PAR38, 3000K, 1400 Lumen |
| 8W | | 8A19/LED/DIM/30† | A19, Warm White, 3000K |
| 8W | | 8A19/LED/DIM/50† | A19, Cool White, 5000K |
| 8W | | 8PAR20/LED/DIM30/NFL | PAR20, Warm White, 3000K |
| 8W | | 8PAR20/LED/DIM50/NFL | PAR20, Warm White, 5000K |
| 18W | | 18PAR38/LED/DIM/30/NFL† | PAR38, 3000K |
| 18W | | 18PAR38/LED/DIM/50/NFL† | PAR38, 5000K |

† Requires a minimum of 2 lamps

© 02/2015 Lutron Electronics Co., Inc. | P/N 368-3266 REV I

Dimmable CFL & LED bulbs

Compatible with C•L® dimmers



CFL bulbs* for Maestro® occupancy sensor C•L dimmers

Maestro occupancy sensor C•L: MSCL-OP153M, MSCL-VP153M

Maximum wattage controlled: 150W



| Brand | Wattage | Model | Description |
|----------|---------|----------------------------------|---|
| EcoSmart | 5W | 8TC05F ^{††} | Candle, Torpedo Tip, 2700K, 200 Lumen |
| | 5W | 8TFC05F ^{††} | Candle, Flame Tip, 2700K, 200 Lumen |
| | 5W | 8TC05 ^{††} | Candle, (ES5CCDF052, ES9CCDF052) |
| | 11W | BPESL11R20/DM/ESM | R20, Soft White |
| | 14W | 40114 [†] | Spiral, Soft White (ES5M814DIM2, ES9M814DIM2) |
| | 14W | 2R2014DIM | R20, 2700K, 410 Lumen |
| | 15W | 2R3015DIM | R30 Flood, Soft White (ES5R315DIM2) |
| | 15W | 2R3015DIM50K | R30 Flood, Daylight (ES5R315DIM250K) |
| | 15W | 2R3015DIM35K | R30 Flood, Bright White (ES5R315DIM35K) |
| | 23W | 40123 [†] | Spiral, Soft White (ES5M823DIM2) |
| Feit | 11W | BPESL11R20/DM | R20 |
| | 23W | BPESL23R40/DIM | R40 |
| GE | 26W | FLE26HT3/2/DV/SW | Spiral |
| | 26W | FLE26/2/DVR/40 | R40 |
| Philips | 20W | EL/A R40 Dim 20W | R40 |
| Sylvania | 5W | CF5EL/DEC/DIM [†] | Candle |
| | 5W | CF5EL/B10/827/L/DIM [†] | Candle |
| | 14W | CF14EL/TWIST/DIM | Spiral |
| | 24W | CF24EL/TWIST/DIM | Spiral |
| TCP | 5W | 8TC05F ^{††} | Candle |
| | 5W | 8TFC05F ^{††} | Candle, flame tip |
| | 14W | 40114 [†] | Spiral |
| | 14W | 2R2014DIM | R20, 2700K, 410 Lumen |
| | 15W | 2R3015DIM | R30, Soft White, 2700K |
| | 16W | 4R3016TD | R30, TruDim, 2700K |
| | 16W | 4R3016TD30K | R30, TruDim, 3000K |
| | 16W | 4R3016TD35K | R30, TruDim, 3500K |
| | 16W | 4R3016TD41K | R30, TruDim, 4100K |
| | 16W | 4R3016TD50K | R30, TruDim, 5000K |
| | 16W | 4R3016TD65K | R30, TruDim, 6500K |
| | 23W | 40123 [†] | Spiral |

* CFLs typically require a warmup period before their full dimming range is achieved.

[†] Requires a minimum of 2 lamps

^{††} Requires a minimum of 3 lamps

Dimmable CFL & LED bulbs

Compatible with C•L® dimmers



CFL bulbs* for Maestro® occupancy sensor C•L dimmers

Maestro occupancy sensor C•L: MSCL-OP153M, MSCL-VP153M

Maximum wattage controlled: 150W



| Brand | Wattage | Model | Description |
|-----------|---------|------------|------------------------|
| Utilitech | 11W | LBP11R20DM | R20, Soft White, 2700K |
| | 15W | LBP15TDM | Spiral |
| | 23W | LBP23TDM | Spiral |
| | 23W | LBP23R40DM | R40 |

* CFLs typically require a warmup period before their full dimming range is achieved.

© 02/2015 Lutron Electronics Co., Inc. | P/N 368-3266 REV I

Dimmable CFL & LED bulbs

Compatible with C•L® dimmers



LED bulbs for Maestro® C•L dimmers

Maestro C•L: MACL-153M

Maximum wattage controlled: 150W



| Brand | Wattage | Model | Description |
|----------------------------|----------------------------|----------------------------------|---|
| Commercial Electric | 12.5W | CE-JB4-600L-27K (T47) | 4" Downlight, 600 Lumen, Soft White, 2700K |
| | 12.5W | CE-JB6-650L-27K (T67) | 6" Downlight, 650 Lumen, Soft White, 2700K |
| | 14.5W | CED6 WW 120 WH | 6" Downlight, White |
| Cooper | 9.4W | RL560WH-R | Halo® Downlight, 600 Lumen, Warm White, 3000K |
| | 13.8W | ML706827 | Halo 6" Retrofit Module 2700K |
| | 13.8W | ML706830 | Halo 6" Retrofit Module 3000K |
| | 13.8W | ML706835 | Halo 6" Retrofit Module 3500K |
| | 13.8W | ML706840 | Halo 6" Retrofit Module 4000K |
| Cree | 6W | BA19-04527OMF-12DE26-1U100 | A19, Warm Soft White, 2700K, 450 Lumen, Medium base |
| | 6W | BA19-04527OMF-12DE26-2U100 | A19, Warm Soft White, 2700K, 450 Lumen, Medium base |
| | 6W | BA19-04550OMF-12DE26-2U500 | A19, 5000K, 450 Lumen, 40WE, 4pk |
| | 9W | BA19-08050OMF-12DE26-1U100 | A19, Daylight, 5000K, 800 Lumen, Medium base |
| | 9W | BA19-08050OMF-12DE26-2U100 | A19, Daylight, 5000K, 800 Lumen, Medium base |
| | 9.5W | BA19-08027OMF-12DE26-1U100 | A19, Warm Soft White, 2700K, 800 Lumen, Medium base |
| | 9.5W | BA19-08027OMF-12DE26-2U100 | A19, Soft White, 2700K, 800 Lumen, Medium base |
| | 9.5W | BA19-08027OMF-12DE26-2U500 | A19, 2700K, 800 Lumen, E26, 60WE, 4pk |
| | 9.5W | BBR30-06527FLF-12DE26-1U100 | BR30, 650 Lumen, Soft White, 2700K |
| | 9.5W | BBR30-06550FLF-12DE26-1U100 | BR30, Daylight, 5000K 650 Lumen, 9.5W |
| | 9.5W | CR4-575L | 4" Downlight, 2700K, 575 Lumen, Medium Base |
| | 9.5W | CR6-575L | 6" Downlight, 2700K, Medium Base |
| | 9.5W | CR6-575L-GU24 | 6" Downlight, 2700K, GU24 Base |
| | 9.5W | H1CR6TW62527E04 | 6" Downlight, 2700K, 625 Lumen |
| | 18W | BA21-16027OMF-12DE26-1U100 | A21, 2700K, 1600 Lumen, E26, 18W |
| 18W | BA21-16050OMF-12DE26-1U100 | A21, 5000K, 1600 Lumen, E26, 18W | |

Dimmable CFL & LED bulbs

Compatible with C·L® dimmers



LED bulbs for Maestro® C·L dimmers

Maestro C·L: MACL-153M

Maximum wattage controlled: 150W



| Brand | Wattage | Model | Description |
|----------|---------|---|--|
| EcoSmart | 6W | ECS GP19 WW 40WE 120 [†] | A19, 3000K |
| | 6W | ECS 25 40WE W27 120 DG | G25, 2700K, 400 Lumen, E12 |
| | 7W | ECS 25 60WE W27 120 DG | G25, 2700K, E12 |
| | 8W | ECS 19 CW 120 | A19, Cool White, 5000K |
| | 8W | ECS 19 WW 120 | A19, Warm White, 3000K |
| | 8W | ECS 20 CW FL 120 | PAR20, Daylight, 5000K, 490 Lumen |
| | 8W | ECS 20 CW FL 50WE 120 | PAR20, 5000K, 490 Lumen |
| | 8W | ECS 20 WW FL 120 | PAR20, Warm White, 3000K |
| | 8W | ECS 20 WW FL 50WE 120 | PAR20, 3000K, 450 Lumen |
| | 8W | ECS 20 50WE CW FL 120 TP | PAR20, Daylight, 5000K, 575 Lumen, E26 |
| | 8W | ECS 20 50WE WW FL 120 TP | PAR20, Bright White, 3000K, 500 Lumen, E26 |
| | 8W | ECS 25 WW 120 | G25, Warm White, 3000K |
| | 8W | ECS A19 V1 CW 120 | A19, Daylight, 5000K |
| | 8W | ECS A19 V1 WW 120 | A19, Warm White, 3000K |
| | 8W | ECS BR20 50WE CW 120 DG | BR20, Daylight, 5000K, 600 Lumen, E26 |
| | 8W | ECS BR20 50WE WW 120 DG | BR20, Warm White, 3000K, 550 Lumen, E26 |
| | 8W | ECS BR20 50WE W27 120 | BR20, Soft White, 2700K |
| | 9.5W | ECO4-575L | 4" Downlight, 2700K, 575 Lumen, Medium Base |
| | 9.5W | ECO4-575L-50K | 4" Downlight, 5000K, 575 Lumen, Medium Base |
| | 9.5W | ECO4-575L-50K-GU24 | 4" Downlight, 5000K, GU24 Base |
| | 9.5W | ECO-575L | 6" Downlight, 2700K, Medium Base |
| | 9.5W | ECO-575L-50K | 6" Downlight, 5000K, Medium Base |
| | 9.5W | ECO-575L-50K-GU24 | 6" Downlight, 5000K, GU24 Base |
| | 9.5W | ECO-575L-GU24 | 6" Downlight, 2700K, GU24 Base |
| | 10W | ECS BR30 65WE CW 120 DG [†] | BR30, Daylight, 5000K, 700 Lumen, E26 |
| | 10W | ECS BR30 65WE CW 120 DG 3PK [†] | BR30, Daylight, 5000K, 700 Lumen, E26, 3pk |
| | 10W | ECS BR30 65WE W27 120 DG [†] | BR30, Soft White, 2700K, 650 Lumen, E26 |
| | 10W | ECS BR30 65WE W27 120 DG 3BX [†] | BR30, Soft White, 2700K, 650 Lumen, E26, 3pk |

[†] Requires a minimum of 2 lamps

© 02/2015 Lutron Electronics Co., Inc. | P/N 368-3266 REV I

Dimmable CFL & LED bulbs

Compatible with C•L® dimmers



LED bulbs for Maestro® C•L dimmers

Maestro C•L: MACL-153M

Maximum wattage controlled: 150W



| Brand | Wattage | Model | Description |
|----------|---------------------|----------------------------|---|
| EcoSmart | 10W | ECS BR30 65WE WW 120 DG† | BR30, Warm White, 3000K, 650 Lumen, E26 |
| | 10.5W | ECS 30 75WE xxx GB xx 120* | PAR30 Gimbal, Various color temperatures, 75WE |
| | 10.5W | ECS 30 75WE WW GB FL 120 | PAR30 Gimbal, 3000K, 750 Lumen, E26, 75WE |
| | 11.5W | ECS BR30 65WE CW 120† | BR30, 5000K, Medium Base |
| | 11.5W | ECS BR30 65WE W27 120† | BR30, 2700K, 650 Lumen, Medium Base |
| | 12W | ECS A19 CW 60WE 120 | A19, 5000K, 850 Lumen |
| | 12W | ECS A19 WW 60WE 120 | A19, 3000K, 800 Lumen |
| | 13W | ECS 30 CW FL 75WE 120 | PAR30, 5000K, 810 Lumen |
| | 13W | ECS 30 WW FL 75WE 120 | PAR30, 3000K, 750 Lumen |
| | 13W | ECS A19 V2 CW 120 | A19, Daylight, 5000K |
| | 13W | ECS A19 V2 WW 120 | A19, Warm White, 3000K |
| | 14W | ECS BR40 90WE CW 120 DG | BR40, Daylight, 5000K, 1050 Lumen, E26 |
| | 14W | ECS BR40 90WE W27 120 DG | BR40, 2700K, 1000 Lumen, E26 |
| | 15W | ECS 30 CW FL 120 | PAR30, Daylight, 5000K |
| | 15W | ECS 30 WW FL 120 | PAR30, Warm White, 3000K |
| | 15W | ECS 38 CW FL 90WE 120 | PAR38, 5000K, 970 Lumen |
| | 15W | ECS 38 WW FL 90WE 120 | PAR38, 3000K, 900 Lumen |
| | 15W | ECS BR30 W27 FL 120 | BR30, Soft White, 2700K |
| | 15W | ECS BR40 90WE W27 120 | BR40, Soft White, 2700K |
| | 16W | ECS BR40 W27 FL 120 | BR40, Soft White, 2700K |
| | 17W | ECS 30 V2 WW FL 120 | PAR30, Warm White, 3000K |
| | 18W | ECS 38 CW FL 120 | PAR38, Daylight, 5000K |
| | 18W | ECS 38 WW FL 120 | PAR38, Warm White, 3000K |
| 24W | ECS 38 V2 WW FL 120 | PAR38, Warm White, 3000K | |
| Feit | 3.5W | CFCDM/LED† | Candle, Flame Tip Clear, 3000K, Candelabra Base |
| | 3.5W | EFCDM/LED† | Candle, Flame Tip Clear, 3000K, Medium Base |
| | 4.5W | R14DM/LED | R14, Soft White, 2700K, 300 Lumen, E26, 40WE |
| | 4.8W | CFCDM/300/LED† | Candle, 3000K, 310 Lumen, Candelabra Base |

* "xx" and "xxx" denote other characters which may be included in the model number.

† Requires a minimum of 2 lamps

Dimmable CFL & LED bulbs

Compatible with C·L® dimmers



LED bulbs for Maestro® C·L dimmers

Maestro C·L: MACL-153M

Maximum wattage controlled: 150W



| Brand | Wattage | Model | Description |
|-------|---------|-----------------------|---|
| Feit | 4.8W | EFCDM/300/LED† | Candle, 3000K, 310 Lumen, Medium Base |
| | 5W | MR16/GU10/DM/LED | MR16, GU10 Base |
| | 6.5W | BPMR16/GU10/DM/LED | MR16, GU10 base |
| | 6.5W | MR16/GU10/DM/LED | MR16, GU10 base |
| | 6.5W | R16DM/LED | R16, Soft White, 2700K, 400 Lumen, E26, 40WE |
| | 7.5W | PAR20DM/5K/LED | PAR20, 5000K |
| | 7.5W | PAR20DM/LED | PAR20, 3000K |
| | 8W | A19/DM/GU24/LED | A19, 3000K, GU24 Base |
| | 8W | A19/DM/LED | A19, 3000K |
| | 8W | A19/DM/LED/CAN | A19 |
| | 8W | A19/DM/LED/RP/CAN | A19 |
| | 8W | A19DM/5K/LED | A19, 5000K |
| | 8W | BPCEA19/DM/LED | A19 |
| | 8W | BPCER20/DM/LED† | R20 (90mA ridged reflector version) |
| | 8W | R20/DM/LED† | R20, 2700K, 450 Lumen (90mA ridged reflector version) |
| | 8W | R20DM/LED/CAN† | R20 (90mA ridged reflector version) |
| | 9.5W | BPCER20/DM/LED | PAR20 |
| | 9.5W | PAR20/5K/LEDG5 | PAR20, 5000K |
| | 9.5W | PAR20/5K/LEDG5/CAN | PAR20, 5000K |
| | 9.5W | PAR20/LEDG5 | PAR20, 3000K, 450 Lumen |
| | 9.5W | PAR20/LEDG5/CAN | PAR20 |
| | 10W | BPAG800/5K/LED | A19, 5000K |
| | 10W | BPAG800/LED | A19, 3000K, 800 Lumen |
| | 10W | G25/DM/LED† | G25, 3000K |
| | 13W | BPCEBR30LED | BR30 |
| | 13.5W | A19/OM800/5K/LED | A19, 5000K, Omni Directional |
| | 13.5W | A19/OM800/LED | A19, 3000K, Omni Directional |
| | 13.5W | A19DM/800/LED | A19, 3000K |
| | 13.5W | BPCEA19/OM800/LED | A19, Omni Directional |
| | 13.5W | BPCEA19/OM800/LED/CAN | A19, Omni Directional |

† Requires a minimum of 2 lamps

© 02/2015 Lutron Electronics Co., Inc. | P/N 368-3266 REV I

Dimmable CFL & LED bulbs

Compatible with C•L® dimmers



LED bulbs for Maestro® C•L dimmers

Maestro C•L: MACL-153M

Maximum wattage controlled: 150W



| Brand | Wattage | Model | Description |
|-------|------------------|------------------------------------|--|
| Feit | 15W | BPCEPAR30/LEDG5 | PAR30 |
| | 15W | PAR30L/5K/LEDG5 | PAR30, 5000K |
| | 15W | PAR30L/5K/LEDG5/CAN | PAR30, 5000K |
| | 15W | PAR30L/LEDG5 | PAR30 |
| | 15W | PAR30L/LEDG5/CAN | PAR30 |
| | 16W | A19/OM1100R/LED | A19, 3000K, 1100 Lumen, Omni Directional |
| | 16.8W | LEDR56/3K | 5" or 6" Downlight, 3000K, 840 Lumen |
| | 17W | BPCEBR40/LED | BR40, 2700K, 1065 Lumen |
| | 17W | BR40/DM/LED† | BR40, 2700K, 1065 Lumen |
| | 18W | 18PAR38/DM/LED | PAR38, 3000K |
| | 18W | PAR38DM/5K/LED | PAR38, 5000K |
| | 18W | PAR38DM/LED | PAR38, 3000K |
| | 20W | 20PAR38/LEDG5 | PAR38 |
| | 20W | BPCEPAR38/LEDG5 | PAR38 |
| | 20W | PAR38/5K/LEDG5 | PAR38, 5000K |
| | 20W | PAR38/5K/LEDG5/CAN | PAR38, 5000K |
| | 20W | PAR38/LEDG5 | PAR38 |
| | 20W | PAR38/LEDG5/CAN | PAR38 |
| | 20.5W | LEDR56/827 | 5" or 6" Downlight, 2700K, 1245 Lumen |
| | 22W | A/OM1600R/27K/LED | A21, 2700K, 1600 Lumen |
| 22W | A/OM1600R/5K/LED | A21, Daylight, 5000K, 1600 Lumen | |
| 22W | A/OM1600R/LED | A21, Warm White, 3000K, 1600 Lumen | |
| GE | 8W | LED8DA19/827 | A19, 2700K, 450 Lumen, E26 |
| | 10W | LED10DP30S827/20 | PAR30, 2700K, Short Neck, Silver Base |
| | 10W | LED10DP30S830/20 | PAR30, 3000K, Short Neck, Silver Base |
| | 10W | LED10DP30W827/20 | PAR30, 2700K, Short Neck, White Base |
| | 10W | LED10DP3LS827/20 | PAR30, 2700K, Long Neck, Silver Base |
| | 10W | LED10DP3LS830/20 | PAR30, 3000K, Long Neck, Silver Base |
| | 11W | LED11DA19RVL/TP | A19, 2700K, 570 Lumen |
| | 11W | LED11DA19V2 | A19, 2700K, 800 Lumen |
| | 12W | LED12DR30RVL/BK | BR30, Reveal |
| | 12W | LED12DR30RVL/CDN | BR30, Reveal |

† Requires a minimum of 2 lamps

© 02/2015 Lutron Electronics Co., Inc. | P/N 368-3266 REV I

Dimmable CFL & LED bulbs

Compatible with C·L® dimmers



LED bulbs for Maestro® C·L dimmers

Maestro C·L: MACL-153M

Maximum wattage controlled: 150W



| Brand | Wattage | Model | Description |
|-------|---------|--------------------|---|
| GE | 12W | LED12DR30RVL/TP | BR30, Reveal 2850K, 630 Lumen |
| | 13W | LED13DA19/830 | A19, 3000K |
| | 18W | LED18D38W827/15 | PAR38, 2700K, E26, 15° Beam |
| | 18W | LED18D38W827/25 | PAR38, 2700K, E26, 25° Beam |
| | 18W | LED18D38W827/40 | PAR38, 2700K, E26, 40° Beam |
| | 18W | LED18D38W830/15 | PAR38, 3000K, 1400 Lumen, E26, 15° Beam |
| | 18W | LED18D38W830/25 | PAR38, 3000K, 1400 Lumen, E26, 25° Beam |
| | 18W | LED18D38W830/40 | PAR38, 3000K, 1400 Lumen, E26, 40° Beam |
| | 18W | LED18D38W927/15 | PAR38, 2700K, 1100 Lumen, E26, 15° Beam |
| | 18W | LED18D38W927/25 | PAR38, 2700K, 1100 Lumen, E26, 25° Beam |
| | 18W | LED18D38W927/40 | PAR38, 2700K, 1100 Lumen, E26, 40° Beam |
| | 18W | LED18D38W930/15 | PAR38, 3000K, 1200 Lumen, E26, 15° Beam |
| | 18W | LED18D38W930/25 | PAR38, 3000K, 1200 Lumen, E26, 25° Beam |
| | 18W | LED18D38W930/40 | PAR38, 3000K, 1200 Lumen, E26, 40° Beam |
| | 20W | LED20DP38S827/15 | PAR38, 2700K, 15° Beam, Silver Base |
| | 20W | LED20DP38S827/25 | PAR38, 2700K, 25° Beam, Silver Base |
| | 20W | LED20DP38S827/40 | PAR38, 2700K, 40° Beam, Silver Base |
| | 20W | LED20DP38S830/15 | PAR38, 3000K, 15° Beam, Silver Base |
| | 20W | LED20DP38S830/25 | PAR38, 3000K, 25° Beam, Silver Base |
| | 20W | LED20DP38S830/40 | PAR38, 3000K, 40° Beam, Silver Base |
| Halco | 20W | PAR38FL20/827/LED | PAR38, 2700K, 1150 Lumen Flood |
| | 20W | PAR38FL20/830/LED | PAR38, 3000K, 1200 Lumen Flood |
| | 20W | PAR38FL20/840/LED | PAR38, 4000K, 1250 Lumen Flood |
| | 20W | PAR38FL20/850/LED | PAR38, 5000K, 1300 Lumen Flood |
| | 20W | PAR38NFL20/827/LED | PAR38, 2700K, 1150 Lumen Flood |
| | 20W | PAR38NFL20/830/LED | PAR38, 3000K, 1200 Lumen Flood |
| | 20W | PAR38NFL20/840/LED | PAR38, 4000K Flood |
| | 20W | PAR38NFL20/850/LED | PAR38, 5000K, 1300 Lumen Flood |
| | 20W | PAR38SP20/827/LED | PAR38, 2700K, 1150 Lumen Spot |
| | 20W | PAR38SP20/830/LED | PAR38, 3000K, 1200 Lumen Spot |
| | 20W | PAR38SP20/840/LED | PAR38, 4000K Spot |
| | 20W | PAR38SP20/850/LED | PAR38, 5000K, 1300 Lumen Spot |

Dimmable CFL & LED bulbs

Compatible with C·L® dimmers



LED bulbs for Maestro® C·L dimmers

Maestro C·L: MACL-153M

Maximum wattage controlled: 150W



| Brand | Wattage | Model | Description |
|------------------|---------|---------------------------|---|
| Lighting Science | 8W | DFN 19 CW 120 | A19, Cool White, 5000K |
| | 8W | DFN 19 NW 120 | A19, Neutral White, 4000K |
| | 8W | DFN 19 W27 120 | A19, Warm White, 2700K |
| | 8W | DFN 19 WW 120 | A19, Warm White, 3000K |
| | 8W | DFN 20 CW FL 120 | PAR20, Cool White, 5000K |
| | 8W | DFN 20 CW NFL 120 | PAR20, Cool White, 5000K |
| | 8W | DFN 20 NW FL 120 | PAR20, Neutral White, 4000K |
| | 8W | DFN 20 NW NFL 120 | PAR20, Neutral White, 4000K |
| | 8W | DFN 20 W27 FL 120 | PAR20, Warm White, 2700K |
| | 8W | DFN 20 W27 NFL 120 | PAR20, Warm White, 2700K |
| | 8W | DFN 20 WW FL 120 | PAR20, Warm White, 3000K |
| | 8W | DFN 20 WW NFL 120 | PAR20, Warm White, 3000K |
| | 8W | DFN 25 CW 120 | G25, Cool White, 5000K |
| | 8W | DFN 25 NW 120 | G25, Neutral White, 4000K |
| | 8W | DFN 25 W27 120 | G25, Warm White, 2700K |
| | 8W | DFN 25 WW 120 | G25, Warm White, 3000K |
| | 8W | DFN A19 V1 CW 120 | A19, Cool White, 5000K |
| | 8W | DFN A19 V1 NW 120 | A19, Neutral White, 4000K |
| | 8W | DFN A19 V1 W27 120 | A19, Warm White, 2700K |
| | 8W | DFN A19 V1 WW 120 | A19, Warm White, 3000K |
| | 10.5W | LS 30 75WE xxx GB xx 120* | PAR30, various color temperatures |
| | 11.5W | DFN BR30 65WE CW 120† | BR30, Cool White, 5000K, Medium base |
| | 11.5W | DFN BR30 65WE NW 120† | BR30, Neutral White, 4000K, Medium base |
| | 11.5W | DFN BR30 65WE W27 120† | BR30, Warm White, 2700K, Medium base |
| | 11.5W | DFN BR30 65WE WW 120† | BR30, Warm White, 3000K, Medium base |
| | 13W | LS GLP6 W27 120 WH S1 BX | 6" Downlight, 2700K, E26 retrofit |
| | 13.5W | DFN A19 V2 CW 120 | A19, Cool White, 5000K |
| | 13.5W | DFN A19 V2 NW 120 | A19, Neutral White, 4000K |
| | 13.5W | DFN A19 V2 W27 120 | A19, Warm White, 2700K |
| | 13.5W | DFN A19 V2 WW 120 | A19, Warm White, 3000K |
| | 14.5W | GLP6 NW WH | 6" Downlight, White, 4000K |
| | 14.5W | GLP6 W27 WH | 6" Downlight, White, 2700K |

* "xx" and "xxx" denote other characters which may be included in the model number.

† Requires a minimum of 2 lamps

© 02/2015 Lutron Electronics Co., Inc. | P/N 368-3266 REV I

Dimmable CFL & LED bulbs

Compatible with C·L® dimmers



LED bulbs for Maestro® C·L dimmers

Maestro C·L: MACL-153M

Maximum wattage controlled: 150W



| Brand | Wattage | Model | Description |
|------------------|---------|-----------------------|---------------------------------|
| Lighting Science | 14.5W | GLP6 WW WH | 6" Downlight, Warm White, 3000K |
| | 15W | DFN 30 CW FL 120 | PAR30, Cool White, 5000K |
| | 15W | DFN 30 CW NFL 120 | PAR30, Cool White, 5000K |
| | 15W | DFN 30 NW FL 120 | PAR30, Neutral White, 4000K |
| | 15W | DFN 30 NW NFL 120 | PAR30, Neutral White, 4000K |
| | 15W | DFN 30 W27 FL 120 | PAR30, Warm White, 2700K |
| | 15W | DFN 30 W27 NFL 120 | PAR30, Warm White, 2700K |
| | 15W | DFN 30 WW FL 120 | PAR30, Warm White, 3000K |
| | 15W | DFN 30 WW NFL 120 | PAR30, Warm White, 3000K |
| | 15W | DFN BR30 CW FL 120 | BR30, Cool White, 5000K |
| | 15W | DFN BR30 NW FL 120 | BR30, Neutral White, 4000K |
| | 15W | DFN BR30 W27 FL 120 | BR30, Warm White, 2700K |
| | 15W | DFN BR30 WW FL 120 | BR30, Warm White, 3000K |
| | 16W | DFN BR40 CW 120 | BR40, Cool White, 5000K |
| | 16W | DFN BR40 NW 120 | BR40, Neutral White, 4000K |
| | 16W | DFN BR40 W27 120 | BR40, Warm White, 2700K |
| | 16W | DFN BR40 WW 120 | BR40, Warm White, 3000K |
| | 17W | DFN 30 CW V2 FL 120 | PAR30, Cool White, 5000K |
| | 17W | DFN 30 CW V2 NFL 120 | PAR30, Cool White, 5000K |
| | 17W | DFN 30 NW V2 FL 120 | PAR30, Neutral White, 4000K |
| | 17W | DFN 30 NW V2 NFL 120 | PAR30, Neutral White, 4000K |
| | 17W | DFN 30 W27 V2 FL 120 | PAR30, Warm White, 2700K |
| | 17W | DFN 30 W27 V2 NFL 120 | PAR30, Warm White, 2700K |
| | 17W | DFN 30 WW V2 FL 120 | PAR30, Warm White, 3000K |
| | 17W | DFN 30 WW V2 NFL 120 | PAR30, Warm White, 3000K |
| | 18W | DFN 38 CW FL 120 | PAR38, Cool White, 5000K |
| | 18W | DFN 38 CW NFL 120 | PAR38, Cool White, 5000K |
| | 18W | DFN 38 NW FL 120 | PAR38, Neutral White, 4000K |
| | 18W | DFN 38 NW NFL 120 | PAR38, Neutral White, 4000K |
| | 18W | DFN 38 W27 FL 120 | PAR38, Warm White, 2700K |
| | 18W | DFN 38 W27 NFL 120 | PAR38, Warm White, 2700K |
| | 18W | DFN 38 WW FL 120 | PAR38, Warm White, 3000K |

Dimmable CFL & LED bulbs

Compatible with C·L® dimmers



LED bulbs for Maestro® C·L dimmers

Maestro C·L: MACL-153M

Maximum wattage controlled: 150W



| Brand | Wattage | Model | Description |
|-------------------------|---------|------------------------|--|
| Lighting Science | 18W | DFN 38 WW NFL 120 | PAR38, Warm White, 3000K |
| | 24W | DFN 38 CW V2 FL 120 | PAR38, Cool White, 5000K |
| | 24W | DFN 38 CW V2 NFL 120 | PAR38, Cool White, 5000K |
| | 24W | DFN 38 NW V2 FL 120 | PAR38, Neutral White, 4000K |
| | 24W | DFN 38 NW V2 NFL 120 | PAR38, Neutral White, 4000K |
| | 24W | DFN 38 W27 V2 FL 120 | PAR38, Warm White, 2700K |
| | 24W | DFN 38 W27 V2 NFL 120 | PAR38, Warm White, 2700K |
| | 24W | DFN 38 WW V2 FL 120 | PAR38, Warm White, 3000K |
| | 24W | DFN 38 WW V2 NFL 120 | PAR38, Warm White, 3000K |
| Litetronics | 14W | LP14550FL2D | BR30, 2700K, 925 Lumen |
| | 14W | LP14550FL4D | BR30, 3000K, 925 Lumen |
| | 14W | LP14550FL6D | BR30, 4000K, 925 Lumen |
| Lumapro | 8W | 8A19/LED/DIM/30 | A19, Warm White, 3000K (6GEM2) |
| | 8W | 8A19/LED/DIM/50 | A19, Cool White, 5000K (6GEM3) |
| | 8W | 8PAR20/LED/DIM30/NFL | PAR20, Warm White, 3000K (6GEM4) |
| | 8W | 8PAR20/LED/DIM50/NFL | PAR20, Cool White, 5000K (6GEM5) |
| | 15W | 15PAR30/LED/DIM/30/NFL | PAR30, Warm White, 3000K |
| | 15W | 15PAR30/LED/DIM/50/NFL | PAR30, Cool White, 5000K |
| | 18W | 18PAR38/LED/DIM/30/NFL | PAR38, Warm White, 3000K |
| | 18W | 18PAR38/LED/DIM/50/NFL | PAR38, Cool White, 5000K |
| Philips | 3.5W | 3.512BA11DCAAA | Candle, 2700K, 150 Lumen, Candelabra Base |
| | 3.5W | 3.5E26B12DCBAAA | Candle, 2700K, 150 Lumen, Medium Base |
| | 3.5W | 3.5E26BA12DCBAAA | Candle, 2700K, 150 Lumen, Medium Base |
| | 3.5W | 9290002417 | Candle, 2700K, 150 Lumen, E12 Candelabra base |
| | 3.5W | 9290002419 | Candle, 2700K, 150 Lumen, E26 medium base, blunt tip clear |
| | 4W | 9290002120 | MR16, Bright White, 3000K, 200 Lumen, GU10, 4W |
| | 4.5W | 9290002439 | Candle, Warm White, 2700K, 320 Lumen, E26 base, Post Light |
| | 4.5W | 9290002797† | Candle, 2700K, 330 Lumen, E26, blunt tip |

† Requires a minimum of 2 lamps

© 02/2015 Lutron Electronics Co., Inc. | P/N 368-3266 REV I

Dimmable CFL & LED bulbs

Compatible with C·L® dimmers



LED bulbs for Maestro® C·L dimmers

Maestro C·L: MACL-153M

Maximum wattage controlled: 150W



| Brand | Wattage | Model | Description |
|---------|---------|----------------|--|
| Philips | 4.5W | 9290002889† | Candle, 2700K, 330 Lumen, E12, blunt tip |
| | 4.5W | 9290002890† | A15, 2700K, 330 Lumen, E12 |
| | 4.5W | 9290002891† | A15, 2700K, 330 Lumen, E26 |
| | 6W | 9290002443 | PAR16, 3000K, 300 Lumen, E26 |
| | 6W | 9290002242 | MR16, 3000K, 300 Lumen, GU10 base |
| | 7W | 9290002020 | PAR20, 2700K, 280 Lumen, Medium Base |
| | 7W | 7E26A55-E | A19, 2700K, 240 Lumen |
| | 7W | 7E26A60 | A19 EnduraLED 2700K |
| | 7W | 7E26PAR20D-1 | PAR20, 2700K, 280 Lumen, Medium Base |
| | 7W | 7E26PAR20-E | PAR20, 2700K |
| | 8W | 8E26A60 | A19, 2700K |
| | 8W | 9290002192 | R20, 2700K, 530 Lumen, Medium base |
| | 8W | 9290002267 | A19, 2700K, 470 Lumen |
| | 8W | 9290002295 | A19, 5000K, 470 Lumen |
| | 8W | 9290002329 | PAR20, 3000K, 280 Lumen, Medium base |
| | 8W | 9290002330 | PAR20 |
| | 8W | 9290002331 | PAR20 |
| | 8W | 9290002332 | PAR20 |
| | 8W | 9290002333 | PAR20 |
| | 8W | 9290002334 | PAR20 |
| | 8W | 9290002335 | PAR20 |
| | 8W | 9E26A19DCCAAAA | A19, 2700K, 507 Lumen |
| | 8.5W | 9290002543 | BR30, 5000K, 730 Lumen, 8.5W |
| | 10.5W | 9290002544 | BR30, 2700K, 730 Lumen |
| | 11W | 9290002268 | A19, 2700K, 830 Lumen |
| | 11W | 9290002296 | A19, 5000K, 830 Lumen |
| | 11W | 9290011113 | PAR30L, 3000K, E26 |
| | 12W | 12E26PAR30L-E2 | PAR30, 3000K |
| | 12.5W | 9290001829 | A19, 2700K, 908 Lumen |
| | 12.5W | 12E26A60 | A19, 2700K |
| | 13W | 9290002233 | PAR30, 2700K, 784 Lumen |
| | 13W | 9290002234 | PAR30, 2700K, 770 Lumen |

† Requires a minimum of 2 lamps

© 02/2015 Lutron Electronics Co., Inc. | P/N 368-3266 REV I

Dimmable CFL & LED bulbs

Compatible with C·L® dimmers



LED bulbs for Maestro® C·L dimmers

Maestro C·L: MACL-153M

Maximum wattage controlled: 150W



| Brand | Wattage | Model | Description | |
|---------|---------|-----------------|---|-------------------------|
| Philips | 13W | 13E26B30DAAABAA | BR30, 3000K | |
| | 13W | 9290002197 | BR30, 2700K, 721 Lumen | |
| | 13W | 9290002201 | PAR30, 3000K, 750 Lumen | |
| | 13W | 9290002323 | PAR30, 5000K, 850 Lumen | |
| | 13W | 9290002523 | 13PAR38/F25 3000 DIM AF RO | PAR38, 3000K, 950 Lumen |
| | 14.5W | 9290002199 | BR40, 2700K, 832 Lumen | |
| | 15W | 9290002426 | A21, 2700K, 1180 Lumen | |
| | 15W | 9290002595 | A21, Soft White, 2700K, 1180 Lumen, E26 | |
| | 17W | 9290002018 | A21, 2700K | |
| | 17W | 17E26A21D | A21, 2700K | |
| | 17W | 17E26PAR38-E2 | PAR38, 3000K | |
| | 18W | 9290002202 | PAR38, 3000K, 951 Lumen, Medium Base | |
| | 18W | 9290002236 | PAR38 | |
| | 18W | 9290002237 | PAR38 | |
| | 18W | 9290002245 | PAR38, 2700K, 938 Lumen | |
| | 18W | 9290002246 | PAR38 | |
| | 18W | 9290002307 | PAR38 | |
| | 18W | 9290002308 | PAR38 | |
| | 18W | 9290002309 | PAR38 | |
| | 18W | 9290002310 | PAR38 | |
| | 18W | 9290002311 | PAR38 | |
| | 18W | 18E26PAR38-3 | PAR38 | |
| | 18W | 18E26PAR38-4 | PAR38 | |
| | 18W | 18E26PAR38D-2 | PAR38, 2700K | |
| | 19W | 9290002473 | PAR38, 3000K, 1250 Lumen | |
| | 19.5W | 9290002251 | PAR38, 3000K, 1210 Lumen | |
| | 19.5W | 9290002252 | PAR38, 2700K, 1183 Lumen | |
| | 19.5W | 9290002253 | PAR38, 3000K, 1212 Lumen | |
| | 19.5W | 9290002291 | PAR38, 4000K, 1207 Lumen | |
| | 19.5W | 9290002312 | PAR38, 2700K, 1100 Lumen | |
| | 19.5W | 9290002313 | PAR38, 2700K, 1196 Lumen | |
| | 19.5W | 9290002314 | PAR38, 3000K, 1200 Lumen | |

Dimmable CFL & LED bulbs

Compatible with C·L® dimmers



LED bulbs for Maestro® C·L dimmers

Maestro C·L: MACL-153M

Maximum wattage controlled: 150W



| Brand | Wattage | Model | Description |
|---------|---------|------------------|--|
| Philips | 19.5W | 9290002315 | PAR38, 3000K, 1225 Lumen |
| | 19.5W | 9290002316 | PAR38, 4000K, 1200 Lumen |
| | 19.5W | 9290002317 | PAR38, 4000K, 1245 Lumen |
| | 19.5W | 9290002321 | PAR38, 2700K, 1172 Lumen |
| | 19.5W | 9290002322 | PAR38, 5000K, 1300 Lumen |
| | 22W | 9290002290 | A21, 2700K, 1780 Lumen, Medium base |
| Satco | 7W | S8827 thru S8838 | PAR30 |
| | 8W | S8794 | A19, 2700K, 450 Lumen, GU10 |
| | 8W | S8995 | A19, 3000K, 450 Lumen |
| | 8W | S9002 | R20 |
| | 8W | S9040-S9042 | R20 |
| | 9W | S8991 | 4" Downlight |
| | 11W | S8993-S8994 | BR30, 3000K, Medium and GU24 bases |
| | 11W | S9043-S9045 | BR30, various color temperatures |
| | 11W | S9084 | PAR30, 3000K, 780 Lumen, E26, short neck, 25° Beam |
| | 11W | S9085 | PAR30, 4000K, 780 Lumen, E26, short neck, 25° Beam |
| | 11W | S9086 | PAR30, 3000K, 780 Lumen, E26, short neck, 40° Beam |
| | 11W | S9087 | PAR30, 4000K, 780 Lumen, E26, short neck, 40° Beam |
| | 11W | S9088 | PAR30, 3000K, 780 Lumen, E26, long neck, 25° Beam |
| | 11W | S9089 | PAR30, 4000K, 780 Lumen, E26, long neck, 25° Beam |
| | 11W | S9090 | PAR30, 3000K, 780 Lumen, E26, long neck, 40° Beam |
| | 11W | S9091 | PAR30, 4000K, 780 Lumen, E26, long neck, 40° Beam |
| | 13W | S9003 | R40, 3000K, 880 Lumen |
| | 13W | S9046 | R40, 2700K, 850 Lumen |
| | 13W | S9047 | R40, 4000K, 920 Lumen |
| | 13W | S9048 | R40, 5000K, 950 Lumen |

Dimmable CFL & LED bulbs

Compatible with C·L® dimmers



LED bulbs for Maestro® C·L dimmers

Maestro C·L: MACL-153M

Maximum wattage controlled: 150W



| Brand | Wattage | Model | Description | |
|-------|---------|---------------------|---|--|
| Satco | 14W | S8814 thru S8819 | PAR30 | |
| | 14W | S8821 thru S8826 | PAR30 | |
| | 14W | S8947-S8949 | PAR30 Longneck | |
| | 14W | S8971-S8973 | PAR30 Longneck | |
| | 17W | S8852 thru S8859 | PAR38 | |
| | 17W | S8861 thru S8864 | PAR38 | |
| | 17W | S8977-S8979 | PAR38 | |
| | 17W | S8984-S8986 | PAR38 | |
| | 17W | S9092 | PAR38, 3000K, 1200 Lumen, E26, 25° beam | |
| | 17W | S9093 | PAR38, 4000K, 1200 Lumen, E26, 25° beam | |
| | 17W | S9094 | PAR38, 3000K, 1200 Lumen, E26, 40° beam | |
| | 17W | S9095 | PAR38, 4000K, 1200 Lumen, E26, 40° beam | |
| | 28W | LR38/15/27K/2000/xx | PAR38, 2700K, 2000 Lumen, E26 | |
| | 28W | LR38/15/30K/2100/xx | PAR38, 3000K, 2100 Lumen, E26 | |
| | 28W | LR38/25/27K/2000/xx | PAR38, 2700K, 2000 Lumen, E26 | |
| | 28W | LR38/25/30K/2100/xx | PAR38, 3000K, 2100 Lumen, E26 | |
| | Solais | 7W | LRP20/25/27K | PAR20, 2700K, 475 Lumen, E26, 25° Beam |
| | | 7W | LRP20/25/30K | PAR20, 3000K, 500 Lumen, E26, 25° Beam |
| 7W | | LRP20/40/27K | PAR20, 2700K, 475 Lumen, E26, 40° Beam | |
| 7W | | LRP20/40/30K | PAR20, 3000K, 500 Lumen, E26, 40° Beam | |
| 11W | | LR20/25/27K/675/xx | PAR20, 2700K, 675 Lumen, E26, narrow flood | |
| 11W | | LR20/25/30K/750 | PAR20, 3000K, 750 Lumen, E26, narrow flood | |
| 11W | | LR20/40/27K/675/xx | PAR20, 2700K, 675 Lumen, E26, wide flood | |
| 11W | | LR20/40/30K/750/xx | PAR20, 3000K, 750 Lumen, E26, wide flood | |
| 16W | | LR30/10/27K/1100/xx | PAR30, 2700K, 1100 Lumen, E26, short neck, 10° Beam | |
| 16W | | LR30/10/30K/1125/xx | PAR30, 3000K, 1125 Lumen, E26, short neck, 10° Beam | |

Dimmable CFL & LED bulbs

Compatible with C·L® dimmers



LED bulbs for Maestro® C·L dimmers

Maestro C·L: MACL-153M

Maximum wattage controlled: 150W



| Brand | Wattage | Model | Description |
|-----------------|---------|---------------------|---|
| Solais | 16W | LR30/10/30K/1200/xx | PAR30, 3000K, 1200 Lumen, E26, short neck, 10° Beam |
| | 16W | LR30/15/27K/1100/xx | PAR30, 2700K, 1100 Lumen, E26, short neck, 15° Beam |
| | 16W | LR30/15/30K/1125/xx | PAR30, 3000K, 1125 Lumen, E26, short neck, 15° Beam |
| | 16W | LR30/15/30K/1200/xx | PAR30, 3000K, 1200 Lumen, E26, short neck, 15° Beam |
| | 16W | LR30/25/27K/1100/xx | PAR30, 2700K, 1100 Lumen, E26, short neck, 25° Beam |
| | 16W | LR30/25/30K/1125/xx | PAR30, 3000K, 1125 Lumen, E26, short neck, 25° Beam |
| | 16W | LR30/25/30K/1200/WH | PAR30, 3000K, 1200 Lumen, E26, short neck, 25° Beam |
| | 16W | LR30/40/27K/1100/xx | PAR30, 2700K, 1100 Lumen, E26, short neck, 40° Beam |
| | 16W | LR30/40/30K/1125/xx | PAR30, 3000K, 1125 Lumen, E26, short neck, 40° Beam |
| | 16W | LR30/40/30K/1200/xx | PAR30, 3000K, 1200 Lumen, E26, short neck, 40° Beam |
| | 16W | LRP38/25/27K | PAR38, 2700K, 1025 Lumen, E26, 25° Beam |
| | 16W | LRP38/25/30K | PAR38, 3000K, 1100 Lumen, E26, 25° Beam |
| | 16W | LRP38/40/27K | PAR38, 2700K, 1025 Lumen, E26, 40° Beam |
| | 16W | LRP38/40/30K | PAR38, 3000K, 1100 Lumen, E26, 40° Beam |
| | 20W | LR38/25/30K/1450/SL | PAR38, 3000K, 1450 Lumen, E26, 15° Beam |
| Switch | 10W | A260FUS27B1 | A19, 800 Lumen |
| | 13W | 75FU202 | A19, 3000K, 1100 Lumen, E26 |
| Sylvania | 8W | LED8A/DIM/F/827 | A19, 2700K |
| | 8W | LED8A/DIM/F/830 | A19, 3000K |
| | 8W | LED8A15/DIM/827† | A15, 2700K, 450 Lumen, Medium Base |
| | 8W | LED8A15C/DIM/827† | A15, 2700K, 450 Lumen, Candelabra Base |
| | 8W | LED8A19DIM0827RP | A19, 2700K, 470 Lumen, E26 |
| | 8W | LED8G25/DIM/F/827 | G25, 2700K |
| | 8W | LED8G25/DIM/F/830 | G25, 3000K |

† Requires a minimum of 2 lamps

© 02/2015 Lutron Electronics Co., Inc. | P/N 368-3266 REV I

Dimmable CFL & LED bulbs

Compatible with C•L® dimmers



LED bulbs for Maestro® C•L dimmers

Maestro C•L: MACL-153M

Maximum wattage controlled: 150W



| Brand | Wattage | Model | Description |
|----------|---------|------------------------------------|---|
| Sylvania | 8W | LED8PAR16/DIM/930/FL36/P/LW | PAR16, Soft White, 390 Lumen |
| | 8W | LED8PAR16/GU10/DIM/930/FL36/RP | PAR16, GU10, Soft White, 390 Lumen |
| | 8W | LED8PAR20/DIM/827/FL36 | PAR 20, 2700K |
| | 8W | LED8PAR20/DIM/827/NFL25 | PAR 20, 2700K |
| | 8W | LED8PAR20/DIM/830/FL36 | PAR 20, 3000K |
| | 8W | LED8PAR20/DIM/830/NFL25 | PAR 20, 3000K |
| | 8W | LED8R20/DIM/SE/830/RP | R20, Soft White, 2700K to 2000K, 520 Lumen |
| | 9W | LED/550/RT4/827/FL80/WRFL | 4" Downlight, 2700K |
| | 9W | LED/550/RT4/830/FL80/WRFL | 4" Downlight, 3000K |
| | 10W | LED/600/RT4/830/FL80/RP | Recessed lighting kit, 3000K, 600 Lumen |
| | 10W | LED/700/RT6/830/FL80/RP | Recessed lighting kit, 3000K, 625 Lumen |
| | 10W | LED/RT4/600/827/FL80 | Recessed lighting kit, 2700K, 600 Lumen |
| | 10W | LED/RT6/700/830/FL80 | Recessed lighting kit, 3000K, 700 Lumen |
| | 10W | LED10PAR20/DIM//P/930/FL30 | PAR20, 3000K, 550 Lumen |
| | 10W | LED10PAR30/DIM/SG/827/NFL25 | PAR 30, 2700K |
| | 10W | LED10PAR30/DIM/SG/827/SP10 | PAR 30, 2700K |
| | 10W | LED10PAR30/DIM/SG/827/WSP15 | PAR 30, 2700K |
| | 10W | LED10PAR30/DIM/SG/830/NFL25 | PAR 30, 3000K |
| | 10W | LED10PAR30/DIM/SG/830/SP10 | PAR 30, 3000K |
| | 10W | LED10PAR30/DIM/SG/830/WSP15 | PAR 30, 3000K |
| | 11W | LED/625/RT6/830† | 6" Downlight |
| | 11W | LED11BR30/DIM/HO/827/G3 (78413) | BR30, 2700K, 800 Lumen, E26 |
| | 11W | LED11BR30/DIM/HO/827/G3/RP (78415) | BR30, 2700K, 800 Lumen, E26 |
| | 11W | LED11BR30/DIM/HO/827/G3/RP (79121) | BR30, 2700K, 800 Lumen, E26 |
| | 12W | LED12BR30/DIM/HO/827 | BR30, 2700K, Medium base |
| | 12W | LED12BR30/DIM/HO/827/HVP | BR30, 2700K, Medium base |
| | 12W | LED12BR30/DIM/SE/830/RP | BR30, Soft White, 2700K to 2000K, 850 Lumen |
| | 15W | LED15BR30/DIM/827 | BR30 2700K |
| | 15W | LED15BR40/DIM/HO/827/G3/RP | BR40, Soft White, 2700K, 1100 Lumen, E26, Flood |

† Requires a minimum of 2 lamps

© 02/2015 Lutron Electronics Co., Inc. | P/N 368-3266 REV I

Dimmable CFL & LED bulbs

Compatible with C·L® dimmers



LED bulbs for Maestro® C·L dimmers

Maestro C·L: MACL-153M

Maximum wattage controlled: 150W



| Brand | Wattage | Model | Description |
|-----------|---------|--------------------------------|---|
| Sylvania | 15W | LED15PAR30/DIM/P/930/FL40 | PAR30, 3000K |
| | 15W | LED15PAR30LN/DIM/827/FL40 | PAR30, 2700K |
| | 15W | LED15PAR30LN/DIM/830/NFL25 | PAR30, 3000K |
| | 16W | LED16BR40DIMHO827 | BR40, 2700K, 1100Lumen |
| | 17W | LED17PAR30LN/DIM/830/WSP15/P | PAR30, 3000K, 1200 Lumen, E26, spot |
| | 17W | LED17PAR30LN/DIM/830/WSP20 | PAR30, 3000K, 1200 Lumen, E26, wide spot |
| | 17W | LED17PAR30LN/DIM/P/930/NFL25 | PAR30, 3000K, 900 Lumen |
| | 18W | LED18PAR38/DIM/827/NFL25 | PAR38, 2700K, 860 Lumen |
| | 20W | LED20PAR38/DIM/930/FL40/P2 | PAR38, 3000K, 1000 Lumen |
| | 20W | LED20PAR38DIM830FL40 | PAR38, 3000K, 1300 Lumen |
| | 21W | LED21/PAR38/DIM/P/930/FL30/HVP | PAR38, Warm White, 3000K, 1100 Lumen, E26, 21W |
| | 21W | LED21PAR38/DIM/P/930/FL30 | PAR38, 3000K, 1100 Lumen |
| Toshiba | 13W | LDRB1327WE6USD2 (13BR40/27K-T) | BR40, 2700K, 950 Lumen |
| | 13W | LDRB1340WE6USD2 (13BR40/40L-T) | BR40, 4000K, 1050 Lumen |
| Utilitech | 3W | LG161/2DM/IF/LED | G16.5, Warm White, 3000K, 200 Lumen, E12 base, frosted |
| | 3.5W | LCFCDM/LED† | Candle, Flame Tip Clear, 3000K, Candelabra Base |
| | 3.5W | LEFCDM/LED† | Candle, Flame Tip Clear, 3000K, Medium Base |
| | 4.5W | LR14DMLED | R14, Soft White, 2700K, 300 Lumen, E26, 40WE |
| | 4.8W | LA15DM/CL/300/LED | A15, Warm White, 3000K, 300 Lumen, E26, clear |
| | 4.8W | LA15DM/IF/300/LED | A15, Warm White, 3000K, 300 Lumen, E26, frosted |
| | 4.8W | LA15DMC/CL/300/LED | A15, Warm White, 3000K, 300 Lumen, E12 base, clear |
| | 4.8W | LCFCDM/300/LED† | Candle, 3000K, 310 Lumen, E26, flame tip, clear |
| | 4.8W | LCFFDM/300/LED | Candle, Warm White, 3000K, 300 Lumen, E12 base, frosted flame tip |

† Requires a minimum of 2 lamps

© 02/2015 Lutron Electronics Co., Inc. | P/N 368-3266 REV I

Dimmable CFL & LED bulbs

Compatible with C•L® dimmers



LED bulbs for Maestro® C•L dimmers

Maestro C•L: MACL-153M

Maximum wattage controlled: 150W



| Brand | Wattage | Model | Description |
|-----------|---------|----------------------|--|
| Utilitech | 4.8W | LEFCDM/300/LED† | Candle, 3000K, 310 Lumen, E26, Flame tip, clear |
| | 4.8W | LG161/2DM/CL/300/LED | G16.5, Warm White, 3000K, 300 Lumen, E12 base, clear |
| | 4.8W | LG161/2DM/IF/300/LED | G16.5, Warm White, 3000K, 300 Lumen, E12 base, frosted |
| | 4.8W | LGMDM/CL/300/LED | G16.5, Warm White, 3000K, 300 Lumen, E26, clear |
| | 5W | LMR16GU10DM/LED | MR16, GU10 Base |
| | 6.5W | LMR16/GU10/DM/LED | MR16, GU10 base |
| | 6.5W | LMR16DMGU10 | MR16, GU10 base |
| | 6.5W | LR16DMLED | R16, Soft White, 2700K, 400 Lumen, E26, 40WE |
| | 7.5W | LA19DM/GU24/LED | A19, 3000K, GU24 |
| | 7.5W | LA19DM/LED | A19, 3000K, 450 Lumen, E26 |
| | 7.5W | LA19DM/LEDG2 | A19, 3000K, 450 Lumen |
| | 7.5W | LPAR20DM/5K/LED | PAR20, 5000K |
| | 7.5W | LPAR20DM/LED | PAR20, 3000K |
| | 8W | LA19DM/5K/LED | A19, 5000K |
| | 8W | LG25DM/LEDG2 | G25, Warm White, 3000K, 510 Lumen, E26 |
| | 8W | LR20DM/LED† | R20, 2700K, 450 Lumen (90 mA ridged reflector version) |
| | 9.5W | LPAR20/5K/LEDG5 | PAR20, 5000K, 500 Lumen |
| | 9.5W | LPAR20/LEDG5 | PAR20, 3000K, 450 Lumen |
| | 9.5W | LPAR20DM/SP/LED | PAR20, 3000K, 465 Lumen, Spot |
| | 9.8W | LA19DM/800/LED/G2 | A19, 3000K, 800 Lumen |
| | 10W | LA19DM/800/5K/LEDG2 | A19, 5000K |
| | 10W | LA19DM/800/LEDG2 | A19, 3000K, 800 Lumen |
| | 10W | LG25/DM/LED† | G25, 3000K |
| | 11W | DLS02-41127D1E-WF1 | 4" Downlight, Soft White, 2700K, 650 Lumen, E26 retrofit |
| | 13W | LBR30DM/LEDG2 | BR30 |
| | 13.5W | LA19/OM800/LED | A19, 3000K, 800 Lumen, Omni Directional |
| | 13.5W | LA19DM/800/LED | A19, 3000K |

† Requires a minimum of 2 lamps

© 02/2015 Lutron Electronics Co., Inc. | P/N 368-3266 REV I

Dimmable CFL & LED bulbs

Compatible with C·L® dimmers



LED bulbs for Maestro® C·L dimmers

Maestro C·L: MACL-153M

Maximum wattage controlled: 150W



| Brand | Wattage | Model | Description |
|--------------|-------------------|--------------------------|---|
| Utilitech | 15W | LPAR30L/5K/LEDG5 | PAR30, 5000K, 800 Lumen, long neck flood |
| | 15W | LPAR30L/LEDG5 | PAR30, 3000K, 790 Lumen, long neck flood |
| | 15W | LPAR30LDM/SP/LED | PAR30, 3000K, 790 Lumen, long neck, spot |
| | 15W | LPAR30S/LEDG5 | PAR30, 3000K, 750 Lumen, short neck flood |
| | 16W | LA19/OM1100R/LED | A19, 3000K, 1100 Lumen, Omni Directional |
| | 16W | LBR40DMLEDG2† | BR40, 2700K, 1065 Lumen |
| | 17W | BPCEBR40/DM/LED† | BR40 |
| | 17W | LBR40DM/LED† | BR40, 2700K, 1065 Lumen |
| | 18W | LPAR38DM/5K/LED | PAR38, 5000K |
| | 18W | LPAR38DM/LED | PAR38, 3000K |
| | 20W | L20PAR38/LEDG5 | PAR38, 3000K, 1000 Lumen, flood |
| | 20W | LPAR38/5K/LEDG5 | PAR38, 5000K, 1000 Lumen, flood |
| | 20W | LPAR38/LEDG5 | PAR38, 3000K, 1000 Lumen, flood |
| | 20W | LPAR38DM/SP/LED | PAR38, 3000K, 1000 Lumen, Spot |
| | 22W | LA/OM1600R/5K/LED | A21, Daylight, 5000K, 1600 Lumen |
| | 22W | LA/OM1600R/LED | A21, Warm White, 3000K, 1600 Lumen |
| | 23W | LPAR38/1400/5K/LEDG5 | PAR38, 5000K, 1400 Lumen |
| 23W | LPAR38/1400/LEDG5 | PAR38, 3000K, 1400 Lumen | |
| Westinghouse | 8W | 8A19/LED/DIM/30 | A19, Warm White, 3000K |
| | 8W | 8A19/LED/DIM/50 | A19, Cool White, 5000K |
| | 8W | 8PAR20/LED/DIM30/NFL | PAR20, Warm White, 3000K |
| | 8W | 8PAR20/LED/DIM50/NFL | PAR20, Warm White, 5000K |
| | 15W | 15PAR30/LED/DIM/30/NFL | PAR30, 3000K |
| | 15W | 15PAR30/LED/DIM/50/NFL | PAR30, 5000K |
| | 18W | 18PAR38/LED/DIM/30/NFL | PAR38, 3000K |
| | 18W | 18PAR38/LED/DIM/50/NFL | PAR38, 5000K |

† Requires a minimum of 2 lamps

© 02/2015 Lutron Electronics Co., Inc. | P/N 368-3266 REV I

Dimmable CFL & LED bulbs

Compatible with C·L® dimmers



CFL bulbs* for Maestro® C·L dimmers

Maestro C·L: MACL-153M

Maximum wattage controlled: 150W



| Brand | Wattage | Model | Description |
|-----------------|---------|-------------------------|---|
| EcoSmart | 5W | 8TC05F† | Candle, Torpedo Tip, 2700K, 200 Lumen |
| | 5W | 8TFC05F† | Candle, Flame Tip, 2700K, 200 Lumen |
| | 5W | 8TC05† | Candle, (ES5CCDF052, ES9CCDF052) |
| | 11W | BPESL11R20/DM/ESM | R20, Soft White |
| | 14W | 40114 | Spiral, Soft White (ES5M814DIM2, ES9M814DIM2) |
| | 14W | 2R2014DIM | R20, 2700K, 410 Lumen |
| | 15W | 2R3015DIM | R30 Flood, Soft White (ES5R315DIM2) |
| | 15W | 2R3015DIM50K | R30 Flood, Daylight (ES5R315DIM250K) |
| | 15W | 2R3015DIM35K | R30 Flood, Bright White (ES5R315DIM35K) |
| | 23W | 40123 | Spiral, Soft White (ES5M823DIM2) |
| Feit | 11W | BPESL11R20/DM | R20 |
| | 15W | BPESL15T/DM | Spiral |
| | 23W | BPESL23T/DM | Spiral |
| | 23W | BPESL23R40/DIM | R40 |
| GE | 26W | FLE26HT3/2/DV/SW | Spiral |
| | 26W | FLE26/2/DVR/40 | R40 |
| Philips | 20W | EL/A R40 Dim 20W | R40 |
| Sylvania | 5W | CF5EL/DEC/DIM† | Candle |
| | 5W | CF5EL/B10C/DIM/827/ADP† | Candle |
| | 5W | CF5EL/B10/827/L/DIM† | Candle |
| | 14W | CF14EL/TWIST/DIM | Spiral |
| | 24W | CF24EL/TWIST/DIM | Spiral |
| TCP | 5W | 8TC05F† | Candle |
| | 5W | 8TFC05F† | Candle, flame tip |
| | 14W | 40114 | Spiral |
| | 14W | 2R2014DIM | R20, 2700K, 410 Lumen |
| | 14W | 4R2014TD | R20, TruDim, 2700K |
| | 14W | 4R2014TD30K | R20, TruDim, 3000K |
| | 14W | 4R2014TD35K | R20, TruDim, 3500K |
| | 14W | 4R2014TD41K | R20, TruDim, 4100K |
| | 14W | 4R2014TD50K | R20, TruDim, 5000K |

* CFLs typically require a warmup period before their full dimming range is achieved.

† Requires a minimum of 2 lamps

Dimmable CFL & LED bulbs

Compatible with C·L® dimmers



CFL bulbs* for Maestro® C·L dimmers

Maestro C·L: MACL-153M

Maximum wattage controlled: 150W



| Brand | Wattage | Model | Description |
|------------------|---------|-------------|------------------------|
| TCP | 14W | 4R2014TD65K | R20, TruDim, 6500K |
| | 15W | 2R3015DIM | R30, Soft White, 2700K |
| | 16W | 4R3016TD | R30, TruDim, 2700K |
| | 16W | 4R3016TD30K | R30, TruDim, 3000K |
| | 16W | 4R3016TD35K | R30, TruDim, 3500K |
| | 16W | 4R3016TD41K | R30, TruDim, 4100K |
| | 16W | 4R3016TD50K | R30, TruDim, 5000K |
| | 16W | 4R3016TD65K | R30, TruDim, 6500K |
| | 23W | 40123 | Spiral |
| Utilitech | 11W | LBP11R20DM | R20, Soft White, 2700K |
| | 15W | LBP15TDM | Spiral |
| | 23W | LBP23TDM | Spiral |
| | 23W | LBP23R40DM | R40 |

* CFLs typically require a warmup period before their full dimming range is achieved.

© 02/2015 Lutron Electronics Co., Inc. | P/N 368-3266 REV I

Dimmable CFL & LED bulbs

Compatible with C•L® dimmers



LED bulbs for wall-mounted C•L dimmers

Diva® C•L: DVWCL-153P, DVCL-153P, DVSCCL-153P

Skylark Contour® C•L: CTCL-153P

Skylark C•L: SCL-153P

Lumea® C•L: LGCL-153PH

Toggler®/Ariadni® C•L: TGCL-153P, AYCL-153P

Maximum wattage controlled: 150W



| Brand | Wattage | Model | Description |
|----------------------------|----------------------------|----------------------------------|--|
| Commercial Electric | 12.5W | CE-JB4-600L-27K (T47) | 4" Downlight, 600 Lumen, Soft White, 2700K |
| | 12.5W | CE-JB6-650L-27K (T67) | 6" Downlight, 650 Lumen, Soft White, 2700K |
| | 14.5W | CED6 WW 120 WH | 6" Downlight, White |
| Cooper | 9.4W | RL560WH-R | Halo® Downlight, 600 Lumen, Warm White, 3000K |
| | 14.6W | AP706830WBST24 (ALED3T24) | All-Pro™ 5 or 6" Retrofit Module & Trim |
| | 14.6W | RL706830E26WBS | All-Pro 5 or 6" Retrofit Module & Trim |
| | 14.6W | RL706830WBS | All-Pro 6" Retrofit Module & Trim w/ High-Efficacy Connector |
| Cree | 6W | BA19-04527OMF-12DE26-1U100 | A19, Warm Soft White, 2700K, 450 Lumen, Medium base |
| | 6W | BA19-04527OMF-12DE26-2U100 | A19, Warm Soft White, 2700K, 450 Lumen, Medium base |
| | 6W | BA19-04550OMF-12DE26-2U500 | A19, 5000K, 450 Lumen, 40WE, 4pk |
| | 9W | BA19-08050OMF-12DE26-1U100 | A19, Daylight, 5000K, 800 Lumen, Medium base |
| | 9W | BA19-08050OMF-12DE26-2U100 | A19, Daylight, 5000K, 800 Lumen, Medium base |
| | 9.5W | BA19-08027OMF-12DE26-1U100 | A19, Warm Soft White, 2700K, 800 Lumen, Medium base |
| | 9.5W | BA19-08027OMF-12DE26-2U100 | A19, Soft White, 2700K, 800 Lumen, Medium base |
| | 9.5W | BA19-08027OMF-12DE26-2U500 | A19, 2700K, 800 Lumen, E26, 60WE, 4pk |
| | 9.5W | BBR30-06527FLF-12DE26-1U100 | BR30, 650 Lumen, Soft White, 2700K |
| | 9.5W | BBR30-06550FLF-12DE26-1U100 | BR30, Daylight, 5000K 650 Lumen, 9.5W |
| | 9.5W | CR4-575L | 4" Downlight, 2700K, 575 Lumen, Medium Base |
| | 9.5W | CR6-575L | 6" Downlight, 2700K, Medium Base |
| | 9.5W | CR6-575L-GU24 | 6" Downlight, 2700K, GU24 Base |
| | 9.5W | H1CR6TW62527E04 | 6" Downlight, 2700K, 625 Lumen |
| | 18W | BA21-16027OMF-12DE26-1U100 | A21, 2700K, 1600 Lumen, E26, 18W |
| 18W | BA21-16050OMF-12DE26-1U100 | A21, 5000K, 1600 Lumen, E26, 18W | |

Dimmable CFL & LED bulbs

Compatible with C•L® dimmers



LED bulbs for wall-mounted C•L dimmers

Diva® C•L: DVWCL-153P, DVCL-153P, DVSCCL-153P

Skylark Contour® C•L: CTCL-153P

Skylark C•L: SCL-153P

Lumea® C•L: LGCL-153PH

Toggler®/Ariadni® C•L: TGCL-153P, AYCL-153P

Maximum wattage controlled: 150W



| Brand | Wattage | Model | Description |
|----------|---------|-----------------------------------|---|
| EcoSmart | 4W | ECS B11 CA W27 25WE CL E26 120 DG | B11, 2700K, 200 Lumen, E26 |
| | 6W | ECS 25 40WE W27 120 DG† | G25, 2700K, 400 Lumen, E12 |
| | 6W | ECS GP19 WW 40WE 120 | A19, 3000K |
| | 7W | ECS 25 60WE W27 120 DG† | G25, 2700K, E12 |
| | 8W | ECS 19 CW 120 | A19, Cool White, 5000K |
| | 8W | ECS 19 WW 120 | A19, Warm White, 3000K |
| | 8W | ECS 20 CW FL 120 | PAR20, Daylight, 5000K, 490 Lumen |
| | 8W | ECS 20 CW FL 50WE 120† | PAR20, 5000K, 490 Lumen |
| | 8W | ECS 20 WW FL 120 | PAR20, Warm White, 3000K |
| | 8W | ECS 20 WW FL 50WE 120† | PAR20, 3000K, 450 Lumen |
| | 8W | ECS 25 WW 120 | G25, Warm White, 3000K |
| | 8W | ECS A19 CW 40WE 120† | A19, 5000K, 480 Lumen |
| | 8W | ECS A19 V1 CW 120 | A19, Daylight, 5000K |
| | 8W | ECS A19 V1 WW 120 | A19, Warm White, 3000K |
| | 8W | ECS A19 WW 40WE 120† | A19, 3000K, 450 Lumen |
| | 8W | ECS BR20 50WE CW 120 DG† | BR20, Daylight, 5000K, 600 Lumen, E26 |
| | 8W | ECS BR20 50WE W27 120† | BR20, Soft White, 2700K |
| | 8W | ECS BR20 50WE WW 120 DG† | BR20, Warm White, 3000K, 550 Lumen, E26 |
| | 9.5W | ECO4-575L | 4" Downlight, 2700K, 575 Lumen, Medium Base |
| | 9.5W | ECO4-575L-50K | 4" Downlight, 5000K, 575 Lumen, Medium Base |
| | 9.5W | ECO4-575L-50K-GU24 | 4" Downlight, 5000K, GU24 Base |
| | 9.5W | ECO-575L | 6" Downlight, 2700K, Medium Base |
| | 9.5W | ECO-575L-50K | 6" Downlight, 5000K, Medium Base |
| | 9.5W | ECO-575L-50K-GU24 | 6" Downlight, 5000K, GU24 Base |
| | 9.5W | ECO-575L-GU24 | 6" Downlight, 2700K, GU24 Base |
| | 10W | ECS BR30 65WE CW 120 DG† | BR30, Daylight, 5000K, 700 Lumen, E26 |
| | 10W | ECS BR30 65WE CW 120 DG 3PK† | BR30, Daylight, 5000K, 700 Lumen, E26, 3pk |

† Requires a minimum of 2 lamps

© 02/2015 Lutron Electronics Co., Inc. | P/N 368-3266 REV I

Dimmable CFL & LED bulbs

Compatible with C•L® dimmers



LED bulbs for wall-mounted C•L dimmers

Diva® C•L: DVWCL-153P, DVCL-153P, DVSCCL-153P

Skylark Contour® C•L: CTCL-153P

Skylark C•L: SCL-153P

Lumea® C•L: LGCL-153PH

Toggler®/Ariadni® C•L: TGCL-153P, AYCL-153P

Maximum wattage controlled: 150W



| Brand | Wattage | Model | Description |
|----------|---------------------|-------------------------------|--|
| EcoSmart | 10W | ECS BR30 65WE W27 120 DG† | BR30, Soft White, 2700K, 650 Lumen, E26 |
| | 10W | ECS BR30 65WE W27 120 DG 3BX† | BR30, Soft White, 2700K, 650 Lumen, E26, 3pk |
| | 10W | ECS BR30 65WE WW 120 DG† | BR30, Warm White, 3000K, 650 Lumen, E26 |
| | 10.5W | ECS 30 75WE xxx GB xx 120* | PAR30 Gimbal, Various color temperatures, 75WE |
| | 10.5W | ECS 30 75WE WW GB FL 120 | PAR30 Gimbal, 3000K, 750 Lumen, E26, 75WE |
| | 11W | ECS RFK6 65WE W27 120 REC† | Downlight, Soft White, 2700K, 600 Lumen, E26 |
| | 13W | ECS A19 V2 CW 120 | A19, Daylight, 5000K |
| | 13W | ECS A19 V2 WW 120 | A19, Warm White, 3000K |
| | 15W | ECS 38 CW FL 90WE 120 | PAR38, 5000K, 970 Lumen |
| | 15W | ECS 38 WW FL 90WE 120 | PAR38, 3000K, 900 Lumen |
| | 15W | ECS BR30 W27 FL 120 | BR30, Soft White, 2700K |
| | 16W | ECS 38 90WE WW FL 120 TP | PAR38, Bright White, 3000K, 1000 Lumen, E26 |
| | 16W | ECS BR40 W27 FL 120 | BR40, Soft White, 2700K |
| | 17W | ECS 30 V2 WW FL 120 | PAR30, Warm White, 3000K |
| | 18W | ECS 38 CW FL 120 | PAR38, Daylight, 5000K |
| | 18W | ECS 38 WW FL 120 | PAR38, Warm White, 3000K |
| | 19W | ECS 38 120WE WW FL 120 TP | PAR38, Bright White, 3000K, 1300 Lumen, E26 |
| 24W | ECS 38 V2 WW FL 120 | PAR38, Warm White, 3000K | |
| Feit | 4.5W | R14DM/LED | R14, Soft White, 2700K, 300 Lumen, E26, 40WE |
| | 4.8W | CFCDM/300/LED† | Candle, 3000K, 310 Lumen, Candelabra Base |
| | 4.8W | EFCDM/300/LED† | Candle, 3000K, 310 Lumen, Medium Base |
| | 6.5W | BPMR16/GU10/DM/LED† | MR16, GU10 base |
| | 6.5W | MR16/GU10/DM/LED† | MR16, GU10 base |

* "xx" and "xxx" denote other characters which may be included in the model number.

† Requires a minimum of 2 lamps

© 02/2015 Lutron Electronics Co., Inc. | P/N 368-3266 REV I

Dimmable CFL & LED bulbs

Compatible with C•L® dimmers



LED bulbs for wall-mounted C•L dimmers

Diva® C•L: DVWCL-153P, DVCL-153P, DVSCCL-153P

Skylark Contour® C•L: CTCL-153P

Skylark C•L: SCL-153P

Lumea® C•L: LGCL-153PH

Toggler®/Ariadni® C•L: TGCL-153P, AYCL-153P

Maximum wattage controlled: 150W



| Brand | Wattage | Model | Description |
|-------|---------|--------------------|--|
| Feit | 6.5W | R16DM/LED | R16, Soft White, 2700K, 400 Lumen, E26, 40WE |
| | 7.5W | PAR20DM/5K/LED | PAR20, 5000K |
| | 7.5W | PAR20DM/LED | PAR20, 3000K |
| | 8W | A19/DM/5K/LED | A19, 5000K |
| | 8W | A19/DM/GU24/LED | A19, 3000K, GU24 Base |
| | 8W | A19/DM/LED | A19, 3000K |
| | 8W | A19/DM/LED/CAN | A19 |
| | 8W | A19/DM/LED/RP/CAN | A19 |
| | 8W | BPCEA19/DM/LED | A19 |
| | 8W | BPCER20/DM/LED | R20 (90mA ridged reflector version) |
| | 8W | BPCER20/DM/LED | R20, 2700K, 450 Lumen, E26 Medium base (70mA smooth reflector version) |
| | 8W | R20/927/LED | R20, 2700K |
| | 8W | R20/930/LED | R20, 3000K |
| | 8W | R20/950/LED | R20, 5000K, |
| | 8W | R20/DM/LED | R20, 2700K, 450 Lumen (90mA ridged reflector version) |
| | 8W | R20/DM/LEDG2/CAN | R20, 2700K |
| | 8W | R20DM/LED/CAN | R20 (90mA ridged reflector version) |
| | 9.5W | BPCER20/DM/LED | PAR20 |
| | 9.5W | PAR20/5K/LEDG5 | PAR20, 5000K |
| | 9.5W | PAR20/5K/LEDG5/CAN | PAR20, 5000K |
| | 9.5W | PAR20/LEDG5 | PAR20, 3000K, 450 Lumen |
| | 9.5W | PAR20/LEDG5/CAN | PAR20 |
| | 10W | BPAG800/5K/LED | A19, 5000K |
| | 10W | BPAG800/LED | A19, 3000K, 800 Lumen |
| | 10W | G25/DM/LED | G25, 3000K |
| | 13W | BPCEBR30LED | BR30 |
| | 13.5W | A19/OM800/5K/LED | A19, 5000K, Omni Directional |

Dimmable CFL & LED bulbs

Compatible with C•L® dimmers



LED bulbs for wall-mounted C•L dimmers

Diva® C•L: DVWCL-153P, DVCL-153P, DVSCCL-153P

Skylark Contour® C•L: CTCL-153P

Skylark C•L: SCL-153P

Lumea® C•L: LGCL-153PH

Toggler®/Ariadni® C•L: TGCL-153P, AYCL-153P

Maximum wattage controlled: 150W



| Brand | Wattage | Model | Description |
|-------|-------------------|------------------------------------|--|
| Feit | 13.5W | A19/OM800/LED | A19, 3000K, Omni Directional |
| | 13.5W | A19DM/800/LED | A19, 3000K |
| | 13.5W | BPCEA19/OM800/LED | A19, Omni Directional |
| | 13.5W | BPCEA19/OM800/LED/CAN | A19, Omni Directional |
| | 15W | BPCEPAR30/LEDG5 | PAR30 |
| | 15W | PAR30L/5K/LEDG5 | PAR30, 5000K |
| | 15W | PAR30L/5K/LEDG5/CAN | PAR30, 5000K |
| | 15W | PAR30L/LEDG5 | PAR30 |
| | 15W | PAR30L/LEDG5/CAN | PAR30 |
| | 16W | A19/OM1100R/LED | A19, 3000K, 1100 Lumen, Omni Directional |
| | 16.8W | LEDR56/3K | 5" or 6" Downlight, 3000K, 840 Lumen |
| | 17W | BPCEBR40/LED | BR40, 2700K, 1065 Lumen |
| | 18W | 18PAR38/DM/LED | PAR38, 3000K |
| | 18W | PAR38DM/5K/LED | PAR38, 5000K |
| | 18W | PAR38DM/LED | PAR38, 3000K |
| | 20W | 20PAR38/LEDG5 | PAR38 |
| | 20W | BPCEPAR38/LEDG5 | PAR38 |
| | 20W | PAR38/5K/LEDG5 | PAR38, 5000K |
| | 20W | PAR38/5K/LEDG5/CAN | PAR38, 5000K |
| | 20W | PAR38/LEDG5 | PAR38 |
| | 20W | PAR38/LEDG5/CAN | PAR38 |
| | 20.5W | LEDR56/827 | 5" or 6" Downlight, 2700K, 1245 Lumen |
| 22W | A/OM1600R/27K/LED | A21, 2700K, 1600 Lumen | |
| 22W | A/OM1600R/5K/LED | A21, Daylight, 5000K, 1600 Lumen | |
| 22W | A/OM1600R/LED | A21, Warm White, 3000K, 1600 Lumen | |
| GE | 7W | LED7DP20B827/20 | PAR20, 2700K, Flood, Black Base |
| | 7W | LED7DP20B830/12 | PAR20, 3000K, Spot, Black Base |
| | 7W | LED7DP20B830/20 | PAR20, 3000K, Flood, Black Base |
| | 7W | LED7DP20S827/20 | PAR20, 2700K, Flood, Silver Base |

Dimmable CFL & LED bulbs

Compatible with C•L® dimmers



LED bulbs for wall-mounted C•L dimmers

Diva® C•L: DVWCL-153P, DVCL-153P, DVSCCL-153P

Skylark Contour® C•L: CTCL-153P

Skylark C•L: SCL-153P

Lumea® C•L: LGCL-153PH

Toggler®/Ariadni® C•L: TGCL-153P, AYCL-153P

Maximum wattage controlled: 150W



| Brand | Wattage | Model | Description |
|-------|---------|------------------|---|
| GE | 7W | LED7DP20S830/20 | PAR20, 3000K, Flood, Silver Base |
| | 7W | LED7DP20W827/20 | PAR20, 2700K, Flood, White Base |
| | 7W | LED7DP20W830/12 | PAR20, 3000K, Spot, White Base |
| | 7W | LED7DP20W830/20 | PAR20, 3000K, Flood, White Base |
| | 8W | LED8DA19/827 | A19, 2700K, 450 Lumen, E26 |
| | 10W | LED10DP30S827/20 | PAR30, 2700K, Short Neck, Silver Base |
| | 10W | LED10DP30S830/20 | PAR30, 3000K, Short Neck, Silver Base |
| | 10W | LED10DP30W827/20 | PAR30, 2700K, Short Neck, White Base |
| | 10W | LED10DP3LS827/20 | PAR30, 2700K, Long Neck, Silver Base |
| | 10W | LED10DP3LS830/20 | PAR30, 3000K, Long Neck, Silver Base |
| | 11W | LED11DA19RVL/TP† | A19, 2700K, 570 Lumen |
| | 11W | LED11DA19V2† | A19, 2700K, 800 Lumen |
| | 12W | LED12DR30RVL/BK | BR30, Reveal |
| | 12W | LED12DR30RVL/CDN | BR30, Reveal |
| | 12W | LED12DR30RVL/TP | BR30, Reveal 2850K, 630 Lumen |
| | 18W | LED18D38W827/15 | PAR38, 2700K, E26, 15° Beam |
| | 18W | LED18D38W827/25 | PAR38, 2700K, E26, 25° Beam |
| | 18W | LED18D38W827/40 | PAR38, 2700K, E26, 40° Beam |
| | 18W | LED18D38W830/15 | PAR38, 3000K, 1400 Lumen, E26, 15° Beam |
| | 18W | LED18D38W830/25 | PAR38, 3000K, 1400 Lumen, E26, 25° Beam |
| | 18W | LED18D38W830/40 | PAR38, 3000K, 1400 Lumen, E26, 40° Beam |
| | 18W | LED18D38W927/15 | PAR38, 2700K, 1100 Lumen, E26, 15° Beam |
| | 18W | LED18D38W927/25 | PAR38, 2700K, 1100 Lumen, E26, 25° Beam |
| | 18W | LED18D38W927/40 | PAR38, 2700K, 1100 Lumen, E26, 40° Beam |
| | 18W | LED18D38W930/15 | PAR38, 3000K, 1200 Lumen, E26, 15° Beam |

† Requires a minimum of 2 lamps

© 02/2015 Lutron Electronics Co., Inc. | P/N 368-3266 REV I

Dimmable CFL & LED bulbs

Compatible with C•L® dimmers



LED bulbs for wall-mounted C•L dimmers

Diva® C•L: DWCL-153P, DVCL-153P, DVSCCL-153P

Skylark Contour® C•L: CTCL-153P

Skylark C•L: SCL-153P

Lumea® C•L: LGCL-153PH

Toggler®/Ariadni® C•L: TGCL-153P, AYCL-153P

Maximum wattage controlled: 150W



| Brand | Wattage | Model | Description |
|-------------------------|---------|--------------------|---|
| GE | 18W | LED18D38W930/25 | PAR38, 3000K, 1200 Lumen, E26, 25° Beam |
| | 18W | LED18D38W930/40 | PAR38, 3000K, 1200 Lumen, E26, 40° Beam |
| Halco | 18W | PAR38/18NW/FL/LED† | PAR38, 5000K |
| | 18W | PAR38/18WW/FL/LED† | PAR38, 2700K |
| | 20W | PAR38FL20/827/LED | PAR38, 2700K, 1150 Lumen Flood |
| | 20W | PAR38FL20/830/LED | PAR38, 3000K, 1200 Lumen Flood |
| | 20W | PAR38FL20/840/LED | PAR38, 4000K, 1250 Lumen Flood |
| | 20W | PAR38FL20/850/LED | PAR38, 5000K, 1300 Lumen Flood |
| | 20W | PAR38NFL20/827/LED | PAR38, 2700K, 1150 Lumen Flood |
| | 20W | PAR38NFL20/830/LED | PAR38, 3000K, 1200 Lumen Flood |
| | 20W | PAR38NFL20/840/LED | PAR38, 4000K Flood |
| | 20W | PAR38NFL20/850/LED | PAR38, 5000K, 1300 Lumen Flood |
| | 20W | PAR38SP20/827/LED | PAR38, 2700K, 1150 Lumen Spot |
| | 20W | PAR38SP20/830/LED | PAR38, 3000K, 1200 Lumen Spot |
| | 20W | PAR38SP20/840/LED | PAR38, 4000K Spot |
| | 20W | PAR38SP20/850/LED | PAR38, 5000K, 1300 Lumen Spot |
| Lighting Science | 8W | DFN 19 CW 120 | A19, Cool White, 5000K |
| | 8W | DFN 19 NW 120 | A19, Neutral White, 4000K |
| | 8W | DFN 19 W27 120 | A19, Warm White, 2700K |
| | 8W | DFN 19 WW 120 | A19, Warm White, 3000K |
| | 8W | DFN 20 CW FL 120 | PAR20, Cool White, 5000K |
| | 8W | DFN 20 CW NFL 120 | PAR20, Cool White, 5000K |
| | 8W | DFN 20 NW FL 120 | PAR20, Neutral White, 4000K |
| | 8W | DFN 20 NW NFL 120 | PAR20, Neutral White, 4000K |
| | 8W | DFN 20 W27 FL 120 | PAR20, Warm White, 2700K |
| | 8W | DFN 20 W27 NFL 120 | PAR20, Warm White, 2700K |
| | 8W | DFN 20 WW FL 120 | PAR20, Warm White, 3000K |

† Requires a minimum of 2 lamps

© 02/2015 Lutron Electronics Co., Inc. | P/N 368-3266 REV I

Dimmable CFL & LED bulbs

Compatible with C•L® dimmers



LED bulbs for wall-mounted C•L dimmers

Diva® C•L: DVWCL-153P, DVCL-153P, DVSCCL-153P

Skylark Contour® C•L: CTCL-153P

Skylark C•L: SCL-153P

Lumea® C•L: LGCL-153PH

Toggler®/Ariadni® C•L: TGCL-153P, AYCL-153P

Maximum wattage controlled: 150W



| Brand | Wattage | Model | Description |
|------------------|---------|---------------------------|-----------------------------------|
| Lighting Science | 8W | DFN 20 WW NFL 120 | PAR20, Warm White, 3000K |
| | 8W | DFN 25 CW 120 | G25, Cool White, 5000K |
| | 8W | DFN 25 NW 120 | G25, Neutral White, 4000K |
| | 8W | DFN 25 W27 120 | G25, Warm White, 2700K |
| | 8W | DFN 25 WW 120 | G25, Warm White, 3000K |
| | 8W | DFN A19 V1 CW 120 | A19, Cool White, 5000K |
| | 8W | DFN A19 V1 NW 120 | A19, Neutral White, 4000K |
| | 8W | DFN A19 V1 W27 120 | A19, Warm White, 2700K |
| | 8W | DFN A19 V1 WW 120 | A19, Warm White, 3000K |
| | 10.5W | LS 30 75WE xxx GB xx 120* | PAR30, various color temperatures |
| | 13W | LS GLP6 W27 120 WH S1 BX | 6" Downlight, 2700K, E26 retrofit |
| | 13.5W | DFN A19 V2 CW 120 | A19, Cool White, 5000K |
| | 13.5W | DFN A19 V2 NW 120 | A19, Neutral White, 4000K |
| | 13.5W | DFN A19 V2 W27 120 | A19, Warm White, 2700K |
| | 13.5W | DFN A19 V2 WW 120 | A19, Warm White, 3000K |
| | 14.5W | GLP6 NW WH | 6" Downlight, White, 4000K |
| | 14.5W | GLP6 W27 WH | 6" Downlight, White, 2700K |
| | 14.5W | GLP6 WW WH | 6" Downlight, Warm White, 3000K |
| | 15W | DFN BR30 CW FL 120 | BR30, Cool White, 5000K |
| | 15W | DFN BR30 NW FL 120 | BR30, Neutral White, 4000K |
| | 15W | DFN BR30 W27 FL 120 | BR30, Warm White, 2700K |
| | 15W | DFN BR30 WW FL 120 | BR30, Warm White, 3000K |
| | 16W | DFN BR40 CW 120 | BR40, Cool White, 5000K |
| | 16W | DFN BR40 NW 120 | BR40, Neutral White, 4000K |
| | 16W | DFN BR40 W27 120 | BR40, Warm White, 2700K |
| | 16W | DFN BR40 WW 120 | BR40, Warm White, 3000K |
| | 17W | DFN 30 CW V2 FL 120 | PAR30, Cool White, 5000K |
| | 17W | DFN 30 CW V2 NFL 120 | PAR30, Cool White, 5000K |
| | 17W | DFN 30 NW V2 FL 120 | PAR30, Neutral White, 4000K |

* "xx" and "xxx" denote other characters which may be included in the model number.

© 02/2015 Lutron Electronics Co., Inc. | P/N 368-3266 REV I

Dimmable CFL & LED bulbs

Compatible with C•L® dimmers



LED bulbs for wall-mounted C•L dimmers

Diva® C•L: DVWCL-153P, DVCL-153P, DVSCCL-153P

Skylark Contour® C•L: CTCL-153P

Skylark C•L: SCL-153P

Lumea® C•L: LGCL-153PH

Toggler®/Ariadni® C•L: TGCL-153P, AYCL-153P

Maximum wattage controlled: 150W



| Brand | Wattage | Model | Description |
|------------------|----------------------|--------------------------|---------------------------------------|
| Lighting Science | 17W | DFN 30 NW V2 NFL 120 | PAR30, Neutral White, 4000K |
| | 17W | DFN 30 W27 V2 FL 120 | PAR30, Warm White, 2700K |
| | 17W | DFN 30 W27 V2 NFL 120 | PAR30, Warm White, 2700K |
| | 17W | DFN 30 WW V2 FL 120 | PAR30, Warm White, 3000K |
| | 17W | DFN 30 WW V2 NFL 120 | PAR30, Warm White, 3000K |
| | 18W | DFN 38 CW FL 120 | PAR38, Cool White, 5000K |
| | 18W | DFN 38 CW NFL 120 | PAR38, Cool White, 5000K |
| | 18W | DFN 38 NW FL 120 | PAR38, Neutral White, 4000K |
| | 18W | DFN 38 NW NFL 120 | PAR38, Neutral White, 4000K |
| | 18W | DFN 38 W27 FL 120 | PAR38, Warm White, 2700K |
| | 18W | DFN 38 W27 NFL 120 | PAR38, Warm White, 2700K |
| | 18W | DFN 38 WW FL 120 | PAR38, Warm White, 3000K |
| | 18W | DFN 38 WW NFL 120 | PAR38, Warm White, 3000K |
| | 24W | DFN 38 CW V2 FL 120 | PAR38, Cool White, 5000K |
| | 24W | DFN 38 CW V2 NFL 120 | PAR38, Cool White, 5000K |
| | 24W | DFN 38 NW V2 FL 120 | PAR38, Neutral White, 4000K |
| | 24W | DFN 38 NW V2 NFL 120 | PAR38, Neutral White, 4000K |
| | 24W | DFN 38 W27 V2 FL 120 | PAR38, Warm White, 2700K |
| | 24W | DFN 38 W27 V2 NFL 120 | PAR38, Warm White, 2700K |
| | 24W | DFN 38 WW V2 FL 120 | PAR38, Warm White, 3000K |
| 24W | DFN 38 WW V2 NFL 120 | PAR38, Warm White, 3000K | |
| Litetronics | 14W | LP14550FL2D | BR30, 2700K, 925 Lumen |
| | 14W | LP14550FL4D | BR30, 3000K, 925 Lumen |
| | 14W | LP14550FL6D | BR30, 4000K, 925 Lumen |
| Lumapro | 8W | 8A19/LED/DIM/30 | A19, Warm White, 3000K (6GEM2) |
| | 8W | 8A19/LED/DIM/50 | A19, Cool White, 5000K (6GEM3) |
| | 8W | 8PAR20/LED/DIM30/NFL | PAR20, Warm White, 3000K (6GEM4) |
| | 8W | 8PAR20/LED/DIM50/NFL | PAR20, Cool White, 5000K (6GEM5) |
| Luminus | 18W | TP120-RT5/6-DIM-E | Retrofit downlight, 3000K, 1100 Lumen |

Dimmable CFL & LED bulbs

Compatible with C•L® dimmers



LED bulbs for wall-mounted C•L dimmers

Diva® C•L: DVWCL-153P, DVCL-153P, DVSCCL-153P

Skylark Contour® C•L: CTCL-153P

Skylark C•L: SCL-153P

Lumea® C•L: LGCL-153PH

Toggler®/Ariadni® C•L: TGCL-153P, AYCL-153P

Maximum wattage controlled: 150W



| Brand | Wattage | Model | Description |
|---------|---------|--------------|---|
| Philips | 4W | 9290002120 | MR16, Bright White, 3000K, 200 Lumen, GU10, 4W |
| | 4.5W | 9290002439 | Candle, Warm White, 2700K, 320 Lumen, E26 base, Post Light |
| | 6W | 9290002242 | MR16, 3000K, 300 Lumen, GU10 base |
| | 7W | 9290002020 | PAR20, 2700K, 280 Lumen, Medium Base |
| | 7W | 9290002706 | A19 SlimStyle, Daylight, 5000K, 450 Lumen, E26 |
| | 7W | 9290002706 | A19 SlimStyle, Daylight, 5000K, 450 Lumen, E26 |
| | 7W | 6E26R20 | R20, 2700K |
| | 7W | 7E26PAR20D-1 | PAR20, 2700K, 280 Lumen, Medium Base |
| | 7W | 7E26PAR20-E | PAR20, 2700K |
| | 8W | 8E26A60 | A19, 2700K |
| | 8W | 9290002267 | A19, 2700K, 470 Lumen |
| | 8W | 9290002295 | A19, 5000K, 470 Lumen |
| | 8W | 9290002329 | PAR20, 3000K, 470 Lumen, E26 |
| | 8W | 9290002329 | PAR20, 3000K, 280 Lumen, Medium base |
| | 8W | 9290002330 | PAR20 |
| | 8W | 9290002331 | PAR20 |
| | 8W | 9290002332 | PAR20 |
| | 8W | 9290002333 | PAR20 |
| | 8W | 9290002334 | PAR20 |
| | 8W | 9290002335 | PAR20 |
| | 8W | 9290002704 | A19 SlimStyle, 2700K, 450 Lumen, E26, 40WE |
| | 8.5W | 9290002543 | BR30, 5000K, 730 Lumen, 8.5W |
| | 8.5W | 9290011116 | BR30, 5000K, 730 Lumen, E26 |
| | 9.5W | 9290011117 | BR30, 2700K, 730 Lumen, WarmGlow to 2200K (Nov 2014 or later) |

Dimmable CFL & LED bulbs

Compatible with C•L® dimmers



LED bulbs for wall-mounted C•L dimmers

Diva® C•L: DWCL-153P, DVCL-153P, DVSCCL-153P

Skylark Contour® C•L: CTCL-153P

Skylark C•L: SCL-153P

Lumea® C•L: LGCL-153PH

Toggler®/Ariadni® C•L: TGCL-153P, AYCL-153P

Maximum wattage controlled: 150W



| Brand | Wattage | Model | Description | |
|---------|---------|-----------------|---|-------------------------|
| Philips | 9.5W | 9290011118 | BR30 SlimStyle, 2700K, 650 Lumen, E26, 65WE | |
| | 9.5W | 9290011119 | BR30 SlimStyle, 5000K, 650 Lumen, E26, 65WE | |
| | 10.5W | 9290002544 | BR30, 2700K, 730 Lumen | |
| | 11W | 9290002268 | A19, 2700K, 830 Lumen | |
| | 11W | 9290002296 | A19, 5000K, 830 Lumen | |
| | 11W | 9290011113 | PAR30L, 3000K, E26 | |
| | 12W | 12E26PAR30L-E2 | PAR30, 3000K | |
| | 12.5W | 9290001829 | A19, 2700K, 908 Lumen | |
| | 12.5W | 12E26A60 | A19, 2700K | |
| | 13W | 13E26B30DAAABAA | BR30, 3000K | |
| | 13W | 9290002197 | BR30, 2700K, 721 Lumen | |
| | 13W | 9290002523 | 13PAR38/F25 3000 DIM AF RO | PAR38, 3000K, 950 Lumen |
| | 14.5W | 9290002199 | BR40, 2700K, 832 Lumen | |
| | 15W | 9290002426 | A21, 2700K, 1180 Lumen | |
| | 15W | 9290002595 | A21, Soft White, 2700K, 1180 Lumen, E26 | |
| | 15W | 9290011111 | PAR38, 3000K, 1050 Lumen, E26, Flood | |
| | 15W | 9290011112 | PAR38, 5000K, 1050 Lumen, E26, Flood | |
| | 17W | 9290002018 | A21, 2700K | |
| | 17W | 17E26A21D | A21, 2700K | |
| | 17W | 17E26PAR38-E2 | PAR38, 3000K | |
| | 18W | 18E26PAR38D-2 | PAR38, 2700K | |
| | 19W | 9290002473 | PAR38, 3000K, 1250 Lumen | |
| | 19.5W | 9290002251 | PAR38, 3000K, 1210 Lumen | |
| | 19.5W | 9290002252 | PAR38, 2700K, 1183 Lumen | |
| | 19.5W | 9290002253 | PAR38, 3000K, 1212 Lumen | |
| | 19.5W | 9290002291 | PAR38, 4000K, 1207 Lumen | |
| | 19.5W | 9290002312 | PAR38, 2700K, 1100 Lumen | |
| | 19.5W | 9290002313 | PAR38, 2700K, 1196 Lumen | |

Dimmable CFL & LED bulbs

Compatible with C•L® dimmers



LED bulbs for wall-mounted C•L dimmers

Diva® C•L: DVWCL-153P, DVCL-153P, DVSCCL-153P

Skylark Contour® C•L: CTCL-153P

Skylark C•L: SCL-153P

Lumea® C•L: LGCL-153PH

Toggler®/Ariadni® C•L: TGCL-153P, AYCL-153P

Maximum wattage controlled: 150W



| Brand | Wattage | Model | Description | |
|---------|---------|------------------|--|-------------------------------------|
| Philips | 19.5W | 9290002314 | PAR38, 3000K, 1200 Lumen | |
| | 19.5W | 9290002315 | PAR38, 3000K, 1225 Lumen | |
| | 19.5W | 9290002316 | PAR38, 4000K, 1200 Lumen | |
| | 19.5W | 9290002317 | PAR38, 4000K, 1245 Lumen | |
| | 19.5W | 9290002321 | PAR38, 2700K, 1172 Lumen | |
| | 19.5W | 9290002322 | PAR38, 5000K, 1300 Lumen | |
| | | 22W | 9290002290 | A21, 2700K, 1780 Lumen, Medium base |
| Satco | 5.8W | S8842 thru S8844 | A19 | |
| | 7W | S8827 thru S8838 | PAR30 | |
| | 10.5W | S9037 | A19, 2700K, 810 Lumen, E26 | |
| | 10.5W | S9038 | A19, 3500K, 830 Lumen, E26 | |
| | 10.5W | S9039 | A19, 5000K, 870 Lumen, E26 | |
| | 11W | S9084 | PAR30, 3000K, 780 Lumen, E26, short neck, 25° Beam | |
| | 11W | S9085 | PAR30, 4000K, 780 Lumen, E26, short neck, 25° Beam | |
| | 11W | S9086 | PAR30, 3000K, 780 Lumen, E26, short neck, 40° Beam | |
| | 11W | S9087 | PAR30, 4000K, 780 Lumen, E26, short neck, 40° Beam | |
| | 11W | S9088 | PAR30, 3000K, 780 Lumen, E26, long neck, 25° Beam | |
| | 11W | S9089 | PAR30, 4000K, 780 Lumen, E26, long neck, 25° Beam | |
| | 11W | S9090 | PAR30, 3000K, 780 Lumen, E26, long neck, 40° Beam | |
| | 11W | S9091 | PAR30, 4000K, 780 Lumen, E26, long neck, 40° Beam | |
| | | 13W | S8959 thru S8963 | PAR30 |
| | | 14W | S8814 thru S8819 | PAR30 |
| | 14W | S8821 thru S8826 | PAR30 | |

Dimmable CFL & LED bulbs

Compatible with C•L® dimmers



LED bulbs for wall-mounted C•L dimmers

Diva® C•L: DVWCL-153P, DVCL-153P, DVSCCL-153P

Skylark Contour® C•L: CTCL-153P

Skylark C•L: SCL-153P

Lumea® C•L: LGCL-153PH

Toggler®/Ariadni® C•L: TGCL-153P, AYCL-153P

Maximum wattage controlled: 150W



| Brand | Wattage | Model | Description |
|-------|---------|---------------------|---|
| Satco | 17W | S8852 thru S8859 | PAR38 |
| | 17W | S8861 thru S8864 | PAR38 |
| | 17W | S8977-S8979 | PAR38 |
| | 17W | S8984-S8986 | PAR38 |
| | 17W | S9092 | PAR38, 3000K, 1200 Lumen, E26, 25° beam |
| | 17W | S9093 | PAR38, 4000K, 1200 Lumen, E26, 25° beam |
| | 17W | S9094 | PAR38, 3000K, 1200 Lumen, E26, 40° beam |
| | 17W | S9095 | PAR38, 4000K, 1200 Lumen, E26, 40° beam |
| | 28W | LR38/15/27K/2000/xx | PAR38, 2700K, 2000 Lumen, E26 |
| | 28W | LR38/15/30K/2100/xx | PAR38, 3000K, 2100 Lumen, E26 |
| | 28W | LR38/25/27K/2000/xx | PAR38, 2700K, 2000 Lumen, E26 |
| | 28W | LR38/25/30K/2100/xx | PAR38, 3000K, 2100 Lumen, E26 |
| | 28W | LR38/40/27K/2000/xx | PAR38, 2700K, 2000 Lumen, E26 |
| | 28W | LR38/40/30K/2100/xx | PAR38, 3000K, 2100 Lumen, E26 |
| | Solais | 7W | LRP20/25/27K |
| 7W | | LRP20/25/30K | PAR20, 3000K, 500 Lumen, E26, 25° Beam |
| 7W | | LRP20/40/27K | PAR20, 2700K, 475 Lumen, E26, 40° Beam |
| 7W | | LRP20/40/30K | PAR20, 3000K, 500 Lumen, E26, 40° Beam |
| 11W | | LR20/25/27K/675/xx | PAR20, 2700K, 675 Lumen, E26, narrow flood |
| 11W | | LR20/25/30K/750 | PAR20, 3000K, 750 Lumen, E26, narrow flood |
| 11W | | LR20/40/27K/675/xx | PAR20, 2700K, 675 Lumen, E26, wide flood |
| 11W | | LR20/40/30K/750/xx | PAR20, 3000K, 750 Lumen, E26, wide flood |
| 16W | | LR30/10/27K/1100/xx | PAR30, 2700K, 1100 Lumen, E26, short neck, 10° Beam |
| 16W | | LR30/10/30K/1125/xx | PAR30, 3000K, 1125 Lumen, E26, short neck, 10° Beam |

Dimmable CFL & LED bulbs

Compatible with C•L® dimmers



LED bulbs for wall-mounted C•L dimmers

Diva® C•L: DWCL-153P, DVCL-153P, DVSCCL-153P

Skylark Contour® C•L: CTCL-153P

Skylark C•L: SCL-153P

Lumea® C•L: LGCL-153PH

Toggler®/Ariadni® C•L: TGCL-153P, AYCL-153P

Maximum wattage controlled: 150W



| Brand | Wattage | Model | Description |
|-----------------|---------|-----------------------------------|---|
| Solais | 16W | LR30/10/30K/1200/xx | PAR30, 3000K, 1200 Lumen, E26, short neck, 10° Beam |
| | 16W | LR30/15/27K/1100/xx | PAR30, 2700K, 1100 Lumen, E26, short neck, 15° Beam |
| | 16W | LR30/15/30K/1125/xx | PAR30, 3000K, 1125 Lumen, E26, short neck, 15° Beam |
| | 16W | LR30/15/30K/1200/xx | PAR30, 3000K, 1200 Lumen, E26, short neck, 15° Beam |
| | 16W | LR30/25/27K/1100/xx | PAR30, 2700K, 1100 Lumen, E26, short neck, 25° Beam |
| | 16W | LR30/25/30K/1125/xx | PAR30, 3000K, 1125 Lumen, E26, short neck, 25° Beam |
| | 16W | LR30/25/30K/1200/WH | PAR30, 3000K, 1200 Lumen, E26, short neck, 25° Beam |
| | 16W | LR30/40/27K/1100/xx | PAR30, 2700K, 1100 Lumen, E26, short neck, 40° Beam |
| | 16W | LR30/40/30K/1125/xx | PAR30, 3000K, 1125 Lumen, E26, short neck, 40° Beam |
| | 16W | LR30/40/30K/1200/xx | PAR30, 3000K, 1200 Lumen, E26, short neck, 40° Beam |
| | 16W | LRP38/25/27K | PAR38, 2700K, 1025 Lumen, E26, 25° Beam |
| | 16W | LRP38/25/30K | PAR38, 3000K, 1100 Lumen, E26, 25° Beam |
| | 16W | LRP38/40/27K | PAR38, 2700K, 1025 Lumen, E26, 40° Beam |
| | 16W | LRP38/40/30K | PAR38, 3000K, 1100 Lumen, E26, 40° Beam |
| | 20W | LR38/25/30K/1450/SL | PAR38, 3000K, 1450 Lumen, E26, 15° Beam |
| Switch | 10W | A260FUS27B1 | A19, 800 Lumen |
| Sylvania | 7W | 79120 | PAR20, 2700K, 500 Lumen, E26 |
| | 7W | LED7PAR20/DIM/830/FL30 (78785) | PAR20, 3000K, 450 Lumen, E26, 30° Beam |
| | 7W | LED7PAR20/DIM/830/FL30/RP (79094) | PAR20, 3000K, 450 Lumen, E26, 30° Beam |
| | 8W | LED8A/DIM/F/827 | A19, 2700K |
| | 8W | LED8A/DIM/F/830 | A19, 3000K |

Dimmable CFL & LED bulbs

Compatible with C•L® dimmers



LED bulbs for wall-mounted C•L dimmers

Diva® C•L: DWCL-153P, DVCL-153P, DVSCCL-153P

Skylark Contour® C•L: CTCL-153P

Skylark C•L: SCL-153P

Lumea® C•L: LGCL-153PH

Toggler®/Ariadni® C•L: TGCL-153P, AYCL-153P

Maximum wattage controlled: 150W



| Brand | Wattage | Model | Description |
|----------|---------|------------------------------------|---|
| Sylvania | 8W | LED8A19DIMO827RP | A19, 2700K, 470 Lumen, E26 |
| | 8W | LED8G25/DIM/F/827 | G25, 2700K |
| | 8W | LED8G25/DIM/F/830 | G25, 3000K |
| | 8W | LED8PAR16/DIM/930/FL36/P/LW | PAR16, Soft White, 390 Lumen |
| | 8W | LED8PAR16/GU10/DIM/930/FL36/RP | PAR16, GU10, Soft White, 390 Lumen |
| | 8W | LED8R20/DIM/SE/830/RP | R20, Soft White, 2700K to 2000K, 520 Lumen |
| | 10W | LED/600/RT4/830/FL80/RP | Recessed lighting kit, 3000K, 600 Lumen |
| | 10W | LED/700/RT6/830/FL80/RP | Recessed lighting kit, 3000K, 625 Lumen |
| | 10W | LED/RT4/600/827/FL80 | Recessed lighting kit, 2700K, 600 Lumen |
| | 10W | LED/RT6/700/830/FL80 | Recessed lighting kit, 3000K, 700 Lumen |
| | 10W | LED10PAR20/DIM//P/930/FL30 | PAR20, 3000K, 550 Lumen |
| | 10W | LED10PAR30/DIM/SG/827/NFL25 | PAR 30, 2700K |
| | 10W | LED10PAR30/DIM/SG/827/SP10 | PAR 30, 2700K |
| | 10W | LED10PAR30/DIM/SG/827/WSP15 | PAR 30, 2700K |
| | 10W | LED10PAR30/DIM/SG/830/NFL25 | PAR 30, 3000K |
| | 10W | LED10PAR30/DIM/SG/830/SP10 | PAR 30, 3000K |
| | 10W | LED10PAR30/DIM/SG/830/WSP15 | PAR 30, 3000K |
| | 11W | LED11BR30/DIM/HO/827/G3 (78413) | BR30, 2700K, 800 Lumen, E26 |
| | 11W | LED11BR30/DIM/HO/827/G3/RP (78415) | BR30, 2700K, 800 Lumen, E26 |
| | 11W | LED11BR30/DIM/HO/827/G3/RP (79121) | BR30, 2700K, 800 Lumen, E26 |
| | 12W | LED12BR30/DIM/HO/827 | BR30, 2700K, Medium base |
| | 12W | LED12BR30/DIM/HO/827/HVP | BR30, 2700K, Medium base |
| | 12W | LED12BR30/DIM/SE/830/RP | BR30, Soft White, 2700K to 2000K, 850 Lumen |
| | 14W | LED14PAR38/DIM/830/FL40/W | PAR38, 3000K, 1050 Lumen, E26, Flood, 90WE |
| | 14W | LED14PAR38/DIM/850/FL40WRP | PAR38, 5000K, 1050 Lumen, E26, Flood, 90WE |
| | 15W | LED15PAR30LN/DIM/827/FL40 | PAR30, 2700K |

Dimmable CFL & LED bulbs

Compatible with C•L® dimmers



LED bulbs for wall-mounted C•L dimmers

Diva® C•L: DWCL-153P, DVCL-153P, DVSCCL-153P

Skylark Contour® C•L: CTCL-153P

Skylark C•L: SCL-153P

Lumea® C•L: LGCL-153PH

Toggler®/Ariadni® C•L: TGCL-153P, AYCL-153P

Maximum wattage controlled: 150W



| Brand | Wattage | Model | Description |
|----------|---------|--------------------------------|---|
| Sylvania | 15W | LED15PAR30LN/DIM/830/NFL25 | PAR30, 3000K |
| | 15W | LED15BR40/DIM/HO/827/G3/PP | BR40, Soft White, 2700K, 1100 Lumen, E26, Flood |
| | 16W | LED16BR40DIMHO827 | BR40, 2700K, 1100Lumen |
| | 17W | LED17PAR30LN/DIM/830/WSP15/P | PAR30, 3000K, 1200 Lumen, E26, spot |
| | 17W | LED17PAR30LN/DIM/830/WSP20 | PAR30, 3000K, 1200 Lumen, E26, wide spot |
| | 17W | LED17PAR30LN/DIM/P/930/NFL25 | PAR30, 3000K, 900 Lumen |
| | 20W | LED20PAR38/DIM/830/FL40 | PAR38, 3000K, 1300 Lumen |
| | 20W | LED20PAR38/DIM/930/FL40/P2 | PAR38, 3000K, 1000 Lumen |
| TCP | 11W | LED11E26BR3027K | BR30, 2700K |
| | 14W | LED14E26BR3027K | BR30, 2700K |
| | 17W | LED17E26P3827KFL | PAR38, 2700K |
| | 17W | LED17E26P3827KNFL | PAR38, 2700K |
| | 17W | LED17E26P3830KFL | PAR38, 3000K |
| | 17W | LED17E26P3830KFLBT | PAR38 |
| | 17W | LED17E26P3830KFLWT | PAR38 |
| | 17W | LED17E26P3830KNFL | PAR38, 3000K |
| | 17W | LED17E26P3830KNFLBT | PAR38 |
| | 17W | LED17E26P3830KNFLWT | PAR38 |
| | 17W | LED17E26P3841KFL | PAR38, 4100K |
| | 17W | LED17E26P3841KNFL | PAR38, 4100K |
| | 17W | LED17E26P3850KFL | PAR38, 5000K |
| | 17W | LED17E26P3850KNFL | PAR38, 5000K |
| | Toshiba | 13W | LDRB1327WE6USD2 (13BR40/27K-T) |
| 13W | | LDRB1340WE6USD2 (13BR40/40L-T) | BR40, 4000K, 1050 Lumen |

Dimmable CFL & LED bulbs

Compatible with C•L® dimmers



LED bulbs for wall-mounted C•L dimmers

Diva® C•L: DWCL-153P, DVCL-153P, DVSCCL-153P

Skylark Contour® C•L: CTCL-153P

Skylark C•L: SCL-153P

Lumea® C•L: LGCL-153PH

Toggler®/Ariadni® C•L: TGCL-153P, AYCL-153P

Maximum wattage controlled: 150W



| Brand | Wattage | Model | Description |
|-----------|---------|-----------------------|---|
| Utilitech | 3W | LG161/2DM/IF/LED† | G16.5, Warm White, 3000K, 200 Lumen, E12 base, frosted |
| | 4.5W | LR14DMLED | R14, Soft White, 2700K, 300 Lumen, E26, 40WE |
| | 4.8W | LA15DM/CL/300/LED† | A15, Warm White, 3000K, 300 Lumen, E26, clear |
| | 4.8W | LA15DM/IF/300/LED† | A15, Warm White, 3000K, 300 Lumen, E26, frosted |
| | 4.8W | LA15DMC/CL/300/LED† | A15, Warm White, 3000K, 300 Lumen, E12 base, clear |
| | 4.8W | LCFCDM/300/LED† | Candle, 3000K, 310 Lumen, E26, flame tip, clear |
| | 7.5W | LA19DM/GU24/LED | A19, 3000K, GU24 |
| | 8W | LG25DM/LEDG2† | G25, Warm White, 3000K, 510 Lumen, E26 |
| | 9.5W | LPAR20DM/SP/LED | PAR20, 3000K, 465 Lumen, Spot |
| | 16W | LBR40DMLEDG2 | BR40, 2700K, 1065 Lumen |
| | 4.8W | LCFFDM/300/LED† | Candle, Warm White, 3000K, 300 Lumen, E12 base, frosted flame tip |
| | 4.8W | LEFCDM/300/LED† | Candle, 3000K, 310 Lumen, E26, Flame tip, clear |
| | 4.8W | LG161/2DM/CL/300/LED† | G16.5, Warm White, 3000K, 300 Lumen, E12 base, clear |
| | 4.8W | LG161/2DM/IF/300/LED† | G16.5, Warm White, 3000K, 300 Lumen, E12 base, frosted |
| | 4.8W | LGMDM/CL/300/LED† | G16.5, Warm White, 3000K, 300 Lumen, E26, clear |
| | 6.5W | LMR16/GU10/DM/LED† | MR16, GU10 base |
| | 6.5W | LMR16DMGU10† | MR16, GU10 base |
| | 6.5W | LR16DMLED | R16, Soft White, 2700K, 400 Lumen, E26, 40WE |
| | 7.5W | LA19DM/LED | A19, 3000K, 450 Lumen, E26 |

† Requires a minimum of 2 lamps

© 02/2015 Lutron Electronics Co., Inc. | P/N 368-3266 REV I

Dimmable CFL & LED bulbs

Compatible with C•L® dimmers



LED bulbs for wall-mounted C•L dimmers

Diva® C•L: DVWCL-153P, DVCL-153P, DVSCCL-153P

Skylark Contour® C•L: CTCL-153P

Skylark C•L: SCL-153P

Lumea® C•L: LGCL-153PH

Toggler®/Ariadni® C•L: TGCL-153P, AYCL-153P

Maximum wattage controlled: 150W



| Brand | Wattage | Model | Description |
|-----------|---------|---------------------|--|
| Utilitech | 7.5W | LPAR20DM/5K/LED | PAR20, 5000K |
| | 7.5W | LPAR20DM/LED | PAR20, 3000K |
| | 8W | LA19DM/5K/LED | A19, 5000K |
| | 8W | LR20DM/LED | R20, 2700K, 450 Lumen (90mA ridged reflector version) |
| | 8W | LR20DMLEDG2 | R20, 2700K, 450 Lumen, E26 Medium base (70mA smooth reflector version) |
| | 9.5W | LPAR20/5K/LEDG5 | PAR20, 5000K, 500 Lumen |
| | 9.5W | LPAR20/LEDG5 | PAR20, 3000K, 450 Lumen |
| | 9.8W | LA19DM/800/LED/G2 | A19, 3000K, 800 Lumen |
| | 10W | LA19DM/800/5K/LEDG2 | A19, 5000K |
| | 10W | LA19DM/800/LEDG2 | A19, 3000K, 800 Lumen |
| | 10W | LG25/DM/LED | G25, 3000K |
| | 11W | DLS02-41127D1E-WF1 | 4" Downlight, Soft White, 2700K, 650 Lumen, E26 retrofit |
| | 13W | DLS02-61327D1E-WF1 | 5" or 6" Downlight, Soft White, 2700K, 800 Lumen, E26 retrofit |
| | 13W | DLS02-61350D1E-WF1 | 5" or 6" Downlight, Daylight, 5000K, 800 Lumen, E26 retrofit |
| | 13W | LBR30DM/LEDG2 | BR30 |
| | 13.5W | LA19/OM800/LED | A19, 3000K, 800 Lumen, Omni Directional |
| | 13.5W | LA19DM/800/LED | A19, 3000K |
| | 15W | LPAR30L/5K/LEDG5 | PAR30, 5000K, 800 Lumen, long neck flood |
| | 15W | LPAR30L/LEDG5 | PAR30, 3000K, 790 Lumen, long neck flood |
| | 15W | LPAR30LDM/SP/LED | PAR30, 3000K, 790 Lumen, long neck, spot |
| | 15W | LPAR30S/LEDG5 | PAR30, 3000K, 750 Lumen, short neck flood |
| | 16W | LA19/OM1100R/LED | A19, 3000K, 1100 Lumen, Omni Directional |
| | 18W | LPAR38DM/5K/LED | PAR38, 5000K |
| | 18W | LPAR38DM/LED | PAR38, 3000K |
| | 20W | L20PAR38/LEDG5 | PAR38, 3000K, 1000 Lumen, flood |
| | 20W | LPAR38/5K/LEDG5 | PAR38, 5000K, 1000 Lumen, flood |

Dimmable CFL & LED bulbs

Compatible with C•L® dimmers



LED bulbs for wall-mounted C•L dimmers

Diva® C•L: DWCL-153P, DVCL-153P, DVSCCL-153P

Skylark Contour® C•L: CTCL-153P

Skylark C•L: SCL-153P

Lumea® C•L: LGCL-153PH

Toggler®/Ariadni® C•L: TGCL-153P, AYCL-153P

Maximum wattage controlled: 150W



| Brand | Wattage | Model | Description |
|---------------------|---------|----------------------|------------------------------------|
| Utilitech | 20W | LPAR38/LEDG5 | PAR38, 3000K, 1000 Lumen, flood |
| | 20W | LPAR38DM/SP/LED | PAR38, 3000K, 1000 Lumen, Spot |
| | 22W | LA/OM1600R/5K/LED | A21, Daylight, 5000K, 1600 Lumen |
| | 22W | LA/OM1600R/LED | A21, Warm White, 3000K, 1600 Lumen |
| | 23W | LPAR38/1400/5K/LEDG5 | PAR38, 5000K, 1400 Lumen |
| | 23W | LPAR38/1400/LEDG5 | PAR38, 3000K, 1400 Lumen |
| Westinghouse | 8W | 8A19/LED/DIM/30 | A19, Warm White, 3000K |
| | 8W | 8A19/LED/DIM/50 | A19, Cool White, 5000K |
| | 8W | 8PAR20/LED/DIM30/NFL | PAR20, Warm White, 3000K |
| | 8W | 8PAR20/LED/DIM50/NFL | PAR20, Warm White, 5000K |

Dimmable CFL & LED bulbs

Compatible with C•L® dimmers



CFL bulbs* for wall-mounted C•L dimmers

Diva® C•L: DVWCL-153P, DVCL-153P, DVSCCL-153P

Skylark Contour® C•L: CTCL-153P

Skylark C•L: SCL-153P

Lumea® C•L: LGCL-153PH

Toggler®/Ariadni® C•L: TGCL-153P, AYCL-153P

Maximum wattage controlled: 150W



| Brand | Wattage | Model | Description |
|------------------|---------|------------------------|---|
| Earthmate | 5W | E05129LW | Candle |
| EcoSmart | 5W | 8TC05F | Candle, Torpedo Tip, 2700K, 200 Lumen |
| | 5W | 8TFC05F | Candle, Flame Tip, 2700K, 200 Lumen |
| | 5W | 8TC05 | Candle, (ES5CCDF052, ES9CCDF052) |
| | 11W | BPEL11R20/DM/ESM | R20, Soft White |
| | 14W | 40114 | Spiral, Soft White (ES5M814DIM2, ES9M814DIM2) |
| | 14W | 2R2014DIM | R20, 2700K, 410 Lumen |
| | 15W | 2R3015DIM | R30 Flood, Soft White (ES5R315DIM2) |
| | 15W | 2R3015DIM50K | R30 Flood, Daylight (ES5R315DIM250K) |
| | 15W | 2R3015DIM35K | R30 Flood, Bright White (ES5R315DIM35K) |
| | 23W | 40123 | Spiral, Soft White (ES5M823DIM2) |
| Feit | 11W | BPEL11R20/DM | R20 |
| | 13W | LBP13T2C/DM | Spiral, Candelabra base |
| | 15W | BPEL15T/DM | Spiral |
| | 23W | BPEL23T/DM | Spiral |
| | 23W | BPEL23R40/DIM† | R40 |
| GE | 14W | FLE14HT3/2/DM/SW† | Spiral |
| | 26W | FLE26HT3/2/DV/SW | Spiral |
| | 26W | FLE26/2/DVR/40 | R40 |
| Philips | 16W | EL/A R30 Dim 16W† | R30 |
| | 20W | EL/A R40 Dim 20W | R40 |
| Sylvania | 5W | CF5EL/DEC/DIM | Candle |
| | 5W | CF5EL/B10C/DIM/827/ADP | Candle |
| | 5W | CF5EL/B10/827/L/DIM | Candle |
| | 14W | CF14EL/R20/DIM† | R20 |
| | 14W | CF14EL/TWIST/DIM† | Spiral |
| | 24W | CF24EL/TWIST/DIM† | Spiral |

* CFLs typically require a warmup period before their full dimming range is achieved.

† Requires a minimum of 2 lamps

Dimmable CFL & LED bulbs

Compatible with C•L® dimmers



CFL bulbs* for wall-mounted C•L dimmers

Diva® C•L: DVWCL-153P, DVCL-153P, DVSCCL-153P

Skylark Contour® C•L: CTCL-153P

Skylark C•L: SCL-153P

Lumea® C•L: LGCL-153PH

Toggler®/Ariadni® C•L: TGCL-153P, AYCL-153P

Maximum wattage controlled: 150W



| Brand | Wattage | Model | Description |
|-------|-----------|-------------|------------------------|
| TCP | 3W | 8T03CL | Candle Clear |
| | 5W | 8TC05F | Candle |
| | 5W | 8TFC05F | Candle, flame tip |
| | 8W | 8A08WH | A-bulb |
| | 14W | 40114 | Spiral |
| | 14W | 2R2014DIM | R20, 2700K, 410 Lumen |
| | 14W | 4R2014TD | R20, TruDim, 2700K |
| | 14W | 4R2014TD30K | R20, TruDim, 3000K |
| | 14W | 4R2014TD35K | R20, TruDim, 3500K |
| | 14W | 4R2014TD41K | R20, TruDim, 4100K |
| | 14W | 4R2014TD50K | R20, TruDim, 5000K |
| | 14W | 4R2014TD65K | R20, TruDim, 6500K |
| | 15W | 2R3015DIM | R30, Soft White, 2700K |
| | 16W | 4R3016TD | R30, TruDim, 2700K |
| | 16W | 4R3016TD30K | R30, TruDim, 3000K |
| | 16W | 4R3016TD35K | R30, TruDim, 3500K |
| | 16W | 4R3016TD41K | R30, TruDim, 4100K |
| | 16W | 4R3016TD50K | R30, TruDim, 5000K |
| | 16W | 4R3016TD65K | R30, TruDim, 6500K |
| | Utilitech | 23W | 10123 |
| 23W | | 40123 | Spiral |
| 11W | | LBP11R20DM | R20, Soft White, 2700K |
| 15W | | LBP15TDM | Spiral |
| 23W | | LBP23TDM | Spiral |
| | 23W | LBP23R40DM | R40 |

* CFLs typically require a warmup period before their full dimming range is achieved.

Dimmable CFL & LED bulbs

Compatible with C·L® dimmers



LED bulbs for C·L lamp dimmers

Credenza® C·L: TTCL-100H

Maximum wattage controlled: 100W



| Brand | Wattage | Model | Description |
|-------------------------|---------------|------------------------------------|---|
| Cree | 6W | BA19-04527OMF-12DE26-1U100 | A19, Warm Soft White, 2700K, 450 Lumen, Medium base |
| | 9W | BA19-08050OMF-12DE26-1U100 | A19, Daylight, 5000K, 800 Lumen, Medium base |
| | 9.5W | BA19-08027OMF-12DE26-1U100 | A19, Warm Soft White, 2700K, 800 Lumen, Medium base |
| | 18W | BA21-16027OMF-12DE26-1U100 | A21, 2700K, 1600 Lumen, E26 |
| | 18W | BA21-16050OMF-12DE26-1U100 | A21, 5000K, 1600 Lumen, E26 |
| EcoSmart | 8W | ECS 19 WW 120 | A19, Warm White, 3000K |
| | 8W | ECS A19 V1 CW 120 | A19, Daylight, 5000K |
| | 8W | ECS A19 V1 WW 120 | A19, Warm White, 3000K |
| | 13W | ECS A19 V2 CW 120 | A19, Daylight, 5000K |
| | 13W | ECS A19 V2 WW 120 | A19, Warm White, 3000K |
| Feit | 6.5W | R16DM/LED | R16, Soft White, 2700K, 400 Lumen, E26, 40WE |
| | 10W | BPAG800/5K/LED | A19, 5000K |
| | 10W | BPAG800/LED | A19, 3000K, 800 Lumen |
| | 22W | A/OM1600R/27K/LED | A21, 2700K, 1600 Lumen |
| | 22W | A/OM1600R/5K/LED | A21, Daylight, 5000K, 1600 Lumen |
| 22W | A/OM1600R/LED | A21, Warm White, 3000K, 1600 Lumen | |
| GE | 14W | LED14DA21V2/827W | A21, 2700K, 1100 Lumen, E26 |
| Lighting Science | 8W | DFN 19 CW 120 | A19, Cool White, 5000K |
| | 8W | DFN 19 NW 120 | A19, Neutral White, 4000K |
| | 8W | DFN 19 W27 120 | A19, Warm White, 2700K |
| | 8W | DFN 19 WW 120 | A19, Warm White, 3000K |
| | 8W | DFN A19 V1 CW 120 | A19, Cool White, 5000K |
| | 8W | DFN A19 V1 NW 120 | A19, Neutral White, 4000K |
| | 8W | DFN A19 V1 W27 120 | A19, Warm White, 2700K |
| | 8W | DFN A19 V1 WW 120 | A19, Warm White, 3000K |
| | 13.5W | DFN A19 V2 CW 120 | A19, Cool White, 5000K |
| | 13.5W | DFN A19 V2 NW 120 | A19, Neutral White, 4000K |
| | 13.5W | DFN A19 V2 W27 120 | A19, Warm White, 2700K |
| | 13.5W | DFN A19 V2 WW 120 | A19, Warm White, 3000K |

Dimmable CFL & LED bulbs

Compatible with C·L® dimmers



LED bulbs for C·L lamp dimmers

Credenza® C·L: TTCL-100H

Maximum wattage controlled: 100W



| Brand | Wattage | Model | Description |
|---------------------|---------|---------------------|--|
| Lumapro | 8W | 8A19/LED/DIM/30 | A19, Warm White, 3000K (6GEM2) |
| | 8W | 8A19/LED/DIM/50 | A19, Cool White, 5000K (6GEM3) |
| Philips | 7W | 7E26A60 | A19 EnduraLED 2700K |
| | 8W | 8E26A60 | A19, 2700K |
| | 12.5W | 12E26A60 | A19, 2700K |
| | 15W | 9290002426 | A21, 2700K, 1180 Lumen |
| | 15W | 9290002595 | A21, Soft White, 2700K, 1180 Lumen, E26 |
| Switch | 10W | A260FUS27B1 | A19, 800 Lumen |
| | 13W | 75FU202 | A19, 3000K, 1100 Lumen, E26 |
| Sylvania | 8W | LED8A/DIM/F/827 | A19, 2700K |
| | 8W | LED8A/DIM/F/830 | A19, 3000K |
| Utilitech | 6.5W | LR16DMLED | R16, Soft White, 2700K, 400 Lumen, E26, 40WE |
| | 9.8W | LA19DM/800/LED/G2 | A19, 3000K, 800 Lumen |
| | 10W | LA19DM/800/5K/LEDG2 | A19, 5000K |
| | 10W | LA19DM/800/LEDG2 | A19, 3000K, 800 Lumen |
| | 22W | LA/OM1600R/5K/LED | A21, Daylight, 5000K, 1600 Lumen |
| | 22W | LA/OM1600R/LED | A21, Warm White, 3000K, 1600 Lumen |
| Westinghouse | 8W | 8A19/LED/DIM/30 | A19, Warm White, 3000K |
| | 8W | 8A19/LED/DIM/50 | A19, Cool White, 5000K |

Dimmable CFL & LED bulbs

Compatible with C·L® dimmers



CFL bulbs* for C·L lamp dimmers

Credenza® C·L: TTCL-100H

Maximum wattage controlled: 100W



| Brand | Wattage | Model | Description |
|--------------------|---------|------------------|---|
| EcoSmart | 14W | 40114 | Spiral, Soft White (ES5M814DIM2, ES9M814DIM2) |
| | 23W | 10123 | Spiral |
| | 23W | 40123 | Spiral, Soft White (ES5M823DIM2) |
| Feit | 15W | BPESEL15T/DM | Spiral |
| | 23W | BPESEL23T/DM | Spiral |
| Litetronics | 5W | MB-500D | A19 |
| | 5W | MB-500DL | A19 |
| | 8W | MB-800D | A19 |
| | 8W | MB-800DL | A19 |
| | 11W | MB-15527D | Post Light |
| | 27W | L-27527D | Spiral |
| Philips | 15W | EL/mdt DIM 15W | Spiral |
| | 20W | EL/mdt DIM 20W | Spiral |
| | 32W | EL/dt Dim 32W | Spiral |
| Sylvania | 14W | CF14EL/TWIST/DIM | Spiral |
| | 24W | CF24EL/TWIST/DIM | Spiral |
| TCP | 14W | 40114 | Spiral |
| | 23W | 10123 | Spiral |
| | 23W | 40123 | Spiral |
| Utilitech | 15W | LBP15TDM | Spiral |
| | 23W | LBP23TDM | Spiral |

* CFLs typically require a warmup period before their full dimming range is achieved.

© 02/2015 Lutron Electronics Co., Inc. | P/N 368-3266 REV I

Dimmable CFL & LED bulbs

Compatible with C·L® dimmers



LED bulbs for Maestro Wireless® C·L dimmers

Maestro Wireless: MRF2-6CL

More bulbs coming soon for Maestro Wireless C·L Dimmers

Maximum wattage controlled: 150W



| Brand | Wattage | Model | Description |
|-------|-----------------|---------------------------------------|--|
| Cree | 9W | BA19-08050OMF-12DE26-1U100 | A19, Daylight, 5000K, 800 Lumen, Medium base |
| | 9W | BA19-08050OMF-12DE26-2U100 | A19, Daylight, 5000K, 800 Lumen, Medium base |
| | 9.5W | BA19-08027OMF-12DE26-2U100 | A19, Soft White, 2700K, 800 Lumen, Medium base |
| | 9.5W | BA19-08027OMF-12DE26-2U500 | A19, 2700K, 800 Lumen, E26, 60WE, 4pk |
| | 9.5W | BBR30-06527FLF-12DE26-1U100 | BR30, 650 Lumen, Soft White, 2700K |
| | 9.5W | BBR30-06550FLF-12DE26-1U100 | BR30, Daylight, 5000K 650 Lumen, 9.5W |
| | 18W | BA21-16027OMF-12DE26-1U100 | A21, 2700K, 1600 Lumen, E26, 18W |
| | 18W | BA21-16050OMF-12DE26-1U100 | A21, 5000K, 1600 Lumen, E26, 18W |
| Feit | 4.5W | R14DM/LED | R14, Soft White, 2700K, 300 Lumen, E26, 40WE |
| | 6.5W | BPMR16/GU10/DM/LED† | MR16, GU10 base |
| | 6.5W | MR16/GU10/DM/LED† | MR16, GU10 base |
| | 6.5W | R16DM/LED | R16, Soft White, 2700K, 400 Lumen, E26, 40WE |
| | 13W | BPCEBR30LED | BR30 |
| | 13.5W | A19/OM800/5K/LED† | A19, 5000K, Omni Directional |
| | 13.5W | A19/OM800/LED† | A19, 3000K, Omni Directional |
| | 13.5W | BPCEA19/OM800/LED† | A19, Omni Directional |
| | 13.5W | BPCEA19/OM800/LED/CAN† | A19, Omni Directional |
| | 16.8W | LEDR56/3K† | 5" or 6" Downlight, 3000K, 840 Lumen |
| | 17W | BPCEBR40/LED | BR40, 2700K, 1065 Lumen |
| | 17W | BR40/DM/LED† | BR40, 2700K, 1065 Lumen |
| | 20W | 20PAR38/LEDG5 | PAR38 |
| | 20W | BPCEPAR38/LEDG5 | PAR38 |
| | 20W | PAR38/5K/LEDG5 | PAR38, 5000K |
| | 20W | PAR38/5K/LEDG5/CAN | PAR38, 5000K |
| | 20W | PAR38/LEDG5 | PAR38 |
| 20W | PAR38/LEDG5/CAN | PAR38 | |
| 20.5W | LEDR56/827 | 5" or 6" Downlight, 2700K, 1245 Lumen | |

† Requires a minimum of 2 lamps

© 02/2015 Lutron Electronics Co., Inc. | P/N 368-3266 REV I

Dimmable CFL & LED bulbs

Compatible with C·L® dimmers



LED bulbs for Maestro Wireless® C·L dimmers

Maestro Wireless: MRF2-6CL

More bulbs coming soon for Maestro Wireless C·L Dimmers

Maximum wattage controlled: 150W



| Brand | Wattage | Model | Description |
|--------------------|---------|--------------------|---|
| GE | 11W | LED11DA19RVL/TP | A19, 2700K, 570 Lumen |
| | 11W | LED11DA19V2 | A19, 2700K, 800 Lumen |
| Halco | 20W | PAR38FL20/827/LED | PAR38, 2700K, 1150 Lumen Flood |
| | 20W | PAR38FL20/830/LED | PAR38, 3000K, 1200 Lumen Flood |
| Halco | 20W | PAR38FL20/840/LED | PAR38, 4000K, 1250 Lumen Flood |
| | 20W | PAR38FL20/850/LED | PAR38, 5000K, 1300 Lumen Flood |
| | 20W | PAR38NFL20/827/LED | PAR38, 2700K, 1150 Lumen Flood |
| | 20W | PAR38NFL20/830/LED | PAR38, 3000K, 1200 Lumen Flood |
| | 20W | PAR38NFL20/840/LED | PAR38, 4000K Flood |
| | 20W | PAR38NFL20/850/LED | PAR38, 5000K, 1300 Lumen Flood |
| | 20W | PAR38SP20/827/LED | PAR38, 2700K, 1150 Lumen Spot |
| | 20W | PAR38SP20/830/LED | PAR38, 3000K, 1200 Lumen Spot |
| | 20W | PAR38SP20/840/LED | PAR38, 4000K Spot |
| | 20W | PAR38SP20/850/LED | PAR38, 5000K, 1300 Lumen Spot |
| Litetronics | 14W | LP14550FL2D† | BR30, 2700K, 925 Lumen |
| | 14W | LP14550FL4D† | BR30, 3000K, 925 Lumen |
| | 14W | LP14550FL6D† | BR30, 4000K, 925 Lumen |
| Philips | 3.5W | 9290002417† | Candle, 2700K, 150 Lumen, E12 Candelabra base |
| | 3.5W | 9290002419† | Candle, 2700K, 150 Lumen, E26 medium base, blunt tip clear |
| | 8W | 9290002329 | PAR20, 3000K, 470 Lumen, E26 |
| | 8.5W | 9290002543 | BR30, 5000K, 730 Lumen, 8.5W |
| | 9.5W | 9290011117 | BR30, 2700K, 730 Lumen, WarmGlow to 2200K (Nov 2014 or later) |
| | 9.5W | 9290011118 | BR30 SlimStyle, 2700K, 650 Lumen, E26, 65WE |
| | 9.5W | 9290011119 | BR30 SlimStyle, 5000K, 650 Lumen, E26, 65WE |
| | 10.5W | 9290002544 | BR30, 2700K, 730 Lumen |
| | 11W | 9290002268 | A19, 2700K, 830 Lumen |
| | 11W | 9290002296 | A19, 5000K, 830 Lumen |

† Requires a minimum of 2 lamps

© 02/2015 Lutron Electronics Co., Inc. | P/N 368-3266 REV I

Dimmable CFL & LED bulbs

Compatible with C·L® dimmers



LED bulbs for Maestro Wireless® C·L dimmers

Maestro Wireless: MRF2-6CL

More bulbs coming soon for Maestro Wireless C·L Dimmers

Maximum wattage controlled: 150W



| Brand | Wattage | Model | Description |
|---------|---------|---------------------------------------|---|
| Philips | 13W | 9290002523 13PAR38/F25 3000 DIM AF RO | PAR38, 3000K, 950 Lumen |
| | 15W | 9290002426 | A21, 2700K, 1180 Lumen |
| | 15W | 9290002595 | A21, Soft White, 2700K, 1180 Lumen, E26 |
| | 15W | 9290011111 | PAR38, 3000K, 1050 Lumen, E26, Flood |
| | 15W | 9290011112 | PAR38, 5000K, 1050 Lumen, E26, Flood |
| | 18W | 9290002202 | PAR38, 3000K, 951 Lumen, Medium Base |
| | 18W | 9290002236 | PAR38 |
| | 18W | 9290002237 | PAR38 |
| | 18W | 9290002245 | PAR38, 2700K, 938 Lumen |
| | 18W | 9290002246 | PAR38 |
| | 18W | 9290002307 | PAR38 |
| | 18W | 9290002308 | PAR38 |
| | 18W | 9290002309 | PAR38 |
| | 18W | 9290002310 | PAR38 |
| | 18W | 9290002311 | PAR38 |
| | 18W | 18E26PAR38-3 | PAR38 |
| | 18W | 18E26PAR38-4 | PAR38 |
| | 19W | 9290002473 | PAR38, 3000K, 1250 Lumen |
| | 19.5W | 9290002251 | PAR38, 3000K, 1210 Lumen |
| | 19.5W | 9290002252 | PAR38, 2700K, 1183 Lumen |
| | 19.5W | 9290002253 | PAR38, 3000K, 1212 Lumen |
| | 19.5W | 9290002291 | PAR38, 4000K, 1207 Lumen |
| | 19.5W | 9290002312 | PAR38, 2700K, 1100 Lumen |
| | 19.5W | 9290002313 | PAR38, 2700K, 1196 Lumen |
| | 19.5W | 9290002314 | PAR38, 3000K, 1200 Lumen |
| | 19.5W | 9290002315 | PAR38, 3000K, 1225 Lumen |
| | 19.5W | 9290002316 | PAR38, 4000K, 1200 Lumen |
| | 19.5W | 9290002317 | PAR38, 4000K, 1245 Lumen |
| | 19.5W | 9290002321 | PAR38, 2700K, 1172 Lumen |
| | 19.5W | 9290002322 | PAR38, 5000K, 1300 Lumen |
| | 22W | 9290002290 | A21, 2700K, 1780 Lumen, Medium base |

† Requires a minimum of 2 lamps

© 02/2015 Lutron Electronics Co., Inc. | P/N 368-3266 REV I

Dimmable CFL & LED bulbs

Compatible with C·L® dimmers



LED bulbs for Maestro Wireless® C·L dimmers

Maestro Wireless: MRF2-6CL

More bulbs coming soon for Maestro Wireless C·L Dimmers

Maximum wattage controlled: 150W



| Brand | Wattage | Model | Description |
|-------|---------|---------------------|--|
| Satco | 8W | S8794 | A19, 2700K, 450 Lumen, GU10 |
| | 8W | S8995 | A19, 3000K, 450 Lumen |
| | 9W | S8991 | 4" Downlight |
| | 11W | S9084 | PAR30, 3000K, 780 Lumen, E26, short neck, 25° Beam |
| | 11W | S9085 | PAR30, 4000K, 780 Lumen, E26, short neck, 25° Beam |
| | 11W | S9086 | PAR30, 3000K, 780 Lumen, E26, short neck, 40° Beam |
| | 11W | S9087 | PAR30, 4000K, 780 Lumen, E26, short neck, 40° Beam |
| | 11W | S9088 | PAR30, 3000K, 780 Lumen, E26, long neck, 25° Beam |
| | 11W | S9089 | PAR30, 4000K, 780 Lumen, E26, long neck, 25° Beam |
| | 11W | S9090 | PAR30, 3000K, 780 Lumen, E26, long neck, 40° Beam |
| | 11W | S9091 | PAR30, 4000K, 780 Lumen, E26, long neck, 40° Beam |
| | 13W | S9003 | R40, 3000K, 880 Lumen |
| | 13W | S9046 | R40, 2700K, 850 Lumen |
| | 13W | S9047 | R40, 4000K, 920 Lumen |
| | 13W | S9048 | R40, 5000K, 950 Lumen |
| | 17W | S8977-S8979 | PAR38 |
| | 17W | S8984-S8986 | PAR38 |
| | 17W | S9092 | PAR38, 3000K, 1200 Lumen, E26, 25° beam |
| | 17W | S9093 | PAR38, 4000K, 1200 Lumen, E26, 25° beam |
| | 17W | S9094 | PAR38, 3000K, 1200 Lumen, E26, 40° beam |
| | 17W | S9095 | PAR38, 4000K, 1200 Lumen, E26, 40° beam |
| | 28W | LR38/15/27K/2000/xx | PAR38, 2700K, 2000 Lumen, E26 |
| | 28W | LR38/15/30K/2100/xx | PAR38, 3000K, 2100 Lumen, E26 |
| | 28W | LR38/25/27K/2000/xx | PAR38, 2700K, 2000 Lumen, E26 |

Dimmable CFL & LED bulbs

Compatible with C·L® dimmers



LED bulbs for Maestro Wireless® C·L dimmers

Maestro Wireless: MRF2-6CL

More bulbs coming soon for Maestro Wireless C·L Dimmers

Maximum wattage controlled: 150W



| Brand | Wattage | Model | Description |
|---------------|---------------------|---|---|
| Satco | 28W | LR38/25/30K/2100/xx | PAR38, 3000K, 2100 Lumen, E26 |
| | 28W | LR38/40/27K/2000/xx | PAR38, 2700K, 2000 Lumen, E26 |
| | 28W | LR38/40/30K/2100/xx | PAR38, 3000K, 2100 Lumen, E26 |
| Solais | 7W | LRP20/25/27K | PAR20, 2700K, 475 Lumen, E26, 25° Beam |
| | 7W | LRP20/25/30K | PAR20, 3000K, 500 Lumen, E26, 25° Beam |
| | 7W | LRP20/40/27K | PAR20, 2700K, 475 Lumen, E26, 40° Beam |
| | 7W | LRP20/40/30K | PAR20, 3000K, 500 Lumen, E26, 40° Beam |
| | 11W | LR20/25/27K/675/xx | PAR20, 2700K, 675 Lumen, E26, narrow flood |
| | 11W | LR20/25/30K/750 | PAR20, 3000K, 750 Lumen, E26, narrow flood |
| | 11W | LR20/40/27K/675/xx | PAR20, 2700K, 675 Lumen, E26, wide flood |
| | 11W | LR20/40/30K/750/xx | PAR20, 3000K, 750 Lumen, E26, wide flood |
| | 16W | LR30/10/27K/1100/xx | PAR30, 2700K, 1100 Lumen, E26, short neck, 10° Beam |
| | 16W | LR30/10/30K/1125/xx | PAR30, 3000K, 1125 Lumen, E26, short neck, 10° Beam |
| | 16W | LR30/10/30K/1200/xx | PAR30, 3000K, 1200 Lumen, E26, short neck, 10° Beam |
| | 16W | LR30/15/27K/1100/xx | PAR30, 2700K, 1100 Lumen, E26, short neck, 15° Beam |
| | 16W | LR30/15/30K/1125/xx | PAR30, 3000K, 1125 Lumen, E26, short neck, 15° Beam |
| | 16W | LR30/15/30K/1200/xx | PAR30, 3000K, 1200 Lumen, E26, short neck, 15° Beam |
| | 16W | LR30/25/27K/1100/xx | PAR30, 2700K, 1100 Lumen, E26, short neck, 25° Beam |
| | 16W | LR30/25/30K/1125/xx | PAR30, 3000K, 1125 Lumen, E26, short neck, 25° Beam |
| | 16W | LR30/25/30K/1200/WH | PAR30, 3000K, 1200 Lumen, E26, short neck, 25° Beam |
| 16W | LR30/40/27K/1100/xx | PAR30, 2700K, 1100 Lumen, E26, short neck, 40° Beam | |

Dimmable CFL & LED bulbs

Compatible with C·L® dimmers



LED bulbs for Maestro Wireless® C·L dimmers

Maestro Wireless: MRF2-6CL

More bulbs coming soon for Maestro Wireless C·L Dimmers

Maximum wattage controlled: 150W



| Brand | Wattage | Model | Description |
|----------|----------------------------|--|---|
| Solais | 16W | LR30/40/30K/1125/xx | PAR30, 3000K, 1125 Lumen, E26, short neck, 40° Beam |
| | 16W | LR30/40/30K/1200/xx | PAR30, 3000K, 1200 Lumen, E26, short neck, 40° Beam |
| | 16W | LRP38/25/27K | PAR38, 2700K, 1025 Lumen, E26, 25° Beam |
| | 16W | LRP38/25/30K | PAR38, 3000K, 1100 Lumen, E26, 25° Beam |
| | 16W | LRP38/40/27K | PAR38, 2700K, 1025 Lumen, E26, 40° Beam |
| | 16W | LRP38/40/30K | PAR38, 3000K, 1100 Lumen, E26, 40° Beam |
| | 20W | LR38/25/30K/1450/SL | PAR38, 3000K, 1450 Lumen, E26, 15° Beam |
| Switch | 13W | 75FU202† | A19, 3000K, 1100 Lumen, E26 |
| Sylvania | 8W | LED8A19DIMO827RP | A19, 2700K, 470 Lumen, E26 |
| | 8W | LED8PAR16/DIM/930/FL36/P/LW† | PAR16, Soft White, 390 Lumen |
| | 8W | LED8PAR16/GU10/DIM/930/FL36/RP† | PAR16, GU10, Soft White, 390 Lumen |
| | 8W | LED8R20/DIM/SE/830/RP | R20, Soft White, 2700K to 2000K, 520 Lumen |
| | 11W | LED11BR30/DIM/HO/827/G3 (78413) | BR30, 2700K, 800 Lumen, E26 |
| | 11W | LED11BR30/DIM/HO/827/G3/RP (78415) | BR30, 2700K, 800 Lumen, E26 |
| | 11W | LED11BR30/DIM/HO/827/G3/RP (79121) | BR30, 2700K, 800 Lumen, E26 |
| | 11W | LED11PAR20/DIM/930/FL30/P2 | PAR20, Soft White, 550 Lumen |
| | 12W | LED12BR30/DIM/HO/827 | BR30, 2700K, Medium base |
| | 12W | LED12BR30/DIM/HO/827/HVP | BR30, 2700K, Medium base |
| | 12W | LED12BR30/DIM/SE/830/RP | BR30, Soft White, 2700K to 2000K, 850 Lumen |
| | 14W | 79084 | A19, Soft White, 2700K, 1100 Lumen, E26 |
| | 14W | LED14PAR38/DIM/830/FL40/W | PAR38, 3000K, 1050 Lumen, E26, Flood, 90WE |
| | 14W | LED14PAR38/DIM/850/FL40WRP | PAR38, 5000K, 1050 Lumen, E26, Flood, 90WE |
| | 16W | LED16BR40DIMHO827 | BR40, 2700K, 1100Lumen |
| | 17W | LED17PAR30LN/DIM/830/WSP15/P | PAR30, 3000K, 1200 Lumen, E26, spot |
| 17W | LED17PAR30LN/DIM/830/WSP20 | PAR30, 3000K, 1200 Lumen, E26, wide spot | |

† Requires a minimum of 2 lamps

© 02/2015 Lutron Electronics Co., Inc. | P/N 368-3266 REV I

Dimmable CFL & LED bulbs

Compatible with C·L® dimmers



LED bulbs for Maestro Wireless® C·L dimmers

Maestro Wireless: MRF2-6CL

More bulbs coming soon for Maestro Wireless C·L Dimmers

Maximum wattage controlled: 150W



| Brand | Wattage | Model | Description |
|-----------|---------|--------------------------------|---|
| Sylvania | 18W | LED18PAR38/DIM/827/NFL25† | PAR38, 2700K, 860 Lumen |
| | 20W | LED20PAR38/DIM/930/FL40/P2 | PAR38, 3000K, 1000 Lumen |
| | 20W | LED20PAR38DIM830FL40 | PAR38, 3000K, 1300 Lumen |
| Toshiba | 13W | LDRB1327WE6USD2 (13BR40/27K-T) | BR40, 2700K, 950 Lumen |
| | 13W | LDRB1340WE6USD2 (13BR40/40L-T) | BR40, 4000K, 1050 Lumen |
| Utilitech | 3W | LG161/2DM/IF/LED | G16.5, Warm White, 3000K, 200 Lumen, E12 base, frosted |
| | 4.5W | LR14DMLED | R14, Soft White, 2700K, 300 Lumen, E26, 40WE |
| | 4.8W | LA15DM/CL/300/LED | A15, Warm White, 3000K, 300 Lumen, E26, clear |
| | 4.8W | LA15DM/IF/300/LED | A15, Warm White, 3000K, 300 Lumen, E26, frosted |
| | 4.8W | LA15DMC/CL/300/LED | A15, Warm White, 3000K, 300 Lumen, E12 base, clear |
| | 4.8W | LCFCDM/300/LED | Candle, 3000K, 310 Lumen, E26, flame tip, clear |
| | 4.8W | LCFFDM/300/LED | Candle, Warm White, 3000K, 300 Lumen, E12 base, frosted flame tip |
| | 4.8W | LEFCDM/300/LED | Candle, 3000K, 310 Lumen, E26, Flame tip, clear |
| | 4.8W | LG161/2DM/CL/300/LED | G16.5, Warm White, 3000K, 300 Lumen, E12 base, clear |
| | 8W | LG25DM/LEDG2† | G25, Warm White, 3000K, 510 Lumen, E26 |
| | 16W | LBR40DMLEDG2 | BR40, 2700K, 1065 Lumen |
| | 4.8W | LG161/2DM/IF/300/LED | G16.5, Warm White, 3000K, 300 Lumen, E12 base, frosted |
| | 4.8W | LGMDM/CL/300/LED | G16.5, Warm White, 3000K, 300 Lumen, E26, clear |
| | 6.5W | LMR16/GU10/DM/LED† | MR16, GU10 base |
| | 6.5W | LMR16DMGU10† | MR16, GU10 base |
| | 6.5W | LR16DMLED | R16, Soft White, 2700K, 400 Lumen, E26, 40WE |

† Requires a minimum of 2 lamps

© 02/2015 Lutron Electronics Co., Inc. | P/N 368-3266 REV I

Dimmable CFL & LED bulbs

Compatible with C·L® dimmers



LED bulbs for Maestro Wireless® C·L dimmers

Maestro Wireless: MRF2-6CL

More bulbs coming soon for Maestro Wireless C·L Dimmers

Maximum wattage controlled: 150W



| Brand | Wattage | Model | Description |
|-----------|---------|------------------|---|
| Utilitech | 13W | LBR30DM/LEDG2 | BR30 |
| | 13.5W | LA19/OM800/LED† | A19, 3000K, 800 Lumen, Omni Directional |
| | 16W | LBR40DMLEDG2† | BR40, 2700K, 1065 Lumen |
| | 17W | BPCEBR40/DM/LED† | BR40 |
| | 17W | LBR40DM/LED† | BR40, 2700K, 1065 Lumen |
| | 20W | L20PAR38/LEDG5 | PAR38, 3000K, 1000 Lumen, flood |
| | 20W | LPAR38/5K/LEDG5 | PAR38, 5000K, 1000 Lumen, flood |
| | 20W | LPAR38/LEDG5 | PAR38, 3000K, 1000 Lumen, flood |
| | 20W | LPAR38DM/SP/LED | PAR38, 3000K, 1000 Lumen, Spot |

† Requires a minimum of 2 lamps

© 02/2015 Lutron Electronics Co., Inc. | P/N 368-3266 REV I

Dimmable CFL & LED bulbs

Compatible with C·L® dimmers



CFL bulbs* for Maestro Wireless® C·L dimmers

Maestro Wireless: MRF2-6CL

Maximum wattage controlled: 150W



| Brand | Wattage | Model | Description |
|------------|---------|------------------|--------------------|
| GE | 26W | FLE26HT3/2/DV/SW | Spiral |
| TCP | 14W | 4R2014TD | R20, TruDim, 2700K |
| | 14W | 4R2014TD30K | R20, TruDim, 3000K |
| | 14W | 4R2014TD35K | R20, TruDim, 3500K |
| | 14W | 4R2014TD41K | R20, TruDim, 4100K |
| | 14W | 4R2014TD50K | R20, TruDim, 5000K |
| | 14W | 4R2014TD65K | R20, TruDim, 6500K |

* CFLs typically require a warmup period before their full dimming range is achieved.

© 02/2015 Lutron Electronics Co., Inc. | P/N 368-3266 REV I

Dimmable CFL & LED bulbs

Compatible with C·L® dimmers



LED bulbs for Caséta® Wireless in-wall dimmer

PD-6WCL

Maximum wattage controlled: 150W



| Brand | Wattage | Model number | Description |
|----------|------------------------------|--|--|
| Cree | 9W | BA19-08050OMF-12DE26-1U100 | A19, Daylight, 5000K, 800 Lumen, Medium base |
| | 9W | BA19-08050OMF-12DE26-2U100 | A19, Daylight, 5000K, 800 Lumen, Medium base |
| | 9.5W | BA19-08027OMF-12DE26-2U100 | A19, Soft White, 2700K, 800 Lumen, Medium base |
| | 9.5W | BA19-08027OMF-12DE26-2U500 | A19, 2700K, 800 Lumen, E26, 60WE, 4pk |
| | 9.5W | CR4-575L | 4" Downlight, 2700K, 575 Lumen, Medium Base |
| | 9.5W | CR6-575L | 6" Downlight, 2700K, Medium Base |
| | 9.5W | CR6-575L-GU24 | 6" Downlight, 2700K, GU24 Base |
| | 9.5W | H1CR6TW62527E04 | 6" Downlight, 2700K, 625 Lumen |
| | 18W | BA21-16027OMF-12DE26-1U100 | A21, 2700K, 1600 Lumen, E26, 18W |
| | 18W | BA21-16050OMF-12DE26-1U100 | A21, 5000K, 1600 Lumen, E26, 18W |
| EcoSmart | 8W | ECS 19 CW 120 | A19, Cool White, 5000K |
| | 8W | ECS 19 WW 120 | A19, Warm White, 3000K |
| | 8W | ECS 20 CW FL 50WE 120 | PAR20, 5000K, 490 Lumen |
| | 8W | ECS 20 WW FL 50WE 120 | PAR20, 3000K, 450 Lumen |
| | 9.5W | ECO4-575L | 4" Downlight, 2700K, 575 Lumen, Medium Base |
| | 9.5W | ECO4-575L-50K | 4" Downlight, 5000K, 575 Lumen, Medium Base |
| | 9.5W | ECO4-575L-50K-GU24 | 4" Downlight, 5000K, GU24 Base |
| | 9.5W | ECO-575L | 6" Downlight, 2700K, Medium Base |
| | 9.5W | ECO-575L-50K | 6" Downlight, 5000K, Medium Base |
| | 9.5W | ECO-575L-50K-GU24 | 6" Downlight, 5000K, GU24 Base |
| | 9.5W | ECO-575L-GU24 | 6" Downlight, 2700K, GU24 Base |
| | 10W | ECS BR30 65WE CW 120 DG | BR30, Daylight, 5000K, 700 Lumen, E26 |
| | 10W | ECS BR30 65WE CW 120 DG 3PK | BR30, Daylight, 5000K, 700 Lumen, E26, 3pk |
| | 10W | ECS BR30 65WE WW 120 DG | BR30, Warm White, 3000K, 650 Lumen, E26 |
| | 10W | ECS BR30 65WE W27 120 DG | BR30, Soft White, 2700K, 650 Lumen, E26 |
| 10W | ECS BR30 65WE W27 120 DG 3BX | BR30, Soft White, 2700K, 650 Lumen, E26, 3pk | |

† Requires a minimum of 2 lamps

© 02/2015 Lutron Electronics Co., Inc. | P/N 368-3266 REV I

Dimmable CFL & LED bulbs

Compatible with C·L® dimmers



LED bulbs for Caséta® Wireless in-wall dimmer

PD-6WCL

Maximum wattage controlled: 150W



| Brand | Wattage | Model number | Description |
|-----------------|--------------|---------------------------------------|---|
| EcoSmart | 10.5W | ECS 30 75WE WW GB FL 120 | PAR30 Gimbal, 3000K, 750 Lumen, E26, 75WE |
| | 11.5W | ECS BR30 65WE CW 120 | BR30, 5000K, Medium Base |
| | 11.5W | ECS BR30 65WE W27 120 | BR30, 2700K, 650 Lumen, Medium Base |
| | 14W | ECS BR40 90WE CW 120 DG | BR40, Daylight, 5000K, 1050 Lumen, E26 |
| | 14W | ECS BR40 90WE W27 120 DG | BR40, 2700K, 1000 Lumen, E26 |
| | 15W | ECS BR30 W27 FL 120 | BR30, Soft White, 2700K |
| | 24W | ECS 38 V2 WW FL 120 | PAR38, Warm White, 3000K |
| Feit | 4.5W | R14DM/LED | R14, Soft White, 2700K, 300 Lumen, E26, 40WE |
| | 5W | MR16/GU10/DM/LED† | MR16, GU10 Base |
| | 6.5W | BPMR16/GU10/DM/LED† | MR16, GU10 base |
| | 6.5W | MR16/GU10/DM/LED† | MR16, GU10 base |
| | 6.5W | R16DM/LED† | R16, Soft White, 2700K, 400 Lumen, E26, 40WE |
| | 7.5W | PAR20DM/5K/LED† | PAR20, 5000K |
| | 7.5W | PAR20DM/LED† | PAR20, 3000K |
| | 8W | BPCER20/DM/LED | R20, 2700K, 450 Lumen, E26 Medium base (70 mA smooth reflector version) |
| | 8W | R20/927/LED | R20, 2700K |
| | 8W | R20/930/LED | R20, 3000K |
| | 8W | R20/950/LED | R20, 5000K |
| | 8W | R20DM/LEDG2/CAN | R20, 2700K |
| | 13W | BPCEBR30LED | BR30 |
| | 13.5W | A19/OM800/5K/LED | A19, 5000K, Omni Directional |
| | 13.5W | A19/OM800/LED | A19, 3000K, Omni Directional |
| | 13.5W | BPCEA19/OM800/LED | A19, Omni Directional |
| | 13.5W | BPCEA19/OM800/LED/CAN | A19, Omni Directional |
| 17W | BR40/DM/LED† | BR40, 2700K, 1065 Lumen | |
| 20.5W | LEDR56/827 | 5" or 6" Downlight, 2700K, 1245 Lumen | |
| GE | 8W | LED8DA19/827 | A19, 2700K, 450 Lumen, E26 |
| | 14W | LED14DA21V2/827W | A21, 2700K, 1100 Lumen, E26 |

† Requires a minimum of 2 lamps

© 02/2015 Lutron Electronics Co., Inc. | P/N 368-3266 REV I

Dimmable CFL & LED bulbs

Compatible with C-L® dimmers



LED bulbs for Caséta® Wireless in-wall dimmer

PD-6WCL

Maximum wattage controlled: 150W



| Brand | Wattage | Model number | Description |
|------------------|----------------------|---------------------------|--|
| Lighting Science | 8W | DFN 19 CW 120 | A19, Cool White, 5000K |
| | 8W | DFN 19 NW 120 | A19, Neutral White, 4000K |
| | 8W | DFN 19 W27 120 | A19, Warm White, 2700K |
| | 8W | DFN 19 WW 120 | A19, Warm White, 3000K |
| | 10.5W | LS 30 75WE xxx GB xx 120* | PAR30, various color temperatures |
| | 11.5W | DFN BR30 65WE CW 120 | BR30, Cool White, 5000K, Medium base |
| | 11.5W | DFN BR30 65WE NW 120 | BR30, Neutral White, 4000K, Medium base |
| | 11.5W | DFN BR30 65WE W27 120 | BR30, Warm White, 2700K, Medium base |
| | 11.5W | DFN BR30 65WE WW 120 | BR30, Warm White, 3000K, Medium base |
| | 13W | LS GLP6 W27 120 WH S1 BX | 6" Downlight, 2700K, E26 retrofit |
| | 15W | DFN BR30 CW FL 120 | BR30, Cool White, 5000K |
| | 15W | DFN BR30 NW FL 120 | BR30, Neutral White, 4000K |
| | 15W | DFN BR30 W27 FL 120 | BR30, Warm White, 2700K |
| | 15W | DFN BR30 WW FL 120 | BR30, Warm White, 3000K |
| | 24W | DFN 38 CW V2 FL 120 | PAR38, Cool White, 5000K |
| | 24W | DFN 38 CW V2 NFL 120 | PAR38, Cool White, 5000K |
| | 24W | DFN 38 NW V2 FL 120 | PAR38, Neutral White, 4000K |
| | 24W | DFN 38 NW V2 NFL 120 | PAR38, Neutral White, 4000K |
| | 24W | DFN 38 W27 V2 FL 120 | PAR38, Warm White, 2700K |
| | 24W | DFN 38 W27 V2 NFL 120 | PAR38, Warm White, 2700K |
| 24W | DFN 38 WW V2 FL 120 | PAR38, Warm White, 3000K | |
| 24W | DFN 38 WW V2 NFL 120 | PAR38, Warm White, 3000K | |
| Lumapro | 8W | 8A19/LED/DIM/30 | A19, Warm White, 3000K (6GEM2) |
| | 8W | 8A19/LED/DIM/50 | A19, Cool White, 5000K (6GEM3) |
| Philips | 4W | 9290002120 | MR16, Bright White, 3000K, 200 Lumen, GU10, 4W |
| | 4.5W | 9290002439 | Candle, Warm White, 2700K, 320 Lumen, E26 base, Post Light |
| | 4.5W | 9290002797 ^{††} | Candle, 2700K, 330 Lumen, E26, blunt tip |
| | 4.5W | 9290002889 ^{††} | Candle, 2700K, 330 Lumen, E12, blunt tip |
| | 4.5W | 9290002890 ^{††} | A15, 2700K, 330 Lumen, E12 |
| | 4.5W | 9290002891 ^{††} | A15, 2700K, 330 Lumen, E26 |
| | 6W | 9290002242 | MR16, 3000K, 300 Lumen, GU10 base |

* "xx" and "xxx" denote other characters which may be included in the model number.

^{††} Requires a minimum of 3 lamps

© 02/2015 Lutron Electronics Co., Inc. | P/N 368-3266 REV I

Dimmable CFL & LED bulbs

Compatible with C·L® dimmers



LED bulbs for Caséta® Wireless in-wall dimmer

PD-6WCL

Maximum wattage controlled: 150W



| Brand | Wattage | Model number | Description | |
|---------|---------|--------------|---|-------------------------|
| Philips | 7W | 9290002706 | A19 SlimStyle, Daylight, 5000K, 450 Lumen, E26 | |
| | 8W | 9290002267 | A19, 2700K, 470 Lumen | |
| | 8W | 9290002295 | A19, 5000K, 470 Lumen | |
| | 8W | 9290002329 | PAR20, 3000K, 470 Lumen, E26 | |
| | 8.5W | 9290002543 | BR30, 5000K, 730 Lumen, 8.5W | |
| | 9.5W | 9290011117 | BR30, 2700K, 730 Lumen, WarmGlow to 2200K (Nov 2014 or later) | |
| | 9.5W | 9290011118 | BR30 SlimStyle, 2700K, 650 Lumen, E26, 65WE | |
| | 9.5W | 9290011119 | BR30 SlimStyle, 5000K, 650 Lumen, E26, 65WE | |
| | 10.5W | 9290002544 | BR30, 2700K, 730 Lumen | |
| | 11W | 9290002268 | A19, 2700K, 830 Lumen | |
| | 11W | 9290002296 | A19, 5000K, 830 Lumen | |
| | 11W | 9290011113 | PAR30L, 3000K, E26 | |
| | 13W | 9290002233 | PAR30, 2700K, 784 Lumen | |
| | 13W | 9290002234 | PAR30, 2700K, 770 Lumen | |
| | 13W | 9290002201 | PAR30, 3000K, 750 Lumen | |
| | 13W | 9290002323 | PAR30, 5000K, 850 Lumen | |
| | 13W | 9290002523 | 13PAR38/F25 3000 DIM AF RO | PAR38, 3000K, 950 Lumen |
| | 14.5W | 9290002199 | BR40, 2700K, 800 Lumen | |
| | 15W | 9290002595 | A21, Soft White, 2700K, 1180 Lumen, E26 | |
| | 15W | 9290011111 | PAR38, 3000K, 1050 Lumen, E26, Flood | |
| | 15W | 9290011112 | PAR38, 5000K, 1050 Lumen, E26, Flood | |
| | 17W | 9290002018† | A21, 2700K | |
| | 17W | 17E26A21D† | A21, 2700K | |
| | 18W | 9290002202 | PAR38, 3000K, 951 Lumen, Medium Base | |
| | 18W | 9290002236 | PAR38 | |
| | 18W | 9290002237 | PAR38 | |
| | 18W | 9290002245 | PAR38, 2700K, 938 Lumen | |
| | 18W | 9290002246 | PAR38 | |
| | 18W | 9290002307 | PAR38 | |
| | 18W | 9290002308 | PAR38 | |

† Requires a minimum of 2 lamps

© 02/2015 Lutron Electronics Co., Inc. | P/N 368-3266 REV I

Dimmable CFL & LED bulbs

Compatible with C·L® dimmers



LED bulbs for Caséta® Wireless in-wall dimmer

PD-6WCL

Maximum wattage controlled: 150W



| Brand | Wattage | Model number | Description |
|----------------|---------------------|-------------------------------|--|
| Philips | 18W | 9290002309 | PAR38 |
| | 18W | 9290002310 | PAR38 |
| | 18W | 9290002311 | PAR38 |
| | 18W | 18E26PAR38-3 | PAR38 |
| | 18W | 18E26PAR38-4 | PAR38 |
| Samsung | 7W | STIPLW8300711AB | SI-P8V071AB0US |
| Satco | 11W | S9084 | PAR30, 3000K, 780 Lumen, E26, short neck, 25° Beam |
| | 11W | S9085 | PAR30, 4000K, 780 Lumen, E26, short neck, 25° Beam |
| | 11W | S9086 | PAR30, 3000K, 780 Lumen, E26, short neck, 40° Beam |
| | 11W | S9087 | PAR30, 4000K, 780 Lumen, E26, short neck, 40° Beam |
| | 11W | S9088 | PAR30, 3000K, 780 Lumen, E26, long neck, 25° Beam |
| | 11W | S9089 | PAR30, 4000K, 780 Lumen, E26, long neck, 25° Beam |
| | 11W | S9090 | PAR30, 3000K, 780 Lumen, E26, long neck, 40° Beam |
| | 11W | S9091 | PAR30, 4000K, 780 Lumen, E26, long neck, 40° Beam |
| | 17W | S9092 | PAR38, 3000K, 1200 Lumen, E26, 25° beam |
| | 17W | S9093 | PAR38, 4000K, 1200 Lumen, E26, 25° beam |
| | 17W | S9094 | PAR38, 3000K, 1200 Lumen, E26, 40° beam |
| | 17W | S9095 | PAR38, 4000K, 1200 Lumen, E26, 40° beam |
| | 28W | LR38/15/27K/2000/xx | PAR38, 2700K, 2000 Lumen, E26 |
| | 28W | LR38/15/30K/2100/xx | PAR38, 3000K, 2100 Lumen, E26 |
| 28W | LR38/25/27K/2000/xx | PAR38, 2700K, 2000 Lumen, E26 | |
| Satco | 28W | LR38/25/30K/2100/xx | PAR38, 3000K, 2100 Lumen, E26 |
| | 28W | LR38/40/27K/2000/xx | PAR38, 2700K, 2000 Lumen, E26 |
| | 28W | LR38/40/30K/2100/xx | PAR38, 3000K, 2100 Lumen, E26 |

Dimmable CFL & LED bulbs

Compatible with C·L® dimmers



LED bulbs for Caséta® Wireless in-wall dimmer

PD-6WCL

Maximum wattage controlled: 150W



| Brand | Wattage | Model number | Description |
|--------|---------|---------------------|---|
| Solais | 7W | LRP20/25/27K | PAR20, 2700K, 475 Lumen, E26, 25° Beam |
| | 7W | LRP20/25/30K | PAR20, 3000K, 500 Lumen, E26, 25° Beam |
| | 7W | LRP20/40/27K | PAR20, 2700K, 475 Lumen, E26, 40° Beam |
| | 7W | LRP20/40/30K | PAR20, 3000K, 500 Lumen, E26, 40° Beam |
| | 11W | LR20/25/27K/675/xx | PAR20, 2700K, 675 Lumen, E26, narrow flood |
| | 11W | LR20/25/30K/750 | PAR20, 3000K, 750 Lumen, E26, narrow flood |
| | 11W | LR20/40/27K/675/xx | PAR20, 2700K, 675 Lumen, E26, wide flood |
| | 11W | LR20/40/30K/750/xx | PAR20, 3000K, 750 Lumen, E26, wide flood |
| | 16W | LR30/10/27K/1100/xx | PAR30, 2700K, 1100 Lumen, E26, short neck, 10° Beam |
| | 16W | LR30/10/30K/1125/xx | PAR30, 3000K, 1125 Lumen, E26, short neck, 10° Beam |
| | 16W | LR30/10/30K/1200/xx | PAR30, 3000K, 1200 Lumen, E26, short neck, 10° Beam |
| | 16W | LR30/15/27K/1100/xx | PAR30, 2700K, 1100 Lumen, E26, short neck, 15° Beam |
| | 16W | LR30/15/30K/1125/xx | PAR30, 3000K, 1125 Lumen, E26, short neck, 15° Beam |
| | 16W | LR30/15/30K/1200/xx | PAR30, 3000K, 1200 Lumen, E26, short neck, 15° Beam |
| | 16W | LR30/25/27K/1100/xx | PAR30, 2700K, 1100 Lumen, E26, short neck, 25° Beam |
| | 16W | LR30/25/30K/1125/xx | PAR30, 3000K, 1125 Lumen, E26, short neck, 25° Beam |
| | 16W | LR30/25/30K/1200/WH | PAR30, 3000K, 1200 Lumen, E26, short neck, 25° Beam |
| | 16W | LR30/40/27K/1100/xx | PAR30, 2700K, 1100 Lumen, E26, short neck, 40° Beam |
| | 16W | LR30/40/30K/1125/xx | PAR30, 3000K, 1125 Lumen, E26, short neck, 40° Beam |
| | 16W | LR30/40/30K/1200/xx | PAR30, 3000K, 1200 Lumen, E26, short neck, 40° Beam |

Dimmable CFL & LED bulbs

Compatible with C·L® dimmers



LED bulbs for Caséta® Wireless in-wall dimmer

PD-6WCL

Maximum wattage controlled: 150W



| Brand | Wattage | Model number | Description |
|------------------|--------------------------------|--|--|
| Solais | 16W | LRP38/25/27K | PAR38, 2700K, 1025 Lumen, E26, 25° Beam |
| | 16W | LRP38/25/30K | PAR38, 3000K, 1100 Lumen, E26, 25° Beam |
| | 16W | LRP38/40/27K | PAR38, 2700K, 1025 Lumen, E26, 40° Beam |
| | 16W | LRP38/40/30K | PAR38, 3000K, 1100 Lumen, E26, 40° Beam |
| | 20W | LR38/25/30K/1450/SL | PAR38, 3000K, 1450 Lumen, E26, 15° Beam |
| Sylvania | 8W | LED8A/DIM/F/827 | A19, 2700K |
| | 8W | LED8A/DIM/F/830 | A19, 3000K |
| | 8W | LED8A19DIMO827RP | A19, 2700K, 470 Lumen, E26 |
| | 8W | LED8PAR16/DIM/930/FL36/P/LW | PAR16, Soft White, 390 Lumen |
| | 8W | LED8PAR16/GU10/DIM/930/FL36/RP | PAR16, GU10, Soft White, 390 Lumen |
| | 9W | LED/550/RT4/827/FL80/WRFL | 4" Downlight, 2700K |
| | 9W | LED/550/RT4/830/FL80/WRFL | 4" Downlight, 3000K |
| | 11W | LED11PAR20/DIM/930/FL30/P2 | PAR20, Soft White, 550 Lumen |
| | 12W | LED12BR30/DIM/HO/827 | BR30, 2700K, Medium base |
| | 12W | LED12BR30/DIM/HO/827/HVP | BR30, 2700K, Medium base |
| | 14W | 79084 | A19, Soft White, 2700K, 1100 Lumen, E26 |
| | 17W | LED17PAR30LN/DIM/830/WSP15/P | PAR30, 3000K, 1200 Lumen, E26, spot |
| | 17W | LED17PAR30LN/DIM/830/WSP20 | PAR30, 3000K, 1200 Lumen, E26, wide spot |
| | 17W | LED17PAR30LN/DIM/P/930/NFL25† | PAR30, 3000K, 900 Lumen |
| | 20W | LED20PAR38/DIM/930/FL40/P2 | PAR38, 3000K, 1000 Lumen |
| 21W | LED21/PAR38/DIM/P/930/FL30/HVP | PAR38, Warm White, 3000K, 1100 Lumen, E26, 21W | |
| 21W | LED21PAR38/DIM/P/930/FL30 | PAR38, 3000K, 1100 Lumen | |
| Utilitech | 3W | LG161/2DM/IF/LED† | G16.5, Warm White, 3000K, 200 Lumen, E12 base, frosted |
| | 4.5W | LR14DMLED | R14, Soft White, 2700K, 300 Lumen, E26, 40WE |
| | 4.8W | LA15DM/CL/300/LED† | A15, Warm White, 3000K, 300 Lumen, E26, clear |
| | 4.8W | LA15DM/IF/300/LED† | A15, Warm White, 3000K, 300 Lumen, E26, frosted |
| | 4.8W | LA15DMC/CL/300/LED† | A15, Warm White, 3000K, 300 Lumen, E12 base, clear |

† Requires a minimum of 2 lamps

© 02/2015 Lutron Electronics Co., Inc. | P/N 368-3266 REV I

Dimmable CFL & LED bulbs

Compatible with C·L® dimmers



LED bulbs for Caséta® Wireless in-wall dimmer

PD-6WCL

Maximum wattage controlled: 150W



| Brand | Wattage | Model number | Description |
|--------------|------------------|-------------------------|--|
| Utilitech | 4.8W | LCFCDM/300/LED† | Candle, 3000K, 310 Lumen, E26, flame tip, clear |
| | 4.8W | LCFFDM/300/LED† | Candle, Warm White, 3000K, 300 Lumen, E12 base, frosted flame tip |
| | 4.8W | LEFCDM/300/LED† | Candle, 3000K, 310 Lumen, E26, Flame tip, clear |
| | 4.8W | LG161/2DM/CL/300/LED† | G16.5, Warm White, 3000K, 300 Lumen, E12 base, clear |
| | 4.8W | LG161/2DM/IF/300/LED† | G16.5, Warm White, 3000K, 300 Lumen, E12 base, frosted |
| | 4.8W | LGMDM/CL/300/LED† | G16.5, Warm White, 3000K, 300 Lumen, E26, clear |
| | 5W | LMR16GU10DM/LED† | MR16, GU10 Base |
| | 6.5W | LMR16/GU10/DM/LED† | MR16, GU10 base |
| | 6.5W | LMR16DMGU10† | MR16, GU10 base |
| | 6.5W | LR16DMLED† | R16, Soft White, 2700K, 400 Lumen, E26, 40WE |
| | 7.5W | LPAR20DM/5K/LED† | PAR20, 5000K |
| | 7.5W | LPAR20DM/LED† | PAR20, 3000K |
| | 8W | LR20DMLEDG2 | R20, 2700K, 450 Lumen, E26 Medium base (70mA smooth reflector version) |
| | 8W | LG25DM/LEDG2† | G25, Warm White, 3000K, 510 Lumen, E26 |
| | 11W | DLS02-41127D1E-WF1 | 4" Downlight, Soft White, 2700K, 650 Lumen, E26 retrofit |
| | 13W | DLS02-61327D1E-WF1 | 5" or 6" Downlight, Soft White, 2700K, 800 Lumen, E26 retrofit |
| | 13W | DLS02-61350D1E-WF1 | 5" or 6" Downlight, Daylight, 5000K, 800 Lumen, E26 retrofit |
| | 13W | LBR30DM/LEDG2 | BR30 |
| | 13.5W | LA19/OM800/LED | A19, 3000K, 800 Lumen, Omni Directional |
| | 16W | LBR40DMLEDG2† | BR40, 2700K, 1065 Lumen |
| 17W | BPCEBR40/DM/LED† | BR40 | |
| 17W | LBR40DM/LED† | BR40, 2700K, 1065 Lumen | |
| Westinghouse | 8W | 8A19/LED/DIM/30 | A19, Warm White, 3000K |
| | 8W | 8A19/LED/DIM/50 | A19, Cool White, 5000K |

† Requires a minimum of 2 lamps

© 02/2015 Lutron Electronics Co., Inc. | P/N 368-3266 REV I

Dimmable CFL & LED bulbs

Compatible with C·L® dimmers



CFL bulbs* for Caséta® Wireless in-wall dimmer

PD-6WCL

Maximum wattage controlled: 150W



| Brand | Wattage | Model | Description |
|------------|---------|------------------|--------------------|
| GE | 26W | FLE26HT3/2/DV/SW | Spiral |
| | 14W | 4R2014TD | R20, TruDim, 2700K |
| TCP | 14W | 4R2014TD30K | R20, TruDim, 3000K |
| | 14W | 4R2014TD35K | R20, TruDim, 3500K |
| | 14W | 4R2014TD41K | R20, TruDim, 4100K |
| | 14W | 4R2014TD50K | R20, TruDim, 5000K |
| | 14W | 4R2014TD65K | R20, TruDim, 6500K |
| | 14W | 4R2014TD65K | R20, TruDim, 6500K |

* CFLs typically require a warmup period before their full dimming range is achieved.

© 02/2015 Lutron Electronics Co., Inc. | P/N 368-3266 REV I

Dimmable CFL & LED bulbs

Compatible with C·L® dimmers



LED bulbs for Caséta® Wireless plug-in dimmer

PD-3PCL

Maximum wattage controlled: 100W



| Brand | Wattage | Model number | Description |
|----------|---------|----------------------------|---|
| Cree | 6W | BA19-04527OMF-12DE26-1U100 | A19, Warm Soft White, 2700K, 450 Lumen, Medium base |
| | 6W | BA19-04527OMF-12DE26-2U100 | A19, Warm Soft White, 2700K, 450 Lumen, Medium base |
| | 6W | BA19-04550OMF-12DE26-2U500 | A19, 5000K, 450 Lumen, 40WE, 4pk |
| | 9W | BA19-08050OMF-12DE26-1U100 | A19, Daylight, 5000K, 800 Lumen, Medium base |
| | 9W | BA19-08050OMF-12DE26-2U100 | A19, Daylight, 5000K, 800 Lumen, Medium base |
| | 9.5W | BA19-08027OMF-12DE26-2U100 | A19, Soft White, 2700K, 800 Lumen, Medium base |
| | 9.5W | BA19-08027OMF-12DE26-2U500 | A19, 2700K, 800 Lumen, E26, 60WE, 4pk |
| | 18W | BA21-16027OMF-12DE26-1U100 | A21, 2700K, 1600 Lumen, E26, 18W |
| | 18W | BA21-16050OMF-12DE26-1U100 | A21, 5000K, 1600 Lumen, E26, 18W |
| EcoSmart | 8W | ECS 19 CW 120 | A19, Cool White, 5000K |
| | 8W | ECS 19 WW 120 | A19, Warm White, 3000K |
| Feit | 7.5W | PAR20DM/5K/LED† | PAR20, 5000K |
| | 7.5W | PAR20DM/LED† | PAR20, 3000K |
| | 9.5W | BPCER20/DM/LED | PAR20 |
| | 9.5W | PAR20/5K/LEDG5 | PAR20, 5000K |
| | 9.5W | PAR20/5K/LEDG5/CAN | PAR20, 5000K |
| | 9.5W | PAR20/LEDG5 | PAR20, 3000K, 450 Lumen |
| | 9.5W | PAR20/LEDG5/CAN | PAR20 |
| | 10W | G25/DM/LED | G25, 3000K |
| | 13.5W | A19/OM800/5K/LED | A19, 5000K, Omni Directional |
| | 13.5W | A19/OM800/LED | A19, 3000K, Omni Directional |
| | 13.5W | BPCEA19/OM800/LED | A19, Omni Directional |
| | 13.5W | BPCEA19/OM800/LED/CAN | A19, Omni Directional |
| GE | 18W | LED18D38W827/15 | PAR38, 2700K, E26, 15° Beam |
| | 18W | LED18D38W827/25 | PAR38, 2700K, E26, 25° Beam |
| | 18W | LED18D38W827/40 | PAR38, 2700K, E26, 40° Beam |
| | 18W | LED18D38W830/15 | PAR38, 3000K, 1400 Lumen, E26, 15° Beam |
| | 18W | LED18D38W830/25 | PAR38, 3000K, 1400 Lumen, E26, 25° Beam |

† Requires a minimum of 2 lamps

© 02/2015 Lutron Electronics Co., Inc. | P/N 368-3266 REV I

Dimmable CFL & LED bulbs

Compatible with C·L[®] dimmers



LED bulbs for Caséta[®] Wireless plug-in dimmer

PD-3PCL

Maximum wattage controlled: 100W



| Brand | Wattage | Model number | Description |
|------------------|---------|------------------------------|---|
| GE | 18W | LED18D38W830/40 | PAR38, 3000K, 1400 Lumen, E26, 40° Beam |
| | 18W | LED18D38W927/15 | PAR38, 2700K, 1100 Lumen, E26, 15° Beam |
| | 18W | LED18D38W927/25 | PAR38, 2700K, 1100 Lumen, E26, 25° Beam |
| | 18W | LED18D38W927/40 | PAR38, 2700K, 1100 Lumen, E26, 40° Beam |
| | 18W | LED18D38W930/15 | PAR38, 3000K, 1200 Lumen, E26, 15° Beam |
| | 18W | LED18D38W930/25 | PAR38, 3000K, 1200 Lumen, E26, 25° Beam |
| | 18W | LED18D38W930/40 | PAR38, 3000K, 1200 Lumen, E26, 40° Beam |
| Lighting Science | 8W | DFN 19 CW 120 | A19, Cool White, 5000K |
| | 8W | DFN 19 NW 120 | A19, Neutral White, 4000K |
| | 8W | DFN 19 W27 120 | A19, Warm White, 2700K |
| | 8W | DFN 19 WW 120 | A19, Warm White, 3000K |
| Lumapro | 8W | 8A19/LED/DIM/30 | A19, Warm White, 3000K (6GEM2) |
| | 8W | 8A19/LED/DIM/50 | A19, Cool White, 5000K (6GEM3) |
| Philips | 8W | 9290002267 | A19, 2700K, 470 Lumen |
| | 8W | 9290002295 | A19, 5000K, 470 Lumen |
| | 11W | 9290002268 | A19, 2700K, 830 Lumen |
| | 11W | 9290002296 | A19, 5000K, 830 Lumen |
| | 14.5W | 9290002199 | BR40, 2700K, 800 Lumen |
| | 15W | 9290002595 | A21, Soft White, 2700K, 1180 Lumen, E26 |
| | 17W | 9290002018 | A21, 2700K |
| Samsung | 7W | STIPLW8300711AB | SI-P8V071AB0US |
| | 10.5W | S9037 | A19, 2700K, 810 Lumen, E26 |
| Satco | 10.5W | S9038 | A19, 3500K, 830 Lumen, E26 |
| | 10.5W | S9039 | A19, 5000K, 870 Lumen, E26 |
| | 8W | LED8A/DIM/F/827 | A19, 2700K |
| Sylvania | 8W | LED8A/DIM/F/830 | A19, 3000K |
| | 8W | LED8A19DIMO827RP | A19, 2700K, 470 Lumen, E26 |
| | 7.5W | LA19DM/LEDG2 | A19, 3000K, 450 Lumen |
| Utilitech | 7.5W | LPAR20DM/5K/LED [†] | PAR20, 5000K |
| | 7.5W | LPAR20DM/LED [†] | PAR20, 3000K |
| | 8W | LG25DM/LEDG2 | G25, Warm White, 3000K, 510 Lumen, E26 |
| | | | |

[†] Requires a minimum of 2 lamps

© 02/2015 Lutron Electronics Co., Inc. | P/N 368-3266 REV I

Dimmable CFL & LED bulbs

Compatible with C·L® dimmers



LED bulbs for Caséta® Wireless plug-in dimmer

PD-3PCL

Maximum wattage controlled: 100W



| Brand | Wattage | Model number | Description |
|--------------|---------|-----------------|---|
| Utilitech | 9.5W | LPAR20/5K/LEDG5 | PAR20, 5000K, 500 Lumen |
| | 9.5W | LPAR20/LEDG5 | PAR20, 3000K, 450 Lumen |
| | 9.5W | LPAR20DM/SP/LED | PAR20, 3000K, 465 Lumen, Spot |
| | 10W | LG25/DM/LED | G25, 3000K |
| | 13.5W | LA19/OM800/LED | A19, 3000K, 800 Lumen, Omni Directional |
| Westinghouse | 8W | 8A19/LED/DIM/30 | A19, Warm White, 3000K |
| | 8W | 8A19/LED/DIM/50 | A19, Cool White, 5000K |



CFL bulbs* for Caséta Wireless plug-in dimmer

PD-3PCL

Maximum wattage controlled: 100W



| Brand | Wattage | Model | Description |
|-------|---------|------------------|-------------|
| GE | 26W | FLE26HT3/2/DV/SW | Spiral |

* CFLs typically require a warmup period before their full dimming range is achieved.