

SPECIFICATION SHEET



Elements Resilient Sheet Flooring

March 26, 2012

PRODUCT SPECIFICATIONS

Series:	L2XXX
Wearlayer:	Urethane (Low Gloss)
Nominal Wearlayer Thickness:	.010" (0.25mm)
Nominal Total Thickness:	.065" (1.6mm)
Widths:	12' (3.6m)
Maximum Roll Size (Sq. Yds.):	128 (107 m ²)
Weight per Sq. Yd. (Lbs.):	2.32 (1.26 kg)
ASTM F-970 Static Load Limit:	75 lbs/in ² (5.27 kg/cm ²)
ASTM F 1303:	Type I, Grade 3, Class A
HUD/FHA Minimum Property Standards:	Meets Wearlayer Thickness Requirement

INSTALLATION

Use:	Residential.
Installation System:	Full Spread.
Location:	Below, on and above grade concrete, approved underlayment grade plywood and approved existing floors.
Seam Method:	Double-cut wet.

- Keep material rolled face out on a sturdy core until time of installation.
- Room temperature, flooring and adhesive shall be maintained between 65° - 85° F for 48 hours before, during and after installation.
- Use only cementitious based patching and leveling compounds.
- Do not contaminate seam edges with adhesive.
- Roll flooring in both directions with a 75-100 lb. (34-45kg) sectional floor roller.
- Protect sealed seams from all traffic for a minimum of 8 hours.

PATTERN MATCH

• Vermont Slate	L2001	36" x 28.8", 14.4" drop, Do Not Reverse
• French Parquet	L2011	36" x 36", 1/2 drop, Do Not Reverse
• Cambridge Modular	L2021	48" x 48", 38.5" drop, Do Not Reverse
• Sonorus	L2031	36" x 36", 1/2 drop, Do Not Reverse

CARE AND MAINTENANCE

- Do not replace frequently moved furniture or allow heavy traffic for at least 24 hours.
- Never slide heavy furniture or appliances across the floor. Place plywood on the floor and move the object across the plywood.
- To minimize scratching and indentations, equip tables and chairs with proper floor protectors.
- Sweep or vacuum to remove loose dirt or debris that can scratch the floor.
- Wash floor with a neutral floor cleaner designed for resilient flooring.
- The use of non-staining mats can remove dirt and debris in the entryways and help prolong the life of the floor.
- Maintain post installation temperature between 55° F and 100° F. Maintain relative humidity between 40% and 70%.

WARRANTY

- 15 Year Wear and Manufacturing Defects.



THE ULTIMATE
FLOORING EXPERIENCE